

LTR 6140 TWIN



**LAMTRAC**



Note: The specifications are given under ideal conditions and on the basis of adequate operator skill and ability.

## Features

Cummins QSB 4.5 Tier III  
Single Boom Arm  
86% Peripheral Visibility  
Side Door Entry  
Double Escape Hatch (Ingress & Egress)

Features Video



Operation Video



## Dimensions

Track Width	450 mm	17.75"
Overall Length	3441 mm	135.5"
Overall Width	1848 mm	72.75"
Overall Height	2210 mm	87"
Ground Clearance	406 mm	16"
Ground Pressure (no attachment)	30.13 kPa	4.37 psi
Weight	6210 kg	13,662 lbs

## Performance

Speed		
Variable Sped Range	0-10 km/h	0-6.2 mph
Hydraulic Flow	44 GPM	5400 PSI

## Engine

Make	Cummins
Model	QSB 4.5
Displacement	4.5 L
Horsepower	140 hp (104 kW) @ 2000 RPM
Torque	457 ft·lbf (620 N·m) @ 1500 RPM

## Tracks

Rubber Compound Track

## Capacities

Fuel Tank	170 Liters	45 gallons
Hydraulic Tank	57 Liters	25 gallons

## Electrical

Voltage		12 Volts
Battery Capacity (Dual)	1500 CCA	310 RC@25 A
Alternator		160 A

## Standard Equipment

Air Conditioning  
Digital Dash Display  
Convenience 12 V Power Port  
Ingress & Egress Roof Escape  
Dome Light  
Joystick Controls  
Rear View Camera  
Cab Heater / Defrost System/Air Conditioning  
Certified Cab - ROPS / FOPS / OPS

## Optional Equipment

Hydraulic Winch	Bucket, General Purpose	Power Box Rake
Mulching Head	Bucket, Light Material	Snow Blade
Root Rake	Bucket, Multi-Purpose	Snow Blower
Auger	Brush Cutter, Rotary	Stump Grinder
Backhoe	Dozer Blade	Trencher
Broom, Rotary	Land Leveler	Vibratory Roller
Rotary Cutter	Dozer Rake	
Pallet Forks		



250 Exportation Street  
Tracadie-Sheila, NB  
Canada  
E1X 1A2

Tel. 1.888.LAMTRAC  
Fax. 506.393.8501  
www.lamtrac.com