

## Lubricant Analysis Report

North America: +1-877-808-3750

Latin America: +1-317-808-3750 / +502-3093-6466 (WhatsApp)

Europe: +1-317-808-3750

**Additional Testing** 

Overall report severity based on comments.

Account Information	Component Information	Sample Information					
Account Number: 153995-0003-0000	Component ID: 2006 LEEBOY 8510T E	Tracking Number: 23123P18223					
Company Name: BOOM & BUCKET	Secondary ID: 47064	Lab Number: H-366410					
Contact: STEVEN MESA	Component Type: DIESEL ENGINE	Lab Location: Houston					
Address: 701 BRAZOS ST. STE 300	Manufacturer: Information Requested	Data Analyst: AC					
AUSTIN, TX US	Model: Information Requested	Sampled: 16-May-2023 Received: 23-May-2023					
Phone Number: 888-417-3477	Application: UNKNOWN						
	Sump Capacity:	Completed: 24-May-2023					
Filter Information	Miscellaneous Information	Product Information					
Filter Type: Information Requested		Product Manufacturer: Information Requested					
Micron Rating: 0		Product Name: Information Requested					
		Viscosity Grade: Information Requested					

Flagged data does not indicate an immediate need for maintenance action. Continue to observe the trend and monitor equipment and fluid conditions. Silicon is at a MINOR LEVEL; SILICON sources can be abrasives (dirt, Alumina Silica), seals and gasket material, lube additive or lube supplement, and/or environmental contaminant; Bearing metal is at a MINOR LEVEL; In order to properly compare data to the correct standards, please provide COMPONENT MANUFACTURER and MODEL, and the FLUID MANUFACTURER, PRODUCT NAME, and VISCOSITY GRADE. Unit and/or lubricant TIME missing.

	Wear Metals (ppm)								Contaminant Metals (ppm) Multi-Source Metals (ppm)					Additive Metals (ppm)										
Sample #	Iron	Chromium	Nickel	Aluminum	Copper	Lead	Tin	Cadmium	Silver	Vanadium	Silicon	Sodium	Potassium	Titanium	Molybdenum	Antimony	Manganese	Lithium	Boron	Magnesium	Calcium	Barium	Phosphorus	Zinc
1	26	0	0	5	9	12	3	0	0	0	29	3	0	1	68	0	0	0	416	517	1623	0	1016	1122

		Sample	e Inforr	mation					Fluid Properties							
# elumi	ate Sampled	ate Received	Lube Time	. Unit Time	lbe Change	Lube Added	ter Change	Fuel Dilution	Soot	Water	Viscosity 40°C	Viscosity 100 °C	a Acid © Number	Base No. D4739	g Oxidation	sd Nitration
"	3   🖺	Õ	h	h h	ニュー	gal	豆	%	%	%	cSt	cSt	KOH / g	KOH/g	cm	0.1mm
1	16-May-2023	23-May-2023	0	0	Unk	0	Unk	<2 - Estimate	<.1	<.1 - FTIR		15.2		4.60	12	6

	Particle Count (particles/mL)												
Sample #	opo Code Based On 4/6/14	mL A particles /	o ^ particles / mL	0 A particles / mL	particles /	72 A particles / mL	& & & & & & & & & & & & & & & & & & &	OZ ^ particles / mL	00 A particles / mL	Test Method			
1	//												

Comments are advisory only and are based on the assumption that the sample and data submitted are valid. Results relate only to the items tested. Missing fluid or component information limits the evaluation. No warranty is expressed or implied. Measurement uncertainty available upon request.