



TERRAMAC® RT9 RUBBER TRACK CARRIER

Standard RT9 Specs

The Terramac® RT9 features an 18,000 lb. carrying capacity and is the only carrier in its class with a non-permitted load for ease of transport. Available with a rock bed, convertible dump-to-flat bed or flat bed this versatile unit travels effortlessly across any type of terrain.



DIMENSIONS	
Full Length	19' 6"
Full Height	9' 11"
Width Over Tracks	8' 3"
Min Ground Clearance	21"
Front Overhang	2' 6"
Track Gauge (Center-to-Center)	6'
Track Width	27.5"
Undercarriage Length (Idler to Drive Hub)	12' 3"
Dump Bed Loading Height Over Side	5' 11"
Height of Rock Bed Side (Vessel)	20"
Length of Rock Bed (Vessel)	10' 6"
Width of Rock Bed (Vessel)	7' 3"
Dumping Angle	60°
Machine Weight (no bed)	22,368 lbs.
Machine Weight (with rock bed)	26,180 lbs.

HYDRAULICS	
Transmission	HST
Drive Pump Max Flow (x2)	43 gpm / side
Drive Pump Max Pressure	5,500 PSI
Tandem Gear Pump Max Flow	
Front Section (AUX Output)	25 gpm @ 3000 PSI
Rear Section (HST Drive)	22 gpm @ 550 PSI
Optional Pump Drive	25 gpm @ 2500 PSI

ENGINE	
Manufacturer	Cummins
Model	QSB 6.7 T4F
Displacement	408 cu. in.
Horsepower	225 HP @ 2200 RPM
Electrical System	12 VDC
Battery	(2) GRP 31, 1125 CCA each
Fuel Capacity	64 gallons

PERFORMANCE	
Max. Carrying Capacity	18,000 lbs.
Travel Speed - 1st Gear	2.5 mph
Travel Speed - 2nd Gear	5.4 mph
Gradability	58% (30°)
Turning Radius	Zero Turn
Ground Pressure (loaded)	6.4 PSI
Ground Pressure (unloaded)	3.8 PSI

T1891

TERRAMAC® RT9 RUBBER TRACK CARRIER

Standard RT9 Units & Dimensions

