

Lubricant Analysis Report

North America: +1-877-808-3750

Latin America: +1-317-808-3750 / +502-3093-6466 (WhatsApp)

Europe: +1-317-808-3750

Overall report severity based on comments.

Account Information	Component Information	Sample Information					
Account Number: 153995-0002-0000	Component ID: HHKHFA03LG0000188 MAIN E	Tracking Number: 23265Y85686					
Company Name: BOOM & BUCKET	Secondary ID: Hyundai	Lab Number: S-119331					
Contact: KRIS HUFF	Component Type: DIESEL ENGINE	Lab Location: Salt Lake City					
Address: 600 CONGRESS AVE	Manufacturer: Information Requested	Data Analyst: ZXH					
AUSTIN, TX US	Model: Information Requested	Sampled: 15-Feb-2024					
Phone Number: 1888-313-1597/909-846-6495	Application: FORKLIFT	Submitted: 15-Feb-2024					
	Sump Capacity:	Received: 20-Feb-2024					
		Completed: 21-Feb-2024					
Filter Information	Miscellaneous Information	Product Information					
Filter Type: Information Requested		Product Manufacturer: Information Requested					
Micron Rating: 0		Product Name: Information Requested					
		Viscosity Grade: Information Requested					

Flagged data does not indicate an immediate need for maintenance action. Continue to observe the trend and monitor equipment and fluid conditions. Aluminum is at a MINOR LEVEL; ALUMINUM sources in ENGINES include pistons, block and components (intake manifold, head, bearing caps), thrust bearings, main/rod bearing overlay or backing, alumina silica, or contamination from grease. In order to properly compare data to the correct standards, please provide COMPONENT MANUFACTURER and MODEL, and the FLUID MANUFACTURER, PRODUCT NAME, and VISCOSITY GRADE. Unit and/or lubricant TIME missing.

		Wear Metals (ppm)									Contaminant Metals (ppm) Multi-Source					rce Metals (ppm)				Additive Metals (ppm)				
Sample #	uo.	Chromium	Nickel	Aluminum	Copper	Lead	Tin	Cadmium	Silver	Vanadium	Silicon	Sodium	Potassium	Titanium	Molybdenum	Antimony	Manganese	Lithium	Boron	Magnesium	Calcium	Barium	Phosphorus	Zinc
1	51	1	0	26	13	1	1	0	0	0	5	12	2	0	65	0	1	0	2	1080	1145	0	1162	1269

		Sample	e Inforr	mation					Fluid Properties							
mple #	te Sampled	te Received	Lube Time	Unit Time	be Change	Lube Added	er Change	Fuel Dilution	Soot	Water	Viscosity 40°C	Viscosity 100°C	a Acid Number	Base No. D4739	/ oxidation	y sq Vitration
Sal	Da	Da	h	h	Lul	qt	Filt	%	%	%	cSt	cSt	KOH/g	KOH/g	cm	0.1mm
1	15-Feb-2024	20-Feb-2024	0	0	No	0	No	<2 - Estimate	<.1	<.1 - FTIR		14.8		7.82	9	4

				Additional Testing							
Sample #	op OSI Based On 4/6/14	mL A particles /	o ^ particles / mL	0 A particles / mL	mL v particles /	72 ^ particles / mL	& K ^ particles / mL	OZ ^ particles / mL	00 A particles / mL	Test Method	
1	11										

Comments are advisory only and are based on the assumption that the sample and data submitted are valid. Results relate only to the items tested. Missing fluid or component information limits the evaluation. No warranty is expressed or implied. Measurement uncertainty available upon request.