

Lubricant Analysis Report

North America: +1-877-808-3750

Latin America: +1-317-808-3750 / +502-3093-6466 (WhatsApp) Europe: +1-317-808-3750

Overall report severity based on comments.

Account Information	Component Information	Sample Information
Account Number: 153995-0000-0000	Component ID: A3029199 E	Tracking Number: 23325Q25822
Company Name: BOOM AND BUCKET	Secondary ID: SN-00986	Lab Number: H-830188
Contact: ADAM LAWRENCE/KRIS HUFF	Component Type: LIQUID PETROLEUM GAS	Lab Location: Houston
Address: C/O SAMIR SHAH 701 BRAZOS	ENGINE	Data Analyst: ZXH
ST STE 300	Manufacturer: DOOSAN	Sampled: 10-Sep-2024
AUSTIN, TX US	Model: Information Requested	Received: 12-Sep-2024
Phone Number: 213-463-5980/775-225-3529	Application: UNKNOWN	Completed: 16-Sep-2024
	Sump Capacity:	
Filter Information	Miscellaneous Information	Product Information
Filter Type: Information Requested		Product Manufacturer: Information Requested
Micron Rating: 0		Product Name: Information Requested
		Viscosity Grade: Information Requested

Flagged data does not indicate an immediate need for maintenance action. Continue to observe the trend and monitor equipment and fluid conditions. Particle Count is at a MODERATE LEVEL. Silver Possibly from solder; Please provide COMPONENT MODEL number to compare data to the correct standards for this component. Please provide missing lubricant information. Manufacturer, product name, and viscosity grade are needed to properly evaluate lubricant properties. Unit and/or lubricant TIME missing. Please provide missing application and sump information.

	Wear Metals (ppm)									Contaminant Metals (ppm) Multi-Source Metals (ppm)					Additive Metals (ppm)									
Sample #	Iron	Chromium	Nickel	Aluminum	Copper	Lead	Tin	Cadmium	Silver	Vanadium	Silicon	Sodium	Potassium	Titanium	Molybdenum	Antimony	Manganese	Lithium	Boron	Magnesium	Calcium	Barium	Phosphorus	Zinc
1	20	0	0	4	5	0	1	0	3	0	12	4	1	0	122	0	1	0	60	796	1351	1	875	1002

	Sampl	e Infori	mation					Fluid Properties							
ipie # e Sampled	e Received	Lube Time	Unit Time	e Change	Lube Added	r Change	Fuel Dilution	Soot	Water	Viscosity 40°C	Viscosity 100 °C	a Acid B Number	Base No. D4739	ක ශ Oxidation	ه Vitration
Date	Date	h	h	Lub	gal	Filte	%	%	%	cSt	cSt		mg KOH / g		0.1mm
10-Sep-202	4 12-Sep-2024	0	0	Unk	0	Unk			<.1 - FTIR		12.7	1.58		13	8

L												
					Parti	cle Count	Additional Testing					
	Sample #	Based On	7 A particles /	ဖ ^ 'particles /	0 ^particles	/particles	particles /	& & & & & & & & & & & & & & & & & & &	0 ^ particles /	00 ^	Test Method	
	Sal	4/6/14	mL	mL	mL	mL	mL	mL	mL	mL		
	1	24 / 20 / 14	119989	6944	301	107	26	2	0	0	ASTM D7647	

Comments are advisory only and are based on the sample information provided by the customer being valid. Results related only to the items tested. Missing fluid or component information limits the evaluation. No warranty is expressed or implied. Measurement uncertainty available upon request.