Akuvox Video Intercom Solution

S562W White Indoor Monitor + E12W Silver Door Station

COMBINED DATASHEET

A compact SIP video intercom pairing for residential, apartment and small commercial installations.

S562W White

7-inch Wi-Fi 6 Indoor Monitor



KEY FEATURES


- 7-inch IPS capacitive touch screen
- Wi-Fi 6 (2.4 GHz) and dual Ethernet ports
- SIP 2.0 audio/video communication
- PoE or 12V DC power
- Wall-mounted or desktop installation

ESSENTIAL SPECIFICATIONS

Display	7-inch IPS LCD, capacitive touch
Network	2 x RJ45 10/100 Mbps, Wi-Fi 6
Power	802.3af PoE or 12V DC
Interfaces	RS485, relay out, bell in, 8 alarm inputs
Dimensions	216.4 x 118.8 x 21.7 mm
Operating	-10 C to +45 C, 10-90% RH

E12W Silver

Single-button IP Video Door Station



KEY FEATURES

- 2 MP wide-angle camera, 123 deg H / 69 deg V
- Two-way audio with echo cancellation
- SIP and ONVIF compatible
- 13.56 MHz RF / NFC reader and Bluetooth 5.0
- IP65 outdoor rating with tamper alarm

ESSENTIAL SPECIFICATIONS

Camera	2 MP, up to 1920 x 1080 @ 30 fps
Access	RF/NFC, Wiegand, relay output
Network	1 x RJ45 10/100 Mbps
Power	802.3af PoE or 12V DC
Dimensions	146 x 70 x 23 mm
Operating	-40 C to +60 C, IP65

MATCHED SYSTEM HIGHLIGHTS

Video calling | Door release | SIP integration | PoE deployment | Wi-Fi indoor station | Remote visitor communication

Specifications condensed from the supplied Akuvox datasheets. Product name E12S has been renamed to E12W Silver as requested. Short-form combined datasheet