


Using a 41A Filter with a Portable Air Quality Box 41CABKIT Instruction Manual

Parts Included:

- Reducer 1" to 3/4"
- Reducer 3/4" to 3/8"
- 3. Hansen Compatible Coupler (3/8" to 1/2")



This is a three-part kit used to connect a 41A Filter to a Portable Air Quality Box.

Installation

- Attach 1" reducer (part labeled 1) by screwing into the top hole of 41A filter lid.
- Attach 3/4" reducer (part labeled 2) to 1" reducer by screwing male end into female end of larger reducer.
- Attach coupler (part labeled 3) to the 3/4" reducer (part labeled 2).
- Connect a V20 hose (1/2" ID hose) to the 41A coupler.
- Attach V20 hose to 1/2" coupler on the inlet of the Portable Air Quality Box.

Bullard Center 2421 Fortune Drive

Lexington, KY 40509 • USA 877-BULLARD (285-5273) Tel: +1-859-234-6616 Fax: +1-859-246-0243

Americas Operations

1898 Safety Way Cynthiana, KY 41031 • USA 877-BULLARD (285-5273) Tel: +1-859-234-6616 Fax: +1-859-234-8987

Bullard GmbH

Dieselstrasse 8a 53424 Remagen • Germany Tel: +49-2642 999980 Fax: +49-2642 9999829

Bullard Asia Pacific Pte. Ltd.

51 Changi Business Park Central 2 #03-04 The Signature Singapore 486066 Tel: +65 6745 0556

©2020 Bullard. All rights reserved.