



Miniature Lamps (Alphanumeric)

Item	Order Code	Amps	Volts	Base	Filament	MOL in/mm	MOD in/mm	Life
47-B	00025	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
47-BP	49420	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
47-G	00026	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
47-P	05200	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
47-R	00027	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
47-Y	00028	0.15	6.3	BA9s	C-2R	1.19/30.2	0.43/11.0	3,000
48	40732	0.06	2	E10	S-2	1.19/30.2	0.43/11.0	1,000
48C2	49549	0.035	48	TS2	C-2F	1.69/42.9	0.27/6.9	10,000
48ESB5	40738	0.04	48	TS5	CC-2F	0.92/23.4	0.27/6.9	5,000
48MB	40740	0.05	48	BA9s	C-2F	1.19/30.2	0.33/8.4	10,000
48PSB5	40742	0.05	48	TS5	C-7A	1.11/28.2	0.27/6.9	10,000
48RC	40743	0.05	48	E12	C-2F	1.22/31.0	0.91/23.1	10,000
49	40744	0.06	2	BA9s	C-6	1.19/30.2	0.43/11.0	1,000
50	40746	0.22	7.5	E10	C-2R	0.94/23.9	0.43/11.0	1,000
51	40756	0.22	7.5	BA9s	C-2R	0.94/23.9	0.43/11.0	1,000
51A	01408	0.035	10	TS6	C-2F	0.92/23.4	0.27/6.9	8,000
51-BP	42016	0.22	7.5	BA9s	C-2R	0.94/23.9	0.43/11.0	1,000
52	40760	0.1	14.4	E10	C-2V	0.94/23.9	0.43/11.0	1,000
53	40761	0.12	14.4	BA9s	C-2V	0.94/23.9	0.43/11.0	1,000
53-BP	40762	0.12	14.4	BA9s	C-2V	0.94/23.9	0.43/11.0	1,000
55	40766	0.41	7	BA9s	C-2R	1.07/27.2	0.59/15.0	200
55A/S8	41702	0.55	12	P15s30	C-8S	2.09/53.1	1.04/26.4	500
55-BP	40767	0.41	7	BA9s	C-2R	1.07/27.2	0.59/15.0	200
55C2	40765	0.050	55	TS2	C-2F	1.69/42.9	0.27/6.9	5,000
55C3	40768	0.05	55	TS3	CC-2F	1.69/42.9	0.27/6.9	5,000
56	44326	0.115	5	W2.1x4.9d	C-2R	0.80/20.3	0.23/5.9	20,000
57	40771	0.24	14	BA9s	C-2V	1.07/27.2	0.59/15.0	500
57-BP	40772	0.24	14	BA9s	C-2V	1.07/27.2	0.59/15.0	500
60MB	40820	0.05	60	BA9s	CC-2F	1.19/30.2	0.33/8.4	7,500
60PSB5	40822	0.05	60	TS5	CC-2F	1.11/28.2	0.27/6.9	7,500
60RB	40821	0.05	60	BA9s	CC-7A	1.16/29.5	0.91/23.1	7,500
63	40830	0.63	7	BA15s	C-6	1.44/36.6	0.75/19.1	1,000
63-BP	40831	0.63	7	BA15s	C-6	1.44/36.6	0.75/19.1	1,000
63-R	81186	0.63	7	BA15s	C-6	1.44/36.6	0.75/19.1	1,000
64	40835	0.63	7	BA15d	C-6	1.44/36.6	0.75/19.1	1,000
67	40845	0.59	13.5	BA15s	C-6	1.44/36.6	0.75/19.1	5,000
67-BP	40846	0.59	13.5	BA15s	C-6	1.44/36.6	0.75/19.1	5,000
67K	49711	0.59	13.5	E12	C-2R	1.38/35.1	0.75/19.1	5,000
68	40850	0.59	13.5	BA15d	C-6	1.44/36.6	0.75/19.1	5,000
68-BP	42018	0.59	13.5	BA15d	C-6	1.44/36.6	0.75/19.1	5,000
70	40876	0.15	14	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	100
73	40898	0.08	14	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	15,000
73-BP	42020	0.08	14	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	15,000
74	40928	0.1	14	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	1,000
74-BP	42022	0.1	14	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	1,000
77A/S8	41704	0.77	12	P15s30	C-8S	2.09/53.1	1.04/26.4	500
79	44328	0.2	6	W2.1x4.9d	C-2R	0.80/20.3	0.23/5.9	1,000
81	40958	1.02	6.5	BA15s	C-6	1.44/36.6	0.75/19.1	500
82	40964	1.02	6.5	BA15d	C-6	1.44/36.6	0.75/19.1	500
84	40968	0.04	6.3	W2.1x4.9d	C-2R	0.80/20.3	0.23/5.9	20,000
85	40972	0.04	28	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	7,000
86	40974	0.2	6.3	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	20,000
86G	00361	0.2	6.3	W2.1x4.9d	C-2F	0.80/20.3	0.23/5.9	20,000
87	40986	1.91	6.8	BA15s	C-6	2.00/50.8	1.04/26.4	300
88	40992	1.91	6.8	BA15d	C-6	2.00/50.8	1.04/26.4	300
89	40995	0.58	13	BA15s	C-6	1.44/36.6	0.75/19.1	750