

# Outdoor Powr-Center® Extension Cords

3-Conductor Grounded • Type STW, SJE00W and SJTW • -40°C to 60°C • 300 and 600 Volts



| CATALOG NUMBER | NO. OF COND. | AWG SIZE | LENGTH OF CORD (FT) | COLOR OF JACKET | POWER RATING |      |       | PKG. PER CTN. | WT./UNIT LBS | WT./CTN. LBS | UPC CODE |
|----------------|--------------|----------|---------------------|-----------------|--------------|------|-------|---------------|--------------|--------------|----------|
|                |              |          |                     |                 | VOLTS        | AMPS | WATTS |               |              |              |          |

## STW-600V

|             |   |    |     |        |     |    |      |   |      |    |              |
|-------------|---|----|-----|--------|-----|----|------|---|------|----|--------------|
| 00594.63.04 | 3 | 12 | 2   | Orange | 125 | 15 | 1875 | 6 | 1.0  | 6  | 079407005949 |
| 00596.61.04 | 3 | 12 | 50  | Orange | 125 | 15 | 1875 | 2 | 11.1 | 22 | 079407005963 |
| 00597.61.04 | 3 | 12 | 100 | Orange | 125 | 15 | 1875 | 2 | 21.7 | 43 | 079407005970 |

## SJTW-300V

|             |   |    |     |        |     |    |      |    |      |    |              |
|-------------|---|----|-----|--------|-----|----|------|----|------|----|--------------|
| 00690.63.04 | 3 | 14 | 10  | Orange | 125 | 15 | 1875 | 12 | 1.2  | 15 | 079407006908 |
| 00691.63.04 | 3 | 14 | 25  | Orange | 125 | 15 | 1875 | 6  | 2.6  | 16 | 079407006915 |
| 00692.63.04 | 3 | 14 | 50  | Orange | 125 | 15 | 1875 | 4  | 4.7  | 19 | 079407006922 |
| 00694.63.04 | 3 | 12 | 10  | Orange | 125 | 15 | 1875 | 12 | 1.8  | 22 | 079407006946 |
| 00696.63.04 | 3 | 12 | 50  | Orange | 125 | 15 | 1875 | 2  | 7.0  | 14 | 079407006960 |
| 00697.63.04 | 3 | 12 | 100 | Orange | 125 | 15 | 1875 | 2  | 13.4 | 27 | 079407006977 |

## SJE00W-300V

|             |   |    |     |        |     |    |      |    |      |    |              |
|-------------|---|----|-----|--------|-----|----|------|----|------|----|--------------|
| 00790.63.07 | 3 | 14 | 10  | Blue   | 125 | 15 | 1875 | 12 | 1.3  | 16 | 079407007905 |
| 00791.63.07 | 3 | 14 | 25  | Blue   | 125 | 15 | 1875 | 6  | 2.7  | 16 | 079407007912 |
| 00792.63.07 | 3 | 14 | 50  | Blue   | 125 | 15 | 1875 | 4  | 4.8  | 19 | 079407007929 |
| 00793.63.07 | 3 | 14 | 100 | Blue   | 125 | 13 | 1625 | 2  | 9.0  | 18 | 079407007936 |
| 00787.63.05 | 3 | 12 | 50  | Yellow | 125 | 15 | 1875 | 2  | 6.5  | 13 | 079407007875 |
| 00788.63.05 | 3 | 12 | 100 | Yellow | 125 | 15 | 1875 | 2  | 13.0 | 26 | 079407007882 |

### Product Construction:

#### Conductor:

- 14 AWG or 12 AWG stranded bare copper per ASTM B-174

#### Insulation:

- Premium-grade, color-coded PVC

#### Jacket:

- PVC; orange, TPE; blue or yellow
- Temperature range: -40°C to 60°C
- Voltage rating: 300 and 600 volts

#### NEMA Configuration:

- 5-15P/5-15R

### Applications:

- General use indoor/outdoor cord
- Chain saws
- Wet/dry vacs
- Orbital sanders
- Other power equipment

### Features:

- Indoor/outdoor use
- 3 grounded outlets

### Industry Approvals:

- UL Listed
- OSHA Acceptable

