

# Rigid and IMC Conduit Fittings

## Threaded Hubs



To secure threaded rigid service entrance conduit to box or enclosure. Insulated throat rated 105°C. BUNA-N sealing ring completely encircles knockout to prevent contaminants from entering enclosure. Concrete-tight.

 File No. E9391: Type 4 - Water Tight

 File No. LR39354

Note: UL Listing not applicable to 5" & 6" Malleable Iron.

## Zinc Die Cast

| Catalog Number | Trade Size | Unit Qty. | Std. Pkg. | Catalog Number | Trade Size | Unit Qty. | Std. Pkg. |
|----------------|------------|-----------|-----------|----------------|------------|-----------|-----------|
| 151-DC         | 1/2"       | 25        | 100       | 156-DC         | 2"         | 2         | 20        |
| 152-DC         | 3/4"       | 25        | 100       | 157-DC         | 2 1/2"     | ---       | 10        |
| 153-DC         | 1"         | 10        | 50        | 158-DC         | 3"         | ---       | 5         |
| 154-DC         | 1 1/4"     | 5         | 25        | 159-DC         | 3 1/2"     | 1         | 5         |
| 155-DC         | 1 1/2"     | 2         | 20        | 160-DC         | 4"         | 1         | 5         |

## Malleable Iron

| Catalog Number | Trade Size | Unit Qty. | Std. Pkg. |
|----------------|------------|-----------|-----------|
| 3161           | 5"         | ---       | 2         |
| 3162           | 6"         | ---       | 2         |

## Lock - A - Liners

Used for converting ordinary bushings and connectors to code approved insulating bushings and connectors without disturbing wiring.



 File No. E11259

## Polypropylene - 105°C

| Catalog Number | Trade Size | Unit Qty. | Std. Pkg. | Catalog Number | Trade Size | Unit Qty. | Std. Pkg. |
|----------------|------------|-----------|-----------|----------------|------------|-----------|-----------|
| 191            | 1/2"       | 25        | 100       | 194            | 1 1/4"     | 10        | 40        |
| 192            | 3/4"       | 25        | 100       | 195            | 1 1/2"     | 10        | 40        |
| 193            | 1"         | 25        | 100       | 196            | 2"         | 10        | 40        |