

DIESEL FUEL CONDITIONER**Stock # 991/992/993/994/995/998****SECTION 01: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

MANUFACTURER..... KLEEN-FLO TUMBLER INDUSTRIES LIMITED
 75 ADVANCE BLVD., BRAMPTON, ON
 L6T 4N1
 905-793-4311

PRODUCT NAME.....DIESEL FUEL CONDITIONER
 PRODUCT CODE..... 991/992/993/994/995/998
 CHEMICAL FORMULA..... MIXTURE.
 MATERIAL USE..... DIESEL FUEL ADDITIVE
 EMERGENCY PHONE NO..... 905-793-4311 (Monday to Friday 8.30am to 4.30pm EST) (English Language only)

SECTION 02: HAZARDS IDENTIFICATION

SIGNAL WORD..... DANGER.

HAZARD CLASSIFICATION..... FLAMMABLE LIQUIDS — CATEGORY 2. SKIN IRRITATION — CATEGORY 2. EYE IRRITATION — CATEGORY 2A. ACUTE TOXICITY (ORAL) CATEGORY 5. SPECIFIC TARGET ORGAN TOXICITY — SINGLE EXPOSURE — CATEGORY 3. SPECIFIC TARGET ORGAN TOXICITY — REPEATED EXPOSURE — CATEGORY 2. ASPIRATION HAZARD — CATEGORY 1.

HAZARD STATEMENT..... H225 HIGHLY FLAMMABLE LIQUID AND VAPOUR. H304 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. H315 CAUSES SKIN IRRITATION. H319 CAUSES SERIOUS EYE IRRITATION. H332 HARMFUL IF INHALED. H335 MAY CAUSE RESPIRATORY IRRITATION. H336 MAY CAUSE DROWSINESS OR DIZZINESS. H373 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

PRECAUTIONARY STATEMENT..... P210 KEEP AWAY FROM HEAT/SPARKS/OPEN FLAMES/HOT SURFACES AND OTHER IGNITION SOURCES – NO SMOKING. P233 KEEP CONTAINER TIGHTLY CLOSED. P240 GROUND/BOND CONTAINER AND RECEIVING EQUIPMENT. P241 USE EXPLOSION-PROOF ELECTRICAL/VENTILATING/LIGHTING EQUIPMENT. P242 USE ONLY NON-SPARKING TOOLS. P243 TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGE. P260 DO NOT BREATHE DUST/FUME/GAS/MIST/VAPOURS/SPRAY. P264 WASH SKIN THOROUGHLY AFTER HANDLING. P271 USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA. P273 AVOID RELEASE TO THE ENVIRONMENT. P280 WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION. P301+P310 IF SWALLOWED: IMMEDIATELY CALL A POISON CENTER OR DOCTOR/PHYSICIAN. P303+P361+P353 IF ON SKIN (OR HAIR): REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER. P304+P312 IF INHALED: CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P304+P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. P305+P351+P338 IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING. P312 CALL A POISON CENTER OR DOCTOR/PHYSICIAN IF YOU FEEL UNWELL. P331 DO NOT INDUCE VOMITING. P337+P313 IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION. P340 REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING. P370+P378 IN CASE OF FIRE: USE DRY SAND, DRY CHEMICAL OR ALCOHOL RESISTANT FOAM FOR EXTINCTION. P403+P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED. P403+P235 STORE IN A WELL-VENTILATED PLACE. KEEP COOL. P405 STORE LOCKED UP. P501 DISPOSE OF CONTENTS/CONTAINER ACCORDING TO ALL APPLICABLE REGULATIONS.

OTHER HAZARDS..... VAPOURS CAN ACCUMULATE IN LOW AREAS. MAY FORM EXPLOSIVE PEROXIDES. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS.

PRODUCT: DIESEL FUEL CONDITIONER

STOCK # 991/992/993/994/995/998

SECTION 03: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	CAS #	WT. %
-----------------------	-------	-------

ISOPROPYL ALCOHOL

67-63-0

80-100

XYLENE

1330-20-7

10-30

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 04: FIRST AID MEASURES

GENERAL ADVICE:..... CONSULT A PHYSICIAN. SHOW THIS SAFETY DATA SHEET TO THE DOCTOR IN ATTENDANCE. MOVE OUT OF DANGEROUS AREA.

IF INHALED:..... IF BREATHED IN, MOVE PERSON INTO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. CONSULT A PHYSICIAN.

IN CASE OF SKIN CONTACT:..... WASH OFF WITH SOAP AND PLenty OF WATER. CONSULT A PHYSICIAN.

IN CASE OF EYE CONTACT:..... WASH EYES WITH COPIOUS AMOUNT OF WATER.

IF SWALLOWED:..... DO NOT INDUCE VOMITING. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. RINSE MOUTH WITH WATER. CONSULT A PHYSICIAN. DO NOT LEAVE VICTIM UNATTENDED.

SECTION 05: FIRE FIGHTING MEASURES

FLAMMABILITY..... FLAMMABLE IN THE PRESENCE OF A SOURCE OF IGNITION WHEN THE TEMPERATURE IS ABOVE THE FLASH POINT. KEEP AWAY FROM HEAT/SPARK/OPEN FLAME/HOT SURFACE. NO SMOKING.

SUITABLE EXTINGUISHING MEDIA..... SUITABLE FOR SURROUNDING FIRE. CARBON DIOXIDE, DRY CHEMICAL, ALCOHOL FOAM, WATER FOG.

HAZARDOUS COMBUSTION PRODUCTS. CARBON OXIDES.

SPECIFIC HAZARDS ARISING FROM THE NO DATA AVAILABLE.

CHEMICAL

SPECIAL PROCEDURES..... EVACUATE HAZARD AREA. WEAR FULL PROTECTIVE EQUIPMENT INCLUDING A SELF-CONTAINED BREATHING APPARATUS. USE WATER TO COOL CONTAINERS.

SECTION 06: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS:..... USE PERSONAL PROTECTIVE EQUIPMENT. AVOID BREATHING VAPORS, MIST OR GAS. ENSURE ADEQUATE VENTILATION. REMOVE ALL SOURCES OF IGNITION. EVACUATE PERSONNEL TO SAFE AREAS. BEWARE OF VAPOURS ACCUMULATING TO FORM EXPLOSIVE CONCENTRATIONS. VAPOURS CAN ACCUMULATE IN LOW AREAS.

ENVIRONMENTAL PRECAUTIONS:..... PREVENT FURTHER LEAKAGE OR SPILLAGE IF SAFE TO DO SO. DO NOT LET PRODUCT ENTER DRAINS. DISCHARGE INTO THE ENVIRONMENT MUST BE AVOIDED.

METHODS AND MATERIALS FOR CONTAIN SPILLAGE AND THEN COLLECT WITH ELECTRICALLY PROTECTED CONTAINMENT AND CLEAN UP: VACUUM CLEANER OR BY WET-BRUSHING AND PLACE IN CONTAINER FOR DISPOSAL ACCORDING TO LOCAL REGULATIONS.

SECTION 07: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING..... HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. AVOID CONTACT WITH EYES, SKIN AND CLOTHING. AVOID BREATHING MIST OR VAPOUR. WEAR PROTECTIVE EQUIPMENT DURING HANDLING. USE ADEQUATE VENTILATION. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. TAKE MEASURES TO PREVENT THE BUILD UP OF ELECTROSTATIC CHARGE.

CONDITIONS FOR SAFE STORAGE..... KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAMES. PROTECT CONTAINER FROM PHYSICAL DAMAGE. KEEP THE CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. STORE IN A COOL AND WELL-VENTILATED AREA, AWAY FROM DIRECT SUNLIGHT, SOURCES OF INTENSE HEAT, OR WHERE FREEZING IS POSSIBLE.

SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL	NIOSH
-------------	-----	-------------------	-----	------------------	-----	-------

ISOPROPYL ALCOHOL 200 ppm

400 ppm

XYLENE 100 ppm

150 ppm

ENGINEERING CONTROLS..... GOOD VENTILATION SHOULD BE PROVIDED TO KEEP VAPOUR AND MIST CONCENTRATIONS BELOW THE EXPOSURE LIMITS.

PRODUCT: DIESEL FUEL CONDITIONER

STOCK # 991/992/993/994/995/998

SECTION 08: EXPOSURE CONTROLS/PERSONAL PROTECTION

SKIN AND BODY PROTECTION..... COMPLETE SUIT PROTECTING AGAINST CHEMICALS. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE.
 FLAME RETARDANT ANTISTATIC PROTECTIVE CLOTHING.
 RESPIRATORY PROTECTION..... USE NIOSH APPROVED SUPPLIED-AIR RESPIRATOR.
 EYE/FACE PROTECTION..... SPLASH PROOF CHEMICAL GOGGLES. FACE SHIELD.
 HYGIENIC MEASURES..... USE GOOD PERSONAL HYGIENE PRACTICES. WASH HANDS BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES. PROMPTLY REMOVE SOILED CLOTHING AND WASH THOROUGHLY BEFORE REUSE. SHOWER AFTER WORK USING PLENTY OF SOAP AND WATER.
 OTHER/TYPE..... EYE WASH STATION AND SAFETY SHOWER SHOULD BE LOCATED NEAR THE WORK STATION.

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE..... LIQUID.
 ODOUR..... ALCOHOL LIKE.
 ODOUR THRESHOLD..... NO DATA AVAILABLE.
 PH..... NO DATA AVAILABLE.
 MELTING POINT/FREEZING POINT (C)..... -88 C.
 BOILING POINT..... 82-83 C.
 FLASH POINT (C), METHOD..... 12 C (ISOPROPYL ALCOHOL).
 EVAPORATION RATE..... 2.3 (nBuAc=1).
 FLAMMABILITY (SOLIDS AND GASES)..... NOT APPLICABLE.
 UPPER FLAMMABLE LIMIT (% BY VOL.)... 12 % (V).
 LOWER FLAMMABLE LIMIT (% BY VOL.)... 2% (V).
 VAPOUR PRESSURE..... 6.020 Pa (20 C).
 VAPOUR DENSITY (AIR=1)..... NO DATA AVAILABLE.
 SPECIFIC GRAVITY (WATER=1)..... 0.796.
 SOLUBILITY IN WATER (% W/W)..... COMPLETELY MISCIBLE.
 AUTO IGNITION TEMPERATURE..... 425 (C).
 PARTITION COEFFICIENT: NO DATA AVAILABLE.
 N-OCTANOL/WATER
 DECOMPOSITION TEMPERATURE..... NO DATA AVAILABLE.
 VISCOSITY..... NO DATA AVAILBLE.

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY:..... EXCESSIVE HEAT, SPARKS AND OPEN FLAME.
 CHEMICAL STABILITY:..... STABLE UNDER RECOMMENDED STORAGE CONDITIONS.
 POSSIBILITY OF HAZARDOUS REACTIONSVAPOURS MAY FORM EXPLOSIVE MIXTURE WITH AIR.
 CONDITIONS TO AVOID:..... AVOID OPEN FLAMES AND SPARKS.
 INCOMPATIBLE MATERIALS :..... STRONG OXIDIZING AGENTS.
 HAZARDOUS DECOMPOSITION CARBON OXIDES.
 PRODUCTS

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
ISOPROPYL ALCOHOL	INHALATION-RAT- 16000 ppm - 8h	ORAL-RAT- >5000 MG/KG
XYLENE	INHALATION-RAT- >20 mg/L	ORAL-RAT- >3523 mg/kg

ACUTE TOXICITY:

ORAL LD50..... SEE ABOVE.
 INHALATION LC50..... SEE ABOVE.
 DERMAL LD50..... RABBIT - 12800 MG/KG.
 SKIN CORROSION / IRRITATION..... RABBIT - MILD SKIN IRRITAION.
 SERIOUS EYE DAMAGE / EYE IRRITATION RABBIT-EYE IRRITATION -24h.
 RESPIRATORY OR SKIN SENSITIZATION. NO DATA AVAILABLE.
 GERM CELL MUTAGENICITY..... NO DATA AVAILABLE.
 CARCINOGENICITY..... IARC: 3 - GROUP 3: NOT CLASSIFIABLE AS TO ITS CARCINOGENICITY TO HUMANS
 . IARC: 2B - POSSIBLY CARCINOGENIC TO HUMANS (ETHYLBENZENE).
 REPRODUCTIVE TOXICITY..... DOES NOT IMPAIR FERTILITY. NOT A DEVELOPMENTAL TOXICANT.
 STOT- SINGLE EXPOSURE..... MAY CAUSE DROWSINESS OR DIZZINESS.
 STOT - REPEAT EXPOSURE..... NO DATA AVAILABLE.
 ASPIRATION HAZARD..... MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

PRODUCT: DIESEL FUEL CONDITIONER

STOCK # 991/992/993/994/995/998

SECTION 11: TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS..... INHALATION - MAY BE HARMFUL IF INHALED. CAUSES RESPIRATORY TRACT IRRITATION. VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS. INGESTION - MAY BE HARMFUL IF SWALLOWED. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. EYES - MAY CAUSE EYE IRRITATION. SKIN - MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. MAY CAUSE SKIN IRRITATION.

SIGNS AND SYMPTOMS OF EXPOSURE.. CENTRAL NERVOUS SYSTEM DEPRESSION, PROLONGED OR REPEATED EXPOSURE CAN CAUSE, NARCOSIS, SKIN IRRITATION. OVER EXPOSURE MAY CAUSE MILD, REVERSIBLE LIVER EFFECTS. ASPIRATION MAY LEAD TO, LUNG EDEMA, PNEUMONIA.

SECTION 12: ECOLOGICAL INFORMATION

PERSISTENCE AND DEGRADABILITY..... READILY BIODEGRADABLE.

BIOACCUMULATIVE POTENTIAL..... NO BIOACCUMULATION IS TO BE EXPECTED.

TOXICITY..... LC50 - PIMEPHALES PROMELAS (FATHEAD MINNOW) - 9,640.00 mg/l - 96 h - (IPA).
EC50 - DAPHNIA MAGNA (WATER FLEA) - 5,102.00 mg/l - 24 h - (IPA).
DISSOLVES IN WATER. IF THE PRODUCT ENTERS SOIL, ONE OR MORE CONSTITUENTS WILL OR MAY BE MOBILE AND MAY CONTAMINATE GROUND WATER.

MOBILITY IN SOIL.....

OTHER ADVERSE EFFECTS..... NO DATA AVAILABLE.

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL METHODS..... INCINERATION INCLUDING ENERGY RECOVERY OF WASTE MATERIAL IN A PERMITTED FACILITY IN ACCORDANCE WITH LOCAL, STATE OR PROVINCIAL AND FEDERAL REGULATIONS.

PACKAGING:..... DISPOSE OF AS UNUSED PRODUCT.

SECTION 14: TRANSPORT INFORMATION

STOCK # 994/995/998 AS FOLLOWS:

UN NUMBER..... 1993.

TDG CLASSIFICATION..... 3.

PACKING GROUP..... II.

PROPER SHIPPING NAME..... FLAMMABLE LIQUID, N.O.S. (2-PROPANOL SOLUTION).

STOCK # 991/992/993: CONSUMER COMMODITY

SECTION 15: REGULATORY INFORMATION

HPR COMPLIANCE..... THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE HPR AND THE SDS CONTAINS ALL THE INFORMATION REQUIRED BY THE HPR.

SECTION 16: OTHER INFORMATION

TSCA- LISTED ON INVENTORY

N.AV.=NOT AVAILABLE

PREPARED BY..... KLEEN-FLO TUMBLER INDUSTRIES LIMITED

PREPARATION DATE..... FEB 21/2017

PRODUIT: CONDITIONNEUR POUR CARBURANT DIESEL

NO DE STOCK: 991/992/993/994/995/998

SECTION 01: IDENTIFICATION DU PRODUIT CHIMIQUE ET DE LA SOCIÉTÉ

RÉFÉRENCE DU FABRICANT..... LES ENTREPRISES KLEEN-FLO TUMBLER LIMITEE
75 ADVANCE BLVD. BRAMPTON, ON
L6T 4N1
905-793-4311

NOM DU PRODUIT..... CONDITIONNEUR POUR CARBURANT DIESEL

CODE DU PRODUIT..... 991/992/993/994/995/998

FORMULE CHIMIQUE..... MÉLANGE.

UTILISATION DE MATÉRIEL..... ADDITIF POUR CARBURANT DIESEL

N ° DE TÉLÉPHONE D'URGENCE..... 450-625-6444 (du lundi au vendredi, de 8h00 à 16h00, heure de l'Est) (en français seulement)

SECTION 02: IDENTIFICATION DES DANGERS

MOT INDICATEUR..... DANGER.

CLASSIFICATION DES RISQUES..... LIQUIDES INFLAMMABLES — CATÉGORIE 2. IRRITATION CUTANÉE — CATÉGORIE 2. IRRITATION OCULAIRE — CATÉGORIE 2A. TOXICITÉ AIGÜE (PAR VOIE ORALE) DE CATÉGORIE 5. TOXICITÉ POUR CERTAINS ORGANES CIBLES — EXPOSITION UNIQUE — CATÉGORIE 3. TOXICITÉ POUR CERTAINS ORGANES CIBLES — EXPOSITIONS RÉPÉTÉES — CATÉGORIE 2. DANGER PAR ASPIRATION — CATÉGORIE 1.

MENTION DE DANGER..... H225 LIQUIDE ET VAPEURS TRÈS INFLAMMABLES. H304 PEUT ÊTRE MORTEL EN CAS D'INGESTION ET DE PÉNÉTRATION DANS LES VOIES RESPIRATOIRES. H315 PROVOQUE UNE IRRITATION CUTANÉE. H319 PROVOQUE UNE SÉVÈRE IRRITATION DES YEUX. H332 NOCIF PAR INHALATION. H335 PEUT IRRITER LES VOIES RESPIRATOIRES. H336 PEUT PROVOQUER SOMNOLENCE OU DES VERTIGES. H373 RISQUE PRESUME D'EFFETS GRAVES POUR LES ORGANES À LA SUITE D'EXPOSITIONS RÉPÉTÉES OU D'UNE EXPOSITION PROLONGÉE.

CONSEIL DE PRUDENCE..... P210, TENIR À L'ÉCART DE LA CHALEUR, DES SURFACES CHAUDES, DES ÉTINCELLES, DES FLAMMES NUES ET DE TOUTE AUTRE SOURCE D'IGNITION. NE PAS FUMER. P233 MAINTENIR LE RÉCIPIENT FERMÉ DE MANIÈRE ÉTANCHE. P240 MISE À LA TERRE/LIAISON ÉQUIPOTENTIELLE DU RÉCIPIENT ET DU MATÉRIEL DE RÉCEPTION. P241 UTILISER DU MATÉRIEL ÉLECTRIQUE/DE VENTILATION/D'ÉCLAIRAGE/ ANTIDÉFLAGRANT. P242 NE PAS UTILISER D'OUTILS PRODUISANT DES ÉTINCELLES. P243 PRENDRE DES MESURES DE PRÉCAUTION CONTRE LES DÉCHARGES ÉLECTROSTATIQUES. P260 NE PAS RESPIRER LES POUSSIÈRES/FUMÉES/GAZ/BROUILLARDS/VAPEURS/ AÉROSOLS. P264 SE LAVER... SOIGNEUSEMENT APRES MANIPULATION. P271 UTILISER SEULEMENT EN PLEIN AIR OU DANS UN ENDROIT BIEN VENTILÉ. P273 ÉVITER LE REJET DANS L'ENVIRONNEMENT. P280 PORTEZ GANTS DE PROTECTION/PROTECTIVE CLOTHING/UNE PROTECTION/VISAGE. P301+P310 EN CAS D'INGESTION: APPELER IMMÉDIATEMENT UN CENTRE ANTIPOISON OU UN MÉDECIN. P303+P361+P353 EN CAS DE CONTACT AVEC LA PEAU (OU LES CHEVEUX): ENLEVER IMMÉDIATEMENT LES VÊTEMENTS CONTAMINÉS. RINCER LA PEAU À L'EAU/SE DOUCHER. P304+P312 EN CAS D'INHALATION: APPELER UN CENTRE ANTIPOISON/ UN MÉDECIN/ EN CAS DE MALAISE. P304+P340 EN CAS D'INHALATION: TRANSPORTER LA VICTIME À L'EXTÉRIEUR ET LA MAINTENIR AU REPOS DANS UNE POSITION OÙ ELLE PEUT CONFORTABLEMENT RESPIRER. P305+P351+P338 EN CAS DE CONTACT AVEC LES YEUX: RINCER AVEC PRÉCAUTION À L'EAU PENDANT PLUSIEURS MINUTES. ENLEVER LES LENTILLES DE CONTACT SI LA VICTIME EN PORTE ET SI ELLES PEUVENT ÊTRE FACILEMENT ENLEVÉES. CONTINUER À RINCER. P312 APPELER UN CENTRE ANTIPOISON OU UN MÉDECIN EN CAS DE MALAISE. P331 NE PAS FAIRE VOMIR. P337+P313 SI L'IRRITATION DES YEUX PERSISTE: DEMANDER UN AVIS MEDICAL/CONSULTER UN MEDECIN. P340 TRANSPORTER LA VICTIME À L'EXTÉRIEUR ET LA MAINTENIR