



Revision Number: 001.0

Issue date: 03/05/2024

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LePage Heavy Duty Contact Cement	IDH number:	2994441
Product type/use:	Solvent based adhesive	Item number:	
Restriction of Use:	None identified	Region:	Canada
Company address:	Contact information:		
Henkel Canada Corporation	Telephone: +1 (905) 814-6511		
Meadowpine Boulevard 2515	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: HIGHLY FLAMMABLE LIQUID AND VAPOUR.
MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.
CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	2
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3
ASPIRATION HAZARD	1

PICTOGRAM(S)



Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Keep container tightly closed. No release into water. Use explosion-proof equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF SWALLOWED: Immediately call a physician or poison control center. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off

IDH number: 2994441

Product name: LePage Heavy Duty Contact Cement

Storage: contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
acetone	67-64-1	10 - 30
Solvent naphtha (petroleum), light aliph., <0.1% benzene	64742-89-8	10 - 30
Methyl ethyl ketone	78-93-3	10 - 30
propyl acetate	109-60-4	10 - 30
Tert-butyl acetate	540-88-5	5 - 10
Phenol, polymer with formaldehyde	9003-35-4	5 - 10
Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane	119-47-1	0.1 - 1
Magnesium oxide	1309-48-4	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air, consult doctor if complaint persists.

Skin contact: Rinse immediately with plenty of running water, seek medical advice if necessary.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.

Ingestion: Do not induce vomiting. Seek medical advice.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self contained breathing apparatus. Wear full protective clothing.

Unusual fire or explosion hazards: None known.

Hazardous combustion products: Carbon dioxide. Carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Storage: Not available.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
acetone	250 ppm TWA 500 ppm STEL	1,000 ppm (2,400 mg/m3) PEL	None	None
Solvent naphtha (petroleum), light aliph., <0.1% benzene	None	100 ppm (400 mg/m3) PEL	None	None
Methyl ethyl ketone	200 ppm TWA 300 ppm STEL	200 ppm (590 mg/m3) PEL	None	None
propyl acetate	100 ppm TWA 150 ppm STEL	200 ppm (840 mg/m3) PEL	None	None
Tert-butyl acetate	50 ppm TWA 150 ppm STEL	200 ppm (950 mg/m3) PEL	None	None
Phenol, polymer with formaldehyde	None	None	None	None
Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane	None	None	None	None
Magnesium oxide	10 mg/m3 TWA Inhalable fraction.	15 mg/m3 PEL Total particulate. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust. 15 MPPCF TWA Respirable fraction.	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Tan
Odor:	Pungent
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Specific gravity:	0.845 - 0.869 at 25 °C (77°F)
Vapor density:	Not available.
Flash point:	-18 °C (0.4 °F) Internal Henkel specification
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.

Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	54.35 %
Viscosity:	1,000 - 1,400 cp
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO ₂) are released.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Heat, flames, sparks and other sources of ignition.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	May cause nose, throat and lung irritation. May cause sensitization by inhalation.
Skin contact:	May cause skin irritation. May cause allergic skin reaction.
Eye contact:	May cause mild irritation
Ingestion:	May be harmful if swallowed. May cause an aspiration hazard if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
acetone	Oral LD50 (Mouse) = 5.2 g/kg Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l Inhalation LC50 (Rat, 4 h) = 50.1 mg/l	Central nervous system, Irritant
Solvent naphtha (petroleum), light aliph., <0.1% benzene	Inhalation LC50 (Rat, 4 h) = > 7,630 mg/m3 Inhalation LC50 (Rat, 4 h) = > 5,610 mg/m3	Irritant
Methyl ethyl ketone	Oral LD50 (Mouse) = 670 mg/kg Oral LD50 (Rat) = 2,300 - 3,500 mg/kg Oral LD50 (Rat) = 4,500 - 6,800 mg/kg Dermal LD50 (Rabbit) = > 8,000 mg/kg	Irritant, Central nervous system
propyl acetate	Oral LD50 (Mouse) = 8,300 mg/kg Oral LD50 (Rabbit) = 6.64 g/kg Oral LD50 (Rat) = 9,370 mg/kg Inhalation LC50 (Rat, 4 h) = 32 mg/l	Central nervous system, Irritant
Tert-butyl acetate	Inhalation LC50 (Rat, 4 h) = > 2.23 mg/l Inhalation LC50 (Rat, 4 h) = 13.3 mg/l	Blood, Cardiac, Central nervous system, Gastrointestinal, Irritant
Phenol, polymer with formaldehyde	None	No Data
Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane	Oral LD50 (Mouse) = 11,000 mg/kg Oral LD50 (Mouse) = 11,000 mg/kg	Irritant
Magnesium oxide	None	Blood, Central nervous system, Immune system, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
acetone	No	No	No
Solvent naphtha (petroleum), light aliph., <0.1% benzene	No	No	No
Methyl ethyl ketone	No	No	No
propyl acetate	No	No	No
Tert-butyl acetate	No	No	No
Phenol, polymer with formaldehyde	No	No	No
Bis(2-hydroxy-3-tert-butyl-5-methylphenyl)methane	No	No	No
Magnesium oxide	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Canada Transportation of Dangerous Goods - Ground

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Adhesives
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: ADHESIVES
Hazard class or division: 3
Identification number: UN 1133
Packing group: II

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/05/2024

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on the Canadian Hazardous Products Regulations (WHMIS 2015) and provides information in accordance with Canadian law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

