

CANAC 114413 Triple expansion polyurethane

DESCRIPTION

CANAC 114413 is a straw-grade polyurethane foam that reacts to ambient humidity. CANAC 114413 fills and seals cracks, voids and holes, eliminates drafts and insulates with a factor of R-5 per square inch. It adheres to most building surfaces. CANAC 114413 is used for electrical and construction plumbing applications.

PHYSICAL PROPERTIES

| | |
|--------------------------------------|--|
| Base | Polyurethane |
| Color | Champagne |
| Consistency | Stable foam thixotropic |
| Curing system | Moisture cure |
| Skin time (20°C (68°F) /65% R.H.) | ± 8 minutes |
| Drying time (20°C (68°F) /65% R.H.) | Dust free after 20-25 minutes |
| Curing time (20°C (68°F) / 65% H.R.) | 30 minutes for a 30mm diameter |
| Yield | 300ml = 11 liters of cured foam |
| Shrinkage | None |
| Post-expansion | None |
| Cellular structure | 70-80% closed cells |
| Relative density | 25 kg/m ³ (when fully cured) |
| Temperature resistance | -40°C (-40°F) to 90°C (194°F) when cured |
| Fire class (DIN 4102 partie 2) | B3 |
| Insulation factor | 35 mW/m.K |
| Shear strength (DIN 53427) | 5 N/cm ² |
| Pressure strength (DIN 53421) | 2 N/cm ² |
| Bowing strength (DIN 53423) | 7 N/cm ² |
| Water absorption (DIN 53429) | 1% Vol |
| Acoustic rating | Rst,w = 58dB |
| V.O.C. | 235 g/L |

PRODUCT CHARACTERISTICS

- Excellent adhesion on most substrates (except PTFE, PE, and PP)
- High thermal and acoustical insulation
- Very good filling capacities
- Excellent mounting capacities
- Excellent stability (no shrink or post-expansion)

APPLICATIONS

- Filling of cavities (roof, plumbing and electricity)
- Sealing of all openings in roof constructions
- Creation of a soundproof screen
- Mounting and sealing of window and door frames
- Connecting of insulation materials and roof constructions
- Application of a soundproofing layer on motors
- Improving thermal isolation in cooling systems

CANAC 114413
Triple expansion polyurethane**DIRECTIONS FOR USE**

All surfaces must be free of dust, oil, grease, frost, or any other contaminant. Clean all surfaces with ADSEAL CLEANER 500. Let evaporate 20 minutes prior to CANAC 114413 application. Shake the aerosol can for at least 30 seconds. Put the adapter (straw) on the can. Moisten surfaces with a water spray prior to application (only when temperature > 0°C). The aerosol can be used in all directions. Remove pressure from the applicator to stop. Fill holes and cavities at 50% as the foam will expand. Repeat shaking regularly during application. If you must work in layers repeat moistening after each layer (only when temperature > 0°C). Fresh foam can be removed using ADFOAM CLEANER 500-gun cleaner. Cured foam can only be removed mechanically. Cured foam may be trimmed or sanded. Cured foam must be protected from UVB radiation by painting or applying a top layer of sealant (silicone or hybrid sealant). Application temperature: -5°C (23°F) to 35°C (95°F).

PACKAGING

- Aerosol can be packaged in 275 grams / 300ml cans

SHELF LIFE

12 months in unopened packaging in a cool and dry storage place at temperatures between 5°C (41°F) and 25°C (77°F). Always store can with the valve pointed upwards.

HANDELING AND SAFETY

Apply the usual industrial hygiene. Wear gloves and safety goggles. Remove cured foam by mechanical means only, never burn away. Consult the SDS (Safety Data Sheet) for more information. If you need additional information, do not hesitate to contact your technical representative. Always test product on your application prior to use. For industrial use only.

IMPORTANT
READ CAREFULLY

The information and recommendations contained herein are derived from our research and information from other reliable sources. This data applies only to our products and not when used with other products. We believe in the reliability of our information. However, no guarantee is offered to that effect. It is the responsibility of the buyer to verify this data according to their own operating conditions to ensure that they conform to the purpose for which the product is intended, even before using it.

THE WARRANTY OFFERED BY ADFAST SHALL BE LIMITED TO THE REPLACEMENT OR REIMBURSEMENT OF THE PRODUCT IF THEY HAVE BEEN DEFECTIVE. NO OTHER IMPLIED OR EXPRESSED WARRANTY APPLIES. ADFAST DISCLAIMS ANY OTHER LIABILITY FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.