



PRO 9750™

2. MANUFACTURER

PROMA ADHESIVES Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3
Tel.: 514.852.8585
Fax: 514.852.8225
Toll-free: 1 866.51.PROMA (77662)
Email: info@proma.ca
Web: www.proma.ca

3. PRODUCT DESCRIPTION

PRO 9750™ is a premium, solvent-free, stain-free wall base adhesive, with strong wet grab, specially designed for vinyl, rubber and carpet wall base. PRO 9750 is easy to use, easy to clean, resistant to breakdown from plasticizer migration and is formulated with antimicrobial protection to prevent the growth of mold, mildew and bacteria. PRO 9750 is freeze/thaw stable to -12°C.

Features

- ♦ For the installation of vinyl, rubber and carpet wall base
- ♦ Use for stair thread installation
- ♦ Solvent free formula for improved indoor air quality
- ♦ Light-colored formula will not stain
- ♦ Strong wet grab and bond strength prevents slip during installation and holds corners tight
- ♦ Antimicrobial protection resists the growth of mold, mildew and bacteria
- ♦ Prevents breakdown of adhesive due to plasticizer migration from vinyl wall base
- ♦ Easy to apply and clean
- ♦ Freeze/thaw stable formula (5 Cycles at -12°C [10°F])
- ♦ Contributes to LEED® objectives and requirements

Packaging

850 mL (28.7 oz) cartridge; 3.79 L (1 US gal) pail; 15.1 L (4 US gal) pail

Suitable Substrates

- ♦ Drywall
- ♦ Plaster
- ♦ Masonry, concrete and brick walls
- ♦ Water-based paint residue over porous substrates
- ♦ Wood, such as APA grade plywood



Limitations

- ♦ For interior installations only.
- ♦ Do not use at temperature below 10°C (50°F) or above 35°C (95°F)
- ♦ Do not install over non-porous surfaces, such as vinyl wall coverings, wallpaper, ceramic tiles, metal, non-porous paint or other.
- ♦ Do not use where high moisture and hydrostatic condition and/or recurring moisture problems exist.
- ♦ Do not install over dusty or dirty substrate that could reduce adhesion.
- ♦ Do not store at extreme temperature (hot or cold) and protect from freezing under -12°C (10°F).



4. TECHNICAL DATA

PHYSICAL PROPERTIES (@23° C [73° F] and 50% RH)	
Open time	Up to 20 minutes
Drying time	24-48 hours

MECHANICAL PROPERTIES (@23° C [73° F] and 50% RH)	
VOC content (per Rule # 1168 of California's SCAQMD)	41 g/L
Odor	Very low
pH	8-10
Specific gravity	10.8 - 11.6 lbs/gal (1.30- 1.40 kg/L)
Consistency	Smooth and easy to spread
Solid content	50-65%
Freeze thaw stability	Pass 5 cycles at -12°C (10°F)
Shelf life	
12 months if kept in its original unopened packaging and stored in a dry location. Protect from freezing under -12°C (10°F).	

Approximate coverage per linear m (linear ft)			
	6.4 cm (2.5") wall base	10.2 cm (4") wall base	15.2 cm (6") wall base
3 x 3 x 3 mm (1/8" x 1/8" x 1/8") v-notch trowel			
849 mL (2.8.7 oz)	21-29 (70-95)	12-18 (40-60)	9-12 (30-40)
3.79 L (1 US gal)	94-123 (310 -405)	58-76 (190-250)	40-52 (130 -170)
10 L (2.6 US gal)	240-300 (790-985)	150-185 (490-610)	100-125 (330-410)
15.1 L (4 US gal)	393-462 (1290-1515)	244-287 (800-940)	165-194 (540-635)

5. INSTALLATION

Surface Preparation

- Inspect the area to make sure that all surfaces are sound and clean. 24 hours prior to installation, condition the adhesive and lay the wall base flat at normal room temperature.

Mixing

No mixing is required. This product is ready to use as is. Consult product SDS prior to use.

Application

- Prepare the wall base according to the manufacturer's instructions to fit the internal and external corners. You may require a marker, a knife and a hand groover for this step.
- Apply the adhesive directly on the wall base with a 1/8" v-notched trowel or an appropriate 2, 3 or 5 holes nozzle applicator by making zigzag (the nozzle method may require a trowel pass to spread evenly and prevent normal drying marks from appearing by telegraphy once the adhesive is dried).
- There is no need to let it flash so it can be installed right away.
- Press the base firmly in place and roll the entire surface with a hand roller toward your starting point to prevent stretching and joint opening of the base. Also, the rolling should be done from the top down to push any excess adhesive toward the bottom of the base to prevent any overflow of adhesive at the top.

Cleaning

Wet adhesive can easily be removed with a clean rag and warm soapy water. Dried adhesive can be removed using mineral spirits; however caution should be taken in order to avoid discoloration or other harmful effect on the base material.

Health and Safety

Refer to the Safety Data Sheet (SDS) for complete details.

6. AVAILABILITY AND COST

PROMA products are widely available in Canada and the Northeast United States. To find a distributor of PROMA products, call **toll-free: 1.866.51.PROMA (77662)**.

7. WARRANTY

PROMA warrants that this product is manufactured using quality raw materials and is of merchantable quality and suitable for the purpose for which it was intended. PROMA's liability under this warranty shall be limited to the replacement of its product proven to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising from the use of/or the inability to use this product.

8. MAINTENANCE

Product requires no special maintenance. Do not leave without floor covering.

9. TECHNICAL SERVICE

For more detailed information on this product, please contact our technical department for proper recommendations and job field assistance. **Toll-free: 1.866.51.PROMA (77662)**.

10. FILING SYSTEM

Additional information is available upon request, or by visiting www.proma.ca.

PROMA Adhesives Inc.

9801, Parkway, Anjou, Quebec Canada H1J 1P3

Tel.: 514.852.8585

Fax: 514.852.8225

Toll-free: 1 866.51.PROMA (77662)

Email: info@proma.ca

© 2024 PROMA Adhesives, Inc.

