



Fall protection

REUSEABLE ROOFER'S BRACKET W/ D-RING

ANCHORAGE DEVICES

Forged steel anchorage mounting plate, when is properly installed, provides a safe anchorage point with a minimum tensile strength of 5000 lbs.



Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Oil & Gas (Extraction)

Certifications and norms

ANSI-ASSE Z359.12:2009



CSA Z259.12

Risk Protection



Fall



Fall protection

REUSEABLE ROOFER'S BRACKET W/ D-RING

ANCHORAGE DEVICES

Forged steel anchorage mounting plate, when is properly installed, provides a safe anchorage point with a minimum tensile strength of 5000 lbs.

Standards - Details

Technical details

Type of equipment	Forged anchorage mounting plate with hinged anchor D
Composition of the main support	Steel
Color	Red
Benefits element	D-ring access slot
Weight (lbs)	2.50
Fall arrest work situations	Long vertical movement or movement on inclined surface, Short vertical movement or movement on inclined surface (less than 3 m), Long horizontal movement on horizontal surface, Long horizontal movement on vertical structure








Fall protection

REUSEABLE ROOFER'S BRACKET W/ D-RING

ANCHORAGE DEVICES

Forged steel anchorage mounting plate, when is properly installed, provides a safe anchorage point with a minimum tensile strength of 5000 lbs.

Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
WCA22100	Red	30 m	REUSEABLE ROOFER'S BRACKET W/ D- RING	776285852213	10776285852210	1	1	0.0	0.0	0.0	0.0



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height