



Fall protection

# AN503120JJ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances



### Specific benefits



#### Hygiene

- Can wash harnesses and textiles with neutral soap



#### Ease of Use

- NFC system guarantees traceability



#### Sustainability

- High webbing tenacity thanks to its weave and width

### Applications

- Public Works
- Building
- Finishing Works/Craftsmanship
- Heavy Industry
- Light Industry
- Maintenance

### Certifications and norms



CATEGORY III

ANSI Z359.13-2013 (R2022)



CSA Z259.11-17

### Risk Protection



Fall



*enjoy safety*

Edit 29/08/2025  
[www.deltaplus-usa.com](http://www.deltaplus-usa.com)



Fall protection

# AN503120JJ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

### Standards - Details

### Technical details

Type of equipment	Flat webbing lanyard
Composition of the main support	Galvanized steel, Polyester
Length (m)	1.2
With connector	yes
Color	Black-Yellow
Connector 1	Small hook, steel, opening 21 mm
Ending	2 sewn thimble loops
Connectors (structure side)	Small hook, steel, opening 21 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1.06
Fall arrest work situations	Vertical movement on a permanent structure, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	4








Fall protection

# AN503120JJ

## ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high impact webbing, with 2 wide opening hooks, for short distances

### Logistics Information

Reference	Color	Size	Designation	EAN13	Box Code			Weight			
AN503120JJ	Black-Yellow	1,2 m	AN503120JJ	3295249281182	13295249281189	5	1	6.12 kg	44.0 cm	28.0 cm	15.0 cm



Multiple Sales



Minimum Order Quantity



Box Width



Box Depth



Box Height