

RESISTO

ELASTOMERIC SEALER ALUMINUM

MASTIC



Sealant used to seal membrane joints and self-adhesive sealing strips. It is also used to seal the roof details (valleys, vents, chimney base, etc.) and for caulking windows and doors and to repair various joints, holes and cracks. Reflective aluminum pigments are distributed throughout the product for better UV resistance throughout the product life.

- UV resistant
- Application on dry and wet surfaces
- Excellent resistance to temperature variations.

PRODUCT PURPOSE

Application	Waterproofing complement
Building Part	Roofing
	Doors and windows frames

PRODUCT CHARACTERISTICS

Technology	SBS modified bitumen
Installation Method	Caulk gun
Operating Temperature	-40 °C to 80 °C (-40 °F to 176 °F)

PACKAGING

Code	Format	Quantity per Pallet
65700	310 ml (10oz)	1200

PROPERTIES

Properties	ELASTOMERIC SEALER ALUMINUM
Colour	Aluminum
Specific Gravity	1.22 kg/L (10.2 lb/gal US)
Solids by Weight	85%
Flow or Slippage	NONE within in-service temperature range

(All values are nominal)

ELASTOMERIC SEALER ALUMINUM

INSTALLATION

Storage	Three years in closed original, packaging, in a cool and well-ventilated area. Up to 40 °C (104 °F).
Minimum Application Temperature	-10 °C (14 °F)
Tools Required	 Extruder
Surface Preparation	The substrate must be clean and free of dust, grease or other contaminants.
Installation	Apply ELASTOMERIC SEALER ALU using a standard extrusion gun.
Drying time	Between 4 and 24 hours, depending on ambient temperature and the amount applied.
Tricks / Tips	For an application with an extruder cartridge, do not exceed 1 cm (1/2 in) wide strips.
Recommendations/ Limitations	It is not recommended to use a product containing bitumen directly on softwood boards or flexible polyvinyl chloride.
Warnings	Keep out of reach of children. Close container after each use. Keep out of the sun and away from ignition sources. During use, keep away from ignition sources. No smoking. After application, keep away from flames until solvent has evaporated. Do not pour residue into drains.