



## Wood Stain & Sealer

### UPDATE

---

**December 20, 2022**

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: [techniseal.com](http://techniseal.com)  
Canada and U.S.A.: dial 1 800 465-7325  
Others: dial (514) 523-8324 (Canada)

### APPLICATIONS

---

- Pressure-treated wood, new or old
- **Not suitable for cedar wood**
- Vertical or horizontal surfaces
- Decks, fences, sidings, outdoor furnitures, etc.

### PROPERTIES

---

- Ideal for pressure-treated wood
- Water-repellent
- Will not peel or crack\*

\* When applied as directed.

### DESCRIPTION

---

Techniseal<sup>®</sup> Wood Stain & Sealer is specially formulated to beautify and extend the life of pressure-treated wood. Made from stabilized linseed oil and nanocrystal pigments, it leaves a translucent matt finish. The Wood Stain & Sealer prevents deterioration caused by harmful UV rays, mould, acid rain and freeze-thaw cycles. This waterbased product does not release unpleasant fumes, and is environmentally friendly.

### DIRECTIONS

---

#### BEFORE YOU BEGIN

- **Do not apply to cedar wood.** • Wait 30 days after purchase of pressure-treated wood before applying Wood Stain & Sealer.
- Strip any unknown coating (old paint, stain or varnish) with an appropriate stripper. Use these products only as directed.
- Apply only to bare material, to material previously protected with this product or to a surface treated with Techniseal<sup>®</sup> Wood Preservative. • Wait until the Wood Stain & Sealer is worn before recoating the surface (minimum 2 years).
- **ALWAYS TEST** on a small hidden area of approximately 0.4 m<sup>2</sup> (4 sq. ft.) to ensure that the result meets your expectations (see Warranty).

## SURFACE PREPARATION (ESSENTIAL)

1. Cover adjacent surfaces that are not to be treated.
2. If necessary, apply some Techniseal® Wood Preservative (60102156) to the end cuts.
3. For bare, pressure-treated wood, move on to step 5.
4. For wood previously treated with this product (minimum 2 years): sprinkle a few drops of water on the surface. If water is absorbed quickly, move on to step 5. If water is repelled, do not apply this product and contact Techniseal®.
5. Clean the entire surface with Techniseal® Wood Cleaner (60102038), as directed on the product label.
6. Smoothen rough surfaces with an 80- to 120-grade sandpaper. Vacuum any residue. While sanding the entire surface is not mandatory, it will provide a smoother and more uniform finish. Rust-proof nails and screws should not be apparent.
7. For any other type of none pressure-treated wood: carry out steps 5 and 6 before applying Techniseal® Wood Preservative (60102156), as directed on the product label. Wait at least 48 hours before applying the Wood Stain & Sealer.

## APPLICATION

### Application Conditions:

- Surface must be clean, dry and warm to the touch.
- Temperature must be between 15°C and 25°C.
- No rain forecast for the next 24 hours.
- Use a consistent application method over the entire surface.

### Tools Required:

- 100 mm (4 in.) stain brush with mixed bristles.
- Masking tape, plastic tarp and other protection accessories.
- Airless sprayer (optional) (see instructions below).

This product is ready to use. Do not dilute. Shake well or stir product thoroughly before and during application. Mix contents of different containers to ensure a uniform colour.

Protect horizontal surfaces when applying product to vertical surfaces such as balusters and lattices.

**Single coat application:** If a second coat is desired, it must be applied a few minutes after the first one (wet on wet). Do not trim, as this will create overlap marks. With the stain brush, saturate the wood with a single coat of Wood Stain & Sealer, **one board at a time**. Avoid product accumulation.

With the stain brush, **immediately** remove excess Wood Stain & Sealer on the surface before it dries. Finish the application on one board before moving on to another. Do not stop in the middle of a board or section to avoid overlap marks. Sprayer application is possible on vertical surfaces.

**Airless sprayer application (optional):** This application method is ideal for vertical applications such as fences, posts and lattices. For horizontal surfaces, it is important to ensure proper wood saturation. Avoid product accumulation. With the stain brush, immediately remove excess Wood Stain & Sealer on the surface before it dries.

**Drying:** Product will be dry to the touch in less than 2 hours. Prevent access during that period. Wait 24 hours before walking on the treated surface.

## CAUTION

- Do not apply a second coat if the first one has started to dry because the Wood Stain & Sealer will not adhere and eventually peel and crack.
- Do not apply under scorching sun because the Wood Stain & Sealer will not penetrate which will compromise its durability.
- Greying of wood is not a sign of deterioration, but a natural phenomenon caused by oxidation and the accumulation of organic matter in the capillaries.
- Shaded areas will wear differently than areas often exposed to sunlight.
- Heavy use of the treated surface could limit product longevity. Wait at least 30 days before cleaning the protected wood.

## COVERAGE

3.78 L cover up to 23 m<sup>2</sup> (250 sq. ft.). Consumption will depend on preparation and porosity of the surface to be treated.

## STORAGE

Keep from freezing. Store in a cool, dry place.

## CLEANING & DISPOSAL

Wash tools and hands with warm soapy water. Consult your retailer or municipality regarding the disposal of empty containers or unused product.

## PACKAGING

Colour	Product Code	Retail Size	Units per box	Units per pallet
CEDAR	60102117 (144-353)	3,78 L	2	180
HONEY	60102120 (144-373)	3,78 L	2	180
NATURAL	60102123 (144-383)	3,78 L	2	180
CHOCOLATE	60102118 (144-303)	3,78 L	2	180
MAHOGANY	60102116 (144-333)	3,78 L	2	180
FOREST	60102119 (144-313)	3,78 L	2	180
WALNUT	60102124 (144-323)	3,78 L	2	180
PINE	60102125 (144-343)	3,78 L	2	180

## WARNING

For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

**KEEP OUT OF REACH OF CHILDREN**

## TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit [www.techniseal.com](http://www.techniseal.com) or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

## LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 0.4 m<sup>2</sup> – 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 0.4 m<sup>2</sup> (4 sq. ft.). This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.