

TECHNICAL DATA SHEET

967-041



Ultraprime interior-exterior oil primer is perfect for priming and sealing various surfaces. It blocks stains and tannin and has a low odor. It is a fast-drying formula with ultra-high hiding power and ultra-high adhesion.

- Ultra-adherent
- Ultra-high hiding power
- Low odors
- Fast dry

TYPE OF SURFACES:

Recommended for new, varnished, or previously painted surfaces such as drywall, acoustic ceilings, wood, and well-dried masonry and plaster.

SURFACE PREPARATION:

Surfaces must be dry and clean, free of dust, dirt, grease, oil, wax, mold, and peeling paint. Glossy surfaces must be roughened.

Cracked or flaking coatings must be scraped or removed prior to application. Holes and cracks must be repaired beforehand using a compound suitable for the surface. Remember to cover or mask surfaces that are not to be painted before application.

Allow new stucco, plaster, and masonry surfaces to dry for 15 to 30 days before painting.

APPLICATION METHOD:

Use the product when the surface temperature is above 10°C (50°F). Mix thoroughly before use. A radical change in color may require an additional coat. This product can be applied with a brush (natural silks), roller (lint-free, 10 or 13 mm), or sprayer.

DRYING:

Even if the paint seems dry to the touch, please wait 1 hour before recoating under the following conditions: if the temperature is around 68°F (20°C) and the humidity level is normal. You may need to double the above drying time if the temperature is below 68°F (20°C) or if the humidity level is high.

In more severe conditions, it is recommended to extend the drying time by diluting it with a good quality paint thinner. Use as follows:

- Dry conditions (RH <35%): 190 mL per 3.78 L
- Direct sunlight or high airflow conditions: 225 mL per 3.78 LL
- Maximum dilution: 225 mL per 3.78 L

WARRANTY:

We certify that our products are of high quality and the information contained in this document is provided in good faith. However, since we do not control the conditions of application and surface preparation, the warranty for this product is limited to its purchase price.

DISPOSAL OF RESIDUES:

Use all contents or dispose of appropriately by checking with your local recycling organizations or returning it to your dealer, who will dispose of it properly.

SPREADING RATE:

Data may vary depending on the porosity and texture of the substrate and whether or not dye has been added. See table if applicable.

CLEANING TOOLS:

Tools should be cleaned with mineral spirits shortly after use.

WARNING:

The guidelines apply to most applications. However, they may not cover certain conditions, application techniques, or special surfaces. If you are unsure, check with your retailer or test on a small area.

SAFETY MEASURES:

Use this product only in a well-ventilated area. Do not use this product outdoors. Do not dilute the product. Wash thoroughly after handling the product. Use appropriate protective equipment. Keep out of reach of children.

FIRST AID:

If swallowed, call a poison control center or doctor immediately. If contact with eyes or skin occurs, rinse thoroughly with water.

TECHNICAL SPECIFICATIONS:

Finish / sheen	Matte, 0-2 (at 85°)
Formula	Primer and sealer
Format (s) offered	Quarts and gallons
Color compatibility	Universal and zero-VOC
Resin	Alkyd
Pigment	Titanium dioxide
Solvent	Mineral spirits
Drying time at 20°C (68°F) to 50% HR†	Dry to the touch – 30 min To recover Latex – 1 to 2 h To recover Alkyd – 4 to 6 h To wash – Do not wash
Coverage	± 550-600 ft² per 3.78L
VOC content	Less than 350 g/L
Solids by volume	55 ± 1% Roller – 10 mm Brush – Natural silks
Recommended tools	Paint sprayer - 0.017-0.021 (1,500-2,500 psi)
Surface temperature for application	Minimum – 15°C (59°F) Maximum – 32°C (89°F)
Recommended film thickness	Wet – 4.0 Mills Dry – 1.4 Mills
Adhesion method	Electromechanical
Cohesion process	Oxidation
Viscosity	92 ± 2 KU
Frost resistance	Protect from freezing
Flash point	40.6°C (105°F)
Weight per 3,78 L	7.3 kg (16.20 lbs)