

SPÉCIFICATIONS

MaxCORE™

ITEM	SPÉCIFICATION
Spécifications	Largeur: 185 mm, Longueur: 1,220 mm
Épaisseur	6mm Couche d'usure: 0,7 mm (28mil)
Profile	Bords micro-biseautés
Couverture	2,28 m² par boîte , 114 m² par palette
Planches par boîte	10 Planches
Boîtes par palette	50 Boîtes
Poids	19,5 kg de la boîte, 975 kg de la palette
Composition	SPC de qualité supérieure vierge à 100%: (Compositve polyvinylique de pierre)
Système	Système de verrouillage Unilin®
Application	Résidentiel, commercial et industriel léger
Surface Treatment	Uréthane avec finition en billes de céramique, un revêtement UV 4x
Visual Pattern Repeat	Approx. every 1,200mm (39.37in)
Print pattern repeat	Approx. 1 plank in every 10 boxes
Backing	Sous-couche de réduction sonore IXPE Quiet intégrée
Garantie	10 ans pour usage commercial 25 Ans

PERFORMANCE

ITEM	SPÉCIFICATION
Classification	EN ISO 10582 Domestic Commercial Light Industrial Heavy Class 23 Very Heavy Class 34 Heavy Class 43
Size & Straightness	EN 426 Passes
Thickness	EN 428 Passes
Dimensional Stability	EN 434 Surpasses
Flexibility	EN 435 Passes
Residual Stability	EN 433 Surpasses
Castor Chair	ISO 4918 Passes
Color Fastness To Light	ISO 105-B02 Surpasses
Product-Content Safety	Reach SVHC 163 Passes
Formaldehyde Emission	EN 717-1 0 Mg/M

SPÉCIFICATIONS

MaxCORE™

PERFORMANCE

ITEM	SPECIFICATION	
Slip Resistance — Dry	EN 13893	Surpasses
Slip Resistance — Wet	Din 51130	Surpasses
Chemical Resistance	EN 423	No Effect
Reaction To Fire	EN 13501-1	B _{fl} -S1 Classification
100% Phthlate Free		Yes
100% Waterproof		Yes
Antimicrobial		Yes
Environmental Certification		Floorscore Certified
Scratch/Abrasion		Excellent
Slip Resistance		Class Ds
IIC (Impact Isolation Class)	Impact Sound Absorption	72 Db
STC (Sound Transmission Class)	Traveling Sound Absorption	71 Db
Use With Radiant Flooring		Recommended



100% ÉTANCHE
PERFORMANCE RIGID CORE



LUCIDA®
SURFACES
setting life's stage™

www.LucidaSurfaces.com

Lucida Surfaces USA 845-877-7008
Lucida Surfaces Canada 514-587-9926