

TECHNISCHE PARAMETER

Modellkennung(en)	10032942, 10032943					
Angabe	Symbol	Wert	Einheit	Angabe	Einheit	
Wärmeleistung				Nur bei elektrischen Speicher-Einzelraumheizgeräten: Art der Regelung der Wärmezufuhr		
Nennwärmeleistung	P _{nom}	0,85	kW	Manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	nein	
Mindestwärmeleistung (Richtwert)	P _{min}	0,85	kW	Manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein	
Maximale kontinuierliche Wärmeleistung	P _{max}	0,85	kW	Elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein	
Hilfsstromverbrauch				Wärmeabgabe mit Gebläseunterstützung		
Bei Nennwärmeleistung (Ventilator-Motor)	e _{l,max}	n.a.	kW	Art der Wärmeleistung/Raumtemperaturkontrolle		
Bei Mindestwärmeleistung (Ventilator-Motor)	e _{l,min}	n.a.	kW	Einstufige Wärmeleistung, keine Raumtemperaturkontrolle	nein	
Im Bereitschaftszustand	e _{l,SB}	0,0008	kW	Zwei oder mehr manuell einstellbare Stufen, keine Raumtemperaturkontrolle	nein	
				Raumtemperaturkontrolle mit mechanischem Thermostat	nein	
				Mit elektronischer Raumtemperaturkontrolle	nein	
				Mit elektronischer Raumtemperaturkontrolle und Tageszeitregelung	nein	
				Mit elektronischer Raumtemperaturkontrolle und Wochentagsregelung	ja	
				Sonstige Regelungsoptionen		
				Raumtemperaturkontrolle mit Präsenzerkennung	nein	
				Raumtemperaturkontrolle mit Erkennung offener Fenster	nein	
				Mit Fernbedienungsoption	nein	
				Mit adaptiver Regelung des Heizbeginns	ja	
				Mit Betriebszeitbegrenzung	nein	
Mit Schwarzkugelsensor	nein					
Kontaktangaben	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Deutschland					

TECHNICAL PARAMETERS

Model identifier(s):	10032942, 10032943					
Item	Symbol	Value	Unit	Item	Unit	
Heat output				Type of heat input, for electric storage local space heaters only		
Nominal heat output	P _{nom}	0.85	kW	manual heat charge control, with integrated thermostat	NO	
Minimum heat output (indicative)	P _{min}	0.85	kW	manual heat charge control with room and/or outdoor temperature feedback	NO	
Maximum continuous heat output	P _{max}	0.85	kW	electronic heat charge control with room and/or outdoor temperature feedback	NO	
Auxiliary electricity consumption				fan assisted heat output		
At nominal heat output (fan motor)	e _{l,max}	N/A	kW	Type of heat output/room temperature control		
At minimum heat output (fan motor)	e _{l,min}	N/A	kW	single stage heat output and no room temperature control	NO	
In standby mode	e _{l,SB}	0.0008	kW	Two or more manual stages, no room temperature control	NO	
				with mechanic thermostat room temperature control	NO	
				with electronic room temperature control	NO	
				electronic room temperature control plus day timer	NO	
				electronic room temperature control plus week timer	YES	
				Other control options (multiple selections possible)		
				room temperature control, with presence detection	NO	
				room temperature control, with open window detection	NO	
				with distance control option	NO	
				with adaptive start control	YES	
				with working time limitation	NO	
with black bulb sensor	NO					
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Germany					