

PRODUCT DATA SHEET

Model identifier(s):		10033034				
Item	Symbol	Value	Unit	Item	Unit	
Heat output			Type of heat input, for electric storage local space heaters only			
Nominal heat output	P_{nom}	2.0	kW	manual heat charge control, with integrated thermostat	N/A	
Minimum heat output (indicative)	P_{min}	1.015	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A	
Maximum continuous heat output	$P_{max,c}$	1.944	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A	
Auxiliary electricity consumption			fan assisted heat output			
At nominal heat output (fan motor)	el_{max}	N/A	kW	Type of heat output/room temperature control		
At minimum heat output (fan motor)	el_{min}	N/A	kW	single stage heat output and no room temperature control	no	
In standby mode	el_{sb}	0.000989	kW	Two or more manual stages, no room temperature control	no	
				with mechanic thermostat room temperature control	no	
				with electronic room temperature control	yes	
				electronic room temperature control plus day timer	yes	
				electronic room temperature control plus week timer	o	
				Other control options (multiple selections possible)		
				room temperature control, with presence detection	no	
				room temperature control, with open window detection	no	
				with distance control option	no	
				with adaptive start control	no	
				with working time limitation	no	
with black bulb sensor	no					
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Germany					

PRODUCT DATA SHEET

Model identifier(s):		10033035				
Item	Symbol	Value	Unit	Item	Unit	
Heat output			Type of heat input, for electric storage local space heaters only			
Nominal heat output	P_{nom}	2.5	kW	manual heat charge control, with integrated thermostat	N/A	
Minimum heat output (indicative)	P_{min}	1.012	kW	manual heat charge control with room and/or outdoor temperature feedback	N/A	
Maximum continuous heat output	$P_{max,c}$	2.545	kW	electronic heat charge control with room and/or outdoor temperature feedback	N/A	
Auxiliary electricity consumption			fan assisted heat output			
At nominal heat output (fan motor)	el_{max}	N/A	kW	Type of heat output/room temperature control		
At minimum heat output (fan motor)	el_{min}	N/A	kW	single stage heat output and no room temperature control	no	
In standby mode	el_{sb}	0.000989	kW	Two or more manual stages, no room temperature control	no	
				with mechanic thermostat room temperature control	no	
				with electronic room temperature control	yes	
				electronic room temperature control plus day timer	yes	
				electronic room temperature control plus week timer	o	
				Other control options (multiple selections possible)		
				room temperature control, with presence detection	no	
				room temperature control, with open window detection	no	
				with distance control option	no	
				with adaptive start control	no	
				with working time limitation	no	
with black bulb sensor	no					
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Germany					