

| | |
|---------------|----------------------------|
| Artikelnummer | 10033278 10033279 10033280 |
|---------------|----------------------------|

| | | | | |
|---|--|--|---|---|
| Hersteller | Chal-Tec GmbH Wallstr. 16 10179 Berlin | | 0051 | |
| Produktnname | Goldflame Deluxe | | Artikelnr. | 10033278 10033279 10033280 |
| Verbrauch | 800 g/h (G30) | | 800 g/h - 786 g/h (G31) | |
| Kategorie | I3B/(50) | I3B/P (37) | I3B/P(30) | I3+(28-30/37) |
| Land | AT, CH, DE, SK | PL | BE, CY, DK, EE, FI, FR, HU, IT, LT, NL, NO, SE, SI, SK, RO, HR, TR, BG, IS, LU, MT | BE, CH, CY, CZ, ES, FR, GB, GR, IE, IT, LT, LU, LV, PT, SK, SI |
| Gasdruck nach Gastyp | 50/50 mbar Butan, Propan und deren Gemische | 37/37 mbar Butan, Propan und deren Gemische | 30/30 mbar Butan, Propan und deren Gemische | 28-30 mbar: Butan 37 mbar: Propan |
| Injectorgroße | 1,4 mm | 1,51 mm | 1,67 mm | 1,67 mm |
| <p>Schließen Sie das Ventil der Flüssiggasflasche oder des Reglers nach Gebrauch. Die Verwendung dieses Gerätes in geschlossenen Räumen kann gefährlich sein und ist verboten. Lesen Sie die Anweisungen, bevor Sie dieses Gerät benutzen. Das Gerät muss gemäß den Anweisungen und örtlichen Vorschriften installiert werden.</p> <ol style="list-style-type: none"> 1) Für den Einsatz im Freien oder in gut belüfteten Bereichen. 2) Ein gut belüfteter Bereich muss mindestens 25% der offenen Fläche aufweisen. 3) Die Oberfläche ist die Summe der Oberflächen der Wände. | | | | |

| | |
|-------------|----------------------------|
| Item number | 10033278 10033279 10033280 |
|-------------|----------------------------|

| | | | | |
|--|---|---|---|---|
| Producer | Chal-Tec GmbH Wallstr. 16 10179 Berlin | | | 0051 |
| Item name | Goldflame Deluxe | | Artikelnr. | 10033278 10033279 10033280 |
| Consumption | 800 g/h (G30) | | 800 g/h - 786 g/h (G31) | |
| Category | I3B/(50) | I3B/P (37) | I3B/P(30) | I3+(28-30/37) |
| Country | AT, CH, DE, SK | PL | BE, CY, DK, EE, FI, FR, HU, IT, LT, NL, NO, SE, SI, SK, RO, HR, TR, BG, IS, LU, MT | BE, CH, CY, CZ, ES, FR, GB, GR, IE, IT, LT, LU, LV, PT, SK, SI |
| Gas & Pressure | 50/50 mbar butane, propane and mix of them | 37/37 mbar butane, propane and mix of them | 30/30 mbar butane, propane and mix of them | 28-30 mbar: Butan 37 mbar: Propan |
| Injector diameter | 1,4 mm | 1,51 mm | 1,67 mm | 1,67 mm |
| <p>Close the valve of the LPG cylinder or the regulator after use The use of this appliance in enclosed areas can be dangerous and is PROHIBITED Read the instructions before using this appliance The appliance must be installed in accordance with the instructions and local regulations.</p> <ol style="list-style-type: none"> 1) For use outdoors or in amply ventilated areas 2) An amply ventilated area must have a minimum of 25% of the surface area open 3) The surface area is the sum of the surfaces of the walls. | | | | |