Modellkennung(en)	10035120 10035121 10035122 10035123 10035124 10035125 10035126				
Angabe	Symbol	Wert	Einheit	Angabe	Einheit
Wärmeleistung				**Nur bei elektrischen Speicher-Einzelraumheizgeräten: Art der Regelung der Wärmezufuhr**	
Nennwärmeleistung	P_{nom}	0,5	kW	Manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	nein
Mindestwärmeleistung (Richtwert)	P_{min}	0,0	kW	Manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein
Maximale kontinuierliche Wärmeleistung	$P_{max,c}$	0,5	kW	Elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	nein
Hilfsstromverbrauch				Wärmeabgabe mit Gebläseunterstützung	nein
Bei Nennwärmeleistung	el_{max}	0,5	kW	**Art der Wärmeleistung/Raumtemperaturkontrolle**	
Bei Mindestwärmeleistung	el_{min}	0,000	kW	Einstufige Wärmeleistung keine Raumtemperaturkontrolle	nein
Im Bereitschaftszustand	el_{SB}	0,001	W	Zwei oder mehr manuell einstellbare Stufen keine Raumtemperaturkontrolle	nein
				Raumtemperaturkontrolle mit mechanischem Thermostat	nein
				Mit elektronischer Raumtemperaturkontrolle	nein
				Mit elektronischer Raumtemperaturkontrolle und Tageszeitregelung	nein
				Mit elektronischer Raumtemperaturkontrolle und Wochentagsregelung	ja
				Sonstige Regelungsoptionen	
				Raumtemperaturkontrolle mit Präsenzerkennung	nein
				Raumtemperaturkontrolle mit Erkennung offener Fenster	ja
				Mit Fernbedienungsoption	nein
				Mit adaptiver Regelung des Heizbeginns	nein
				Mit Betriebszeitbegrenzung	nein
				Mit Schwarzkugelsensor	nein
Kontaktangaben	Chal-Tec GmbH Wallstraße 16 10179 Berlin Deutschland				

Model identifier(s):	10035120 10035121 10035122 10035123 10035124 10035125 10035126				
Item	Symbol	Value	Unit	Item	Unit
Heat output				**Type of heat input, for electric storage local space heaters only**	
Nominal heat output	P_{nom}	0.5	kW	manual heat charge control, with integrated thermostat	no
Minimum heat output (indicative)	P_{min}	0.0	kW	manual heat charge control with room and/or outdoor temperature feedback	no
Maximum continuous heat output	$P_{max,c}$	0.5	kW	electronic heat charge control with room and/or outdoor temperature feedback	no
Auxiliary electricity consumption				fan assisted heat output	no
At nominal heat output (fan motor)	el_{max}	0.5	kW	**Type of heat output/room temperature control**	
At minimum heat output (fan motor)	el_{min}	0.000	kW	single stage heat output and no room temperature control	no
In standby mode	el_{SB}	0.001	W	Two or more manual stages, no room temperature control	no
				with mechanic thermostat room temperature control	no
				with electronic room temperature control	no
				electronic room temperature control plus day timer	no
				electronic room temperature control plus week timer	yes
				Other control options (multiple selections possible)	
				room temperature control, with presence detection	no
				room temperature control, with open window detection	yes
				with distance control option	no
				with adaptive start control	no
				with working time limitation	no
				with black bulb sensor	no
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Germany				