

PRODUKTDATENBLATT

Modellkennung(en)	10041817, 10041818				
Angabe	Symbol	Wert	Einheit	Angabe	Einheit
Wärmeleistung				Nur bei elektrischen Speicher-Einzelraumheizgeräten: Art der Regelung der Wärmezufuhr	
Nennwärmeleistung	P _{nom}	0,5	kW	Manuelle Regelung der Wärmezufuhr mit integriertem Thermostat	k.A.
Mindestwärmeleistung (Richtwert)	P _{min}	0,0	kW	Manuelle Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	k.A.
Maximale kontinuierliche Wärmeleistung	P _{max,c}	k.A.	kW	Elektronische Regelung der Wärmezufuhr mit Rückmeldung der Raum- und/oder Außentemperatur	k.A.
Hilfsstromverbrauch				Wärmeabgabe mit Gebläseunterstützung	k.A.
Bei Nennwärmeleistung	eI _{max}	0,5	kW	Art der Wärmeleistung/Raumtemperaturkontrolle	
Bei Mindestwärmeleistung	eI _{min}	0,0	kW	Einstufige Wärmeleistung, keine Raumtemperaturkontrolle	nein
Im Bereitschaftszustand	eI _{SB}	0,001	W	Zwei oder mehr manuell einstellbare Stufen, keine Raumtemperaturkontrolle	nein
				Raumtemperaturkontrolle mit mechanischem Thermostat	nein
				Mit elektronischer Raumtemperaturkontrolle	nein
				Mit elektronischer Raumtemperaturkontrolle und Tageszeitregelung	nein
				Mit elektronischer Raumtemperaturkontrolle und Wochentagsregelung	ja
				Sonstige Regelungsoptionen	
				Raumtemperaturkontrolle mit Präsenzerkennung	nein
				Raumtemperaturkontrolle mit Erkennung offener Fenster	ja
				Mit Fernbedienungsoption	nein
				Mit adaptiver Regelung des Heizbeginns	nein
				Mit Betriebszeitbegrenzung	nein
				Mit Schwarzkugelsensor	nein
Kontaktangaben	Chal-Tec GmbH, Wallstraße 16, 10179, Berlin, Deutschland				

PRODUCT DATA SHEET

Model identifier(s)	10041817, 10041818				
Specification	Symbol	Value	Unit	Specification	Unit
Heat output				Only for electric storage room heaters: Type of heat supply control	
Nominal heat output	P _{nom}	0.5	kW	Manual control of the heat supply with integrated thermostat	N/A
Minimum heat output (guide value)	P _{min}	0.0	kW	Manual control of the heat supply with feedback of the room and/or outside temperature	N/A
Maximum continuous heat output	P _{max,c}	N/A	kW	Electronic control of the heat supply with feedback of the room and/or outside temperature	N/A
Auxiliary power consumption				Heat output with fan support	N/A
Nominal heat output	eI _{max}	0.5	kW	Type of heat output/room temperature control	
With minimum heat output	eI _{min}	0.0	kW	Single stage heat output, no room temperature control	no
Standby mode	eI _{SB}	0.001	W	Two or more manually adjustable levels, no room temperature control	no
				Room temperature control with mechanical thermostat	no
				With electronic room temperature control	no
				With electronic room temperature control and time of day control	no
				With electronic room temperature control and day of week control	yes
				Other regulatory options	
				Room temperature control with presence detection	no
				Room temperature control with open window detection	yes
				With remote control option	no
				With adaptive control of the heating start	no
				With operating time limit	no
				With black ball sensor	no
Contact details	Chal-Tec GmbH, Wallstraße 16, 10179 Berlin, Germany.				