

# S650

# PRO series

**Product Name:** S650

**Product Number:** 700S650

**Description**

white light LED aluminium alloy penlight

## Specifications

|                                             |                                                                    |
|---------------------------------------------|--------------------------------------------------------------------|
| Housing                                     | Aluminium alloy                                                    |
| Lens                                        | Φ32 planoconvex lens                                               |
| On/off switch                               | Tailcap Switch                                                     |
| Battery type                                | AAA battery                                                        |
| Light source                                | XPL-V5/V6                                                          |
| Colour temperature (Kelvin)                 | 6000-7000K                                                         |
| Focus                                       | Focus                                                              |
| Output 30 seconds (lumen)                   | 650 (high) / 90 (low)                                              |
| Max output 3 seconds (lumen)                | 700 (High) / 90 (low)                                              |
| Run time (hours) down to 1 lumen            | 35 (high) / 42 (low)                                               |
| Run time (hours) down to 10% of full lumens | 2 (High) / 7.5 (low)                                               |
| Beam distance (m)                           | 260 (high focus), 60 (high flood) / 90 (low focus), 20 (low flood) |
| Beam width (cm) from 1m distance            | focus 154cm, flood 16cm                                            |
| Protection class                            | IP65                                                               |
| Operating temperature range (Celsius)       | between -20°C and 50°C                                             |



## General Information

|                                    |               |
|------------------------------------|---------------|
| Torch weight (g)                   | 127.5g        |
| Torch dimensions (cm)              | 37 x 137mm    |
| EAN code box (1 pc)                | 5703296700658 |
| EAN code inner carton = 1 display  | 5703296700665 |
| EAN code outer carton = 6 displays | 5703296700672 |
| Harmonized standard code           | 8513100000    |

### Packaging

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Description           | "PRO" design printed box                                        |
| Box size (cm)         | 16.2 x 8 x 7.2                                                  |
| Box weight (g)        | 375                                                             |
| Carton quantity (pcs) | 8 (inner carton) / 32 (outer carton)                            |
| Carton size (cm)      | 33.6 x 17 x 16 (inner carton) / 36 x 34.6 x 35.1 (outer carton) |
| Carton weight (kg)    | 2.89 (inner carton) / 13.4 (outer carton)                       |

### Features

Lightweight torch with sliding focus  
Switch mode: low-high-off  
Supplied with pouch and lanyard



Elwis Lighting A/S, Sandtoften 11, 2820 Gentofte, DK  
www.elwislighting.com - Tel. +45 70 20 10 24

Version 1 11/2020  
© Elwis Lighting 2020  
All details without  
obligation