

SPECIFICATION: 2DX BACKHOE LOADER

ENGINE

KOEL 4R810, NA, water cooled, 36.4 kW (49 hp), 4 cylinder BSIII diesel engine.

TRANSMISSION

The JCB synchro shuttle transmission provide superb drive power in all conditions. It consists of a 4-speed, fully synchromesh, smooth shift gearbox with integral torque convertor and electrically operated reversing shuttle.

HYDRAULIC PUMP FLOW

70.4 lpm @ 2200 rpm

HYDRAULIC PRESSURE

2610 p.s.i.

BRAKES

Hydraulically actuated, dual line, self adjusting compensated oil immersed, multi-disc type on the rear axle.

STEERING

Full power, front wheel hydrostatic power steering with power track road and manual capability in the event of engine or hydraulic power failure.

ELECTRICAL

100 Ampere-hour 12 V battery system with alternator and full road lighting.

TYRES

Front: 7.5 x 16 - 16 PR
Rear: 14.9 x 24 - 12 PR (IT Tyre)

SHIPPING WEIGHT

5500 kgs

WHEELBASE

2.08 m

STANDARD SHOVEL

0.6 cu.m

STANDARD BUCKET CAPACITY

0.18 cu.m

DUMP HEIGHT

2.3 m

LOAD OVER HEIGHT

2.83 m

MAX. DIG DEPTH

3.02 m

MAX. WORKING HEIGHT

3.88 m

LOADER ARM BREAKOUT FORCE

1834 kgf

BUCKET TEAROUT FORCE

3120 kgf

JCB reserves the right to change specifications without prior notice.

EXPERIENCE THE BEST SERVICE



Extended warranty up to 3 year



Best-in-class service



Easy parts availability



Advanced LiveLink

To know more, visit your nearest dealership

