



ELEVATE YOUR BUSINESS WITH UNMATCHED EFFICIENCY



BACKHOE LOADER



High on Fuel Efficiency
Save more on fuel cost



High on performance
Matches all sites
requirement



Best in Class Quality
Reliable & durable
machine



4 Wheel Drive
All terrain capability



Spacious Cabin
More comfort

2 YEAR
STANDARD
WARRANTY
—OR—
4000
HOURS

LIVE JCB LINK

Standard 5 Year
Subscription



BRITISH ENGINEERING

Available Variants

3DX Plus

4WD, Engine Power 92hp,
6-in-1 Shovel,
Bucket - 0.26 cu.m



2DX

4WD, Engine Power 49hp,
GP Shovel,
Bucket - 0.18 cu.m



*T & C Apply.

SPECIFICATION: 3DX BACKHOE LOADER

ENGINE

JCB 448, 4 Cylinder, 56 kW (76 hp)

TRANSMISSION

JCB synchro shuttle transmission provides superb drive power in all conditions. It consists of a 4-speed, full synchromesh gearbox with integral torque convertor and electrically operated reversing power shuttle.

HYDRAULIC PUMP FLOW

108 LPM@2000 rpm

HYDRAULIC PRESSURE

3850 p.s.i.

BRAKES

JCB 'Q' brakes, hydraulically actuated, dual line, self adjusting (compensated), oil immersed multi-disc type on the rear axle.

STEERING

Front wheel full power hydrostatic system utilising the main hydraulic pump via a steering priority valve. In the event of engine failure, emergency steering is maintained.

ELECTRICAL

130 ampere-hour 12 V battery system with alternator and full road lighting

TYRES

Front: 12.5 x 18-12 PR (4WD)
Rear: 16.9 x 28-12 PR (4WD)

SHIPPING WEIGHT

7660 kg

WHEELBASE

2.24 m

STANDARD SHOVEL

1.1 cu.m GP Shovel (6-in-1 shovel as option)

STANDARD BUCKET CAPACITY

0.26 cu.m

DUMP HEIGHT

2.72 m

LOAD OVER HEIGHT

4.18 m

MAX. DIG DEPTH

4.77 m

MAX. WORKING HEIGHT

5.97 m

LOADER ARM BREAKOUT FORCE

4850 kgf

BUCKET TEAROUT FORCE

5700 kgf

All dimensions, weights and timings are variable within 1.5%,
JCB reserves the right to change specifications without prior notice.

EXPERIENCE THE BEST SERVICE



Extended
warranty
up to 3 year



Best-in-class
service



Easy parts
availability



Advanced
LiveLink

To know more, visit your nearest dealership

