

TAKE YOUR BUSINESS TO NEW HEIGHTS.

JCB 3DX_{PLUS}

BACKHOE LOADER







Ver<u>satile</u>



4 Wheel Drive All Terrain Capability



AC Cabin#











*T&C Apply. | #Optional

Available Variants



2DX

4WD, Engine Power 49 hp, GP Shovel, Bucket - 0.18 cu.m 3DX

4WD, Engine Power 76 hp, GP Shovel, Bucket - 0.26 cu.m

SPECIFICATION: 3DX PLUS BACKHOE LOADER

ENGINE

JCB 444, 68.6 kW (92hp) Engine, turbocharged, 4 cylinder, water cooled, diesel engine 408 Nm @1200 rpm.

TRANSMISSION

JCB synchro shuttle transmission: It provides superb drive power in all conditions. It consists of a 4-speed, full synchromesh gearbox with integral torque convertor and electrically operated reversing power shuttle.

HYDRAULIC PUMP FLOW

123 LPM @ 2000 rpm

HYDRAULIC PRESSURE

3300 p.s.i.

BRAKES

Hydraulically actuated dual line, self adjusting, oil immersed, multi-disc type on the rear axle, well protected from dirt, water etc. requiring no maintenance.

STEERING

Front wheel full power hydrostatic system utilising the main hydraulic pump via a steering priority valve. In the event of engine failure, emergency steering is maintained (all models).

ELECTRICAL

130 Ampere-hour 12 V negative ground, utilising wiring and connectors meeting IP69 water ingress test standard. Central fuse panel.

TYRES

Front: 12.5 x 18 - 12 PR Rear: 16.9 x 28 - 12 PR

All Available Variants: 2DX and 3DX

SHIPPING WEIGHT

7660 kg

WHEELBASE

2.24 m

STANDARD SHOVEL

1.0 cu.m (6-in-1

STANDARD BUCKET CAPACITY

0.26 cu.m

DUMP HEIGHT

2.72 m

LOAD OVER HEIGHT

3.23 m

MAX. DIG DEPTH

4.77 m

MAX. WORKING HEIGHT

5.97 m

LOADER ARM BREAKOUT FORCE

4850 kgf

BUCKET TEAROUT FORCE

5700 kgf

EXPERIENCE THE BEST SERVICE









JCB reserves the right to change specifications without prior notice.

