



## GET THE BENEFITS OF 4 MACHINES IN 1 Lift | Load | Grab | Access



Maximum lift height of 7m\* & 11m\*.



Maximum lift capacity up to 3000 Kg\*.



Q-Fit mechanism for quick change of attachment.



360° Hi-Viz global cabin design with ROPS & FOPS.



LiveLink stay connected 24x7





JCE

## SPECIFICATION: TELEHANDLER

Specifications	530-70	530-110
Engine	JCB 448 Naturally Aspirated, 4 Cylinder, Displacement 4.8 L, Gross power 56 kW (76 hp) Max torque 310 Nm	
Transmission	JCB shyncro shuttle transmission, smooth shift gear box with an integral torque convertor and an electrically operated reversing shuttle.	
Hydraulic pump flow (lpm) @2200 rpm	100	
Hydraulic pressure (p.s.i)	3 5 5 3	
Brakes	Hydraulically actuated, dual line, self adjusting, compensated oil immersed, multi-disc type on the front axle, operated through independent pedals, linked together for normal use. Two independently operating foot pedals enable machine to maneuvre in tight spaces.	
Steering	Rear-wheel hydrostatic power steering with manual capability in the event of engine or hydraulic power failure.	
Electrical	130 Ampere-hour 12 V battery system with alternator and full road lighting. Dust and water proof IP69 electrical connectors.	
Tyres	Front: 13.00 x 24 -16PR, Rear 12.5 x18-12 PR Industrial traction pattern Tyre, Tyre option- HD Tyres/Extra HD Tyres/Solid Tyres	
Wheelbase (m)	2.54	
Operating weight (kg)	7510	9490
Maximum lift capacity (kg)	3 000	3 000
Lift capacity to full height	2 500	3 000*
Lift capacity to full reach	1210	1400
Lift Height (m)	7	11
Maximum forward reach (m)	3.83	7.46
Reach with 1 tonne load (m) Placing height (m)	6.3	10.5

All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependent upon the exact specification of machine.

**EXPERIENCE THE BEST SERVICE** 









\*With stabilisers extended



To know more, visit your nearest dealership