

**RAPIDWAY™ 3-BOLT ELONGATED
FLUSHOMETER TOILET**

- 3-Bolt wall-mounted flushometer valve toilet, less seat
- Vitreous china
- Low consumption, operates at 1.6 gpf/6.0 Lpf
- Blowout bowl design
- Elongated bowl
- 1-1/2" inlet spud
- Fully-glazed 2-1/8" trapway
- 10" x 12" water surface area

- 3445J.101** Elongated bowl only, top spud
- 3445L.101** Elongated bowl only, back spud

Component Parts:

- 047007-0070A** Inlet Spud (furnished with bowl)

Nominal Dimensions:

660 x 356 x 394mm
(26" x 14" x 15-1/2")

Recommended working pressure—between
25 psi at valve when flushing and 80 psi static

Fixture only, less seat, bolt caps, and
flushometer valve

Compliance Certifications -

Meets or Exceeds the Following Specifications:

- ASME A112.19.2/CSA B45.1 for Vitreous
China Fixtures



3445J.101 Rapidway 3-Bolt Top Spud



3445L.101 Rapidway 3-Bolt Back Spud

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White
- Seat:
 - American Standard #5901.100 Heavy duty
open front less cover
 - American Standard #5901.110T Heavy duty
open front less cover with stainless steel check hinge
and EverClean®
- Flushometer Valve:
 - 1.6 gpf:
 - Sensor-Operated: American Standard Selectronic®
DC Power #6065.161.002 (Top Spud)
PWRX #6066.161.002 (Top Spud)
AC Power #6067.161.002 (Top Spud)
 - Manual: American Standard #6047.161.002 (Top Spud)
 - Selectronic® Battery:
6065.262.007 or 6065.362.007 (Back Spud)
 - Selectronic® Plug-in AC:
6067.262.007 or 6067.362.007 (Back Spud)



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES
AND ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE
BUILDING FACILITIES - CHECK LOCAL CODES.

- When installed so top of seat is 432 to 483mm (17" to 19") from the
finished floor.

