
SUBMITTAL DATA SHEET

No-Lead Pex Ball Valves - Specialty Ball Valves Pex Ball Valve - 72030EP

Pex x Pex




A.Y. McDonald Mfg. Co. No-Lead Pex Ball Valves are constructed from heavy duty no-lead brass and are designed for use with potable water in commercial, industrial, and residential applications.



Dimensions

Size	Α	В	С	Weight
1/2"	3.0	1.3	2.32	0.23
3/4"	3.0	1.5	2.54	0.32
1"	4.5	2.0	3.35	0.70
1 1/4"	5.1	2.2	3.57	0.91



Materials

No.	Part	Material			
1	Body	No-Lead Brass			
2	Seat Ring	Teflon			
3	Ball	No-Lead Brass			
4	Сар	No-Lead Brass			
5	Stem	No-Lead Brass			
6	0-ring	NBR			
7	Packing	Teflon			
8	Nut	Zinc			
9	Handle	Zinc Plated w/Vinyl Cover			

SUBMITTAL INFORMATION

Sizes: 1/2" - 1 1/4"

Double O-ring packing

Pex ends conform to ASTM F1807

Blowout proof stem

NSF-372

- NSF/ANSI 61-2013

NSF/ANSI 14-2010a **400 CWP**

IGC-157-2013

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



A.Y. McDonald Mfg. Co.

P.O. Box 508

Dubuque, IA 52004-0508

Toll Free: 1-800-292-2737 Fax: 1-800-832-9296

Hours: 7:00 a.m. - 5:00 p.m., CST

sales@aymcdonald.com www.aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by: 02-16