For Residential and Commercial Applications				
Job Name		Engineer / Architect		
Job Location		Wholesaler		
Submittal Date		Contractor		

B0-**IM & B1**IM Speedi Plumb® PLUS Braided Icemaker, **Humidifier, & Water Filter Connector**

For use in potable water distribution systems in accessible locations only. Use:

Design Features:

- Engineered polymer braided fibers bend freely without kinking or crimping
- TPE inner hose ensures durability
- Rubber washers provide a large pliable sealing surface and ensure a long lasting water-tight connection
- **8-sided pneumatic crimp** provides greater dependability for reliable nut-to-hose connections



Operating Specifications:

Temperature: 40°-140° F, intermittent to 180° F

Pressure: 125 PSI maximum

Tubing Diameter: 0.245" ID (0.470" OD)

MATERIAL SPECIFICATIONS			
Inner Hose	TPE		
Braiding	PVC coated polyester yarn		
Barb	Brass		
Ferrule	Zinc-plated steel		
Washer	Rubber		
Compression Nut	Brass, chrome plated		

Dart Lictina

Part	Part Listing:		
	B0-12IM	1/4" compression x 1/4" compression x 12" length	
	B0-12IM F	1/4" compression x 1/4" compression x 12" length, flag labeled	
	B0-60IM	1/4" compression x 1/4" compression x 60" length	
	B0-60IM F	1/4" compression x 1/4" compression x 60" length, flag labeled	
	B0-60IM P	1/4" compression x 1/4" compression x 60" length, bagged	
	B0-72IM	1/4" compression x 1/4" compression x 72" length	
	B0-72IM F	1/4" compression x 1/4" compression x 72" length, flag labeled	
	B0-72IM P	1/4" compression x 1/4" compression x 72" length, bagged	
	B0-84IM	1/4" compression x 1/4" compression x 84" length	

This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft Mfg. This specification must be returned to BrassCraft Mfg. if requested.






B0-**IM & B1**IM Speedi Plumb® PLUS Braided Icemaker, **Humidifier**, & Water Filter Connector

Part Listing (con't):

B0-84IM P	1/4" compression x 1/4" compression x 84" length, bagged
B0-96IM	1/4" compression x 1/4" compression x 96" length
B0-96IM P	1/4" compression x 1/4" compression x 96" length, bagged
B0-120IM	1/4" compression x 1/4" compression x 120" length
B0-120IM P	1/4" compression x 1/4" compression x 120" length, bagged



PART DIMENSIONS (Inches)		
Model	DIM. A	
B0-12IM	12.0 / 13.0	
B0-60IM	60.0 / 61.0	
B0-72IM	72.0 / 73.0	
B0-84IM	84.0 / 85.0	

PART DIMENSIONS (Inches)		
Model	DIM. A	
B0-96IM	96.0 / 97.0	
B0-120IM	120.0 / 121.0	

Listings & Certifications:

- IAPMO listed to ASME A112.18.6 and CSA B125.6 (File # 0452)
- CSA listed to ASME A112.18.6 and CSA B125.6 (File #204593)
- No-Lead product CSA listed to Low-Lead Content Certification Program – Plumbing Products Class 6853-01







