Filter Housings

Filter Housings come in different sizes, colors, materials of construction and offer different features.

Here is a quick breakdown:

- Size Required flow rates and installation space will determine the size of the housing. Housings typically come in four sizes: 2.5"x 10", 2.5"x 20", 4.5"x 10", 4.5"x 20"
- Color Transparent or Opaque (Blue). Transparent housings allow for visual inspection of the cartridges but are less durable and not suitable for outdoor applications.
- Material of Construction Plastic is standard for most applications. Stainless steel is used for higher temperature applications.

Features - Some housings provide additional unique features:

- Valve-in-Head allows you to bypass or shut off the water during cartridge replacement.
- Pressure Relief Button relieves pressure from the housing prior to changing cartridge
- Stainless Steel Threads reduces possibility of cross threading and allows for tighter pipe fit
- Double O-Ring ensures added seal insurance protecting from leaks



Double O-Ring Seal



Pressure Relief Button



Valve-in-Head

Filter Housing Kits

All Aqua Flo® Point-of-Use Water Filter Housings are easy to install and come with a mounting bracket and hardware plus sump wrench for easy sump removal. Filter cartridges are sold separately.



Sump Wrench



Mounting Bracket and Hardware

WARNING:

Do not use on drinking water supplies, which are microbiologically unsafe or of unknown quality without first adequately disinfecting the water. Protect against freezing to prevent cracking of the filter and water leakage.

NOTE:

All dimensions and micron ratings are nominal. The manufacturer reserves the right to make product improvements which may deviate from the specifications and descriptions stated herein, without obligation to change previously manufactured products or to note the change

We recommended replacing the clear sump every 5 years. Do not subject to freezing temperatures.

Filter Housings











P-H-PR-20BV

P-H-PR-20

P-H-PR-10BV

P-SL-10-1/2-NPR

Aqua Flo Platinum™ Housings

Item #	Model Description	Features	Filter Size (In)	Inlet/Outlet Size NPT (In)	Color	Flow Rate (USGPM	Dimensions A X B (In)	Weight (Lbs)	Certification
36051	HOUSING, P-H-PR-10-34	Pressure Relief, Double O-Ring	2.5" x 10"	3/4"	Blue	4	5 X 12	4	NSF 42
36053	HOUSING, P-H-PR-10BV-1	Pressure Relief, Double O-Ring	4.5" x 10"	1"	Blue	15	7 X 14	6	NSF 42
36112	HOUSING, P-H-PR-20BV-1	Pressure Relief, Double O-Ring	4.5" X 20"	1"	Blue	20	7 X 24	8	NSF 42
36237	HOUSING, P-SL-10-1/2-NPR	NA	2.5" x 10"	1/2"	Blue	4	4 X 12	4	NSF 42
36273	HOUSING, P-H-PR-20-34	Pressure Relief, Double O-Ring	2.5" x 10"	3/4"	Blue	4	5 X 23	7	NSF 42

^{*}NSF-42 for Material Safety and Structural Integrity Only

Aqua Flo™ Housings

Item #	Model Description	Features	Filter Size (In)	Inlet/Outlet Size NPT (In)	Color	Flow Rate (USGPM	Dimensions A X B (In)	Weight (Lbs)	Certification
26065	HOUSING, WVIH34SS	Valve-in-Head, SS Thread	2.5" x 10"	3/4"	Clear	4	5" x 13.5"	4	No
26066	HOUSING, WCT34SS	Pressure Relief, SS Threads	2.5" x 10"	3/4"	Clear	4	5.25" x 12.25"	4	No
26258	HOUSING, H-PR-10BV-1	Pressure Relief	4.5" x 10"	1"	Blue	15	7.25" x 14"	6	No
26259	HOUSING, H-PR-20BV-1	Pressure Relief	4.5" x 20"	1"	Blue	20	7.25" x 24"	8	No
26261	HOUSING, H-PR-20BV-34	Pressure Relief	4.5" x 20"	3/4"	Blue	20	7.25" x 24"	8	No
26262	HOUSING, H-PR-10BV-34	Pressure Relief	4.5" x 10"	3/4"	Blue	15	7.25" x 14"	6	No
26263	HOUSING, H-PR-20BV-15	Pressure Relief	4.5" x 20"	1.5"	Blue	20	7.25" x 24"	7	No
26264	HOUSING, H-PR-10-34	Pressure Relief	2.5" x 10"	3/4"	Blue	4	5.25" x 12.25"	4	No
26265	HOUSING, H-PR-20-34	Pressure Relief	2.5" x 20"	3/4"	Blue	4	5.25" x 22.5"	7	No
65020006	HOUSING, APC34	Pressure Relief	2.5" x 10"	3/4"	Clear	4	5.25" x 12.25"	3	No
65020007	HOUSING, VIH34	Valve-in-Head	2.5" x 10"	3/4"	Clear	4	5" x 13.5"	4	No

Specifications:

◆ Max. Water Temperature: 30°C (100°F)

♦ Min. Water Temperature: 2°C (35°F)

Max. Water Pressure; 100 psi (689 kPa)

◆ Materials of Construction: Reinforced Polypropylene (cap and blue sump) & Styrene-Acrilonitrile (clear sump)

♦ Housing O-Ring: EPDM

Pressure Relief Button: Nylon

◆ Limited One Year Warranty



WVIH34SS



H-PR-20BV



APC34

H-PR-10BV H-PR-10

WCT34SS