# **Accessories**

# TECK® COMMERCIAL



### **SPECIFICATION:** (example)

(Recommended for use with #0 Surface Mount Control Box on Series 1500T, 1501T, 3000T3 and 3001T3 Electronic Faucets)

- Deck mount mixing valve
- The design of this mixing valve does not allow for complete shut-off
- Solid brass fabricated body
- Polished chrome plated finish
- DELTA® washerless stainless steel rotating ball cartridge
- Handle rotation limit stop
- Flexible, braided connector hose to solenoid
- Integral checks
- Removable inlet filter screens

#### □ 24T3003

 152 mm (6") lever blade handle, color indexed, ADA compliant, vandal resistant

#### □ 24T3001

 70 mm (2.75") lever blade handle, color indexed, ADA compliant, vandal resistant



## **Approvals:**

- CSA certified
- Complies to ASME A112.18.1/CSA B125.1
- Indicates compliance to ICC/ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulations

(Contact Delta Representative for State and/or Local Approvals.)

# **DECK MOUNT MIXING VALVE** Recommended for use with #0 Surface Mount Control Box on Series 1500T, 1501T, 3000T3 and 3001T3 Electronic Faucets 24T3003 130mm (5.1") 224mm (8.8") 200mm (7.9") (2.0")35mm DIA. (1.38") MIN. HOLE REQUIRED WASHER 40m (1.56") MAX. SPACER -TO SOLENOID (If Required) WRENCH 3/8" COMPRESSION 3/8" COMPRESSION CONNECTION CONNECTION **.....**} -(- ..... FLEXIBLE STAINLESS STEEL HOSE - 610mm (24") 10mm (3/8") DIA.TUBES 254mm (10") LONG 1/2"-14 NPSM INLET FOR 3/8" OR 1/2" FLEXIBLE RISER OR 1/2-14 NPSM COUPLING NUT (NOT SUPPLIED) 24T3001 148mm (4.8") (5.8") (2.0") WASHER ~35mm DIA (1 38") MIN SPACER (1.56") MAX. HOLE RÉQUIRED TO SOLENOID TO SOLENOID (If Required)

WRENCH

10mm (3/8") DIA.TUBES 254mm (10") LONG

INLET FOR 3/8" OR 1/2" FLEXIBLE RISER OR 1/2-14 NPSM COUPLING NUT (NOT SUPPLIED)

3/8" COMPRESSION CONNECTION

FLEXIBLE STAINLESS STEEL HOSE - 610mm (24") 3/8" COMPRESSION CONNECTION

1/2"-14 NPSM