

Tub and Shower

TRIM ONLY MultiChoice™ Universal Thermostatic shower valve - requires separate order of R10000-UNWS Rough-in

Model No: T17TH125

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- Lindicates compliance to ICC/ANSI A117.1
- Thermostatic Valve ASSE 1016
- Volume Control lever handle ADA compliant to ICC/ANSI A117.1/ADA
- (Contact Delta Representative for State and/or Local Approvals)





NOTES:

T17TH2 - MultiChoice[™] Universal Thermostatic - Shower Valve & Diverter Spout

T17TH3 - MultiChoice™ Universal Thermostatic - Shower Valve & Diverter Valve

T17TH9 - MultiChoice™ Universal Thermostatic - Shower Valve, Diverter Spout & Diverter Valve

SPECIFICATION:


- TempAssure® 17T Thermostatic cartridge
- Thermostatic wax element maintains the outlet temperature to +/- 3.6 F
- Polished chrome plated finish
- Non-removeable red/blue temperature markings
- Cartridge rated minimum 1.7 gpm @45 psi (6.4 L/min @ 310kPa)
- Separate ROUGH-IN R10000-UNWS required
- Lever volume control, field adustable to limit rotation into the hot water zone; temperature adjustment dial
- Handle#: 5 Metal Lever Volume Control Handle w/Temperature Adjustment
- #2 Shower 3-Function Touch-Clean Showerhead, Arm & Flange
- #2 Shower Flow Rate MAX: 1.75GPM @ 80 PSI (6.6 L/min @ 552 kPa)
- #2 Shower Flow Rate MIN: 1.5 GPM @ 45 PSI (5.7 L/min @ 310 kPa)

OPERATION:

Not Available

(Dimensional drawing on following page)





Delta reserves the right (1) to make changes to specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference. Measurement may vary plus or minus 6mm(0.25"). Mounting locations are suggested only. Check with local codes for requirements in your area. This spec was produced February 22, 2018.