

## Elkay SwirlFlo Bi-Level Fountain Mechanical Bubbler with In-Wall Carrier Non-Filtered Non-Refrigerated Stainless

**Model EDFPBM117C** 


### PRODUCT SPECIFICATIONS

Elkay SwirlFlo Bi-Level Fountain Mechanical Bubbler with In-Wall Carrier Non-Filtered Non-Refrigerated Stainless. Furnished with Flexi-Guard ® Safety Bubbler. Mechanical Front Bubbler Button activation. Product shall be Wall Mount (On Wall), for Indoor + Outdoor applications, serving 2 station(s).

Finish:	Stainless Steel		
Power:	No Electrical Required		
Bubbler Style:	Flexi-Guard ® Safety Bubbler		
Activation by:	Mechanical Front Bubbler Button		
Mounting Type:	Wall Mount (On Wall)		
Chilling Capacity:	Non-refrigerated		
Dimensions (L x W x H):	38-1/2" x 19" x 21-15/16"		
Approx. Shipping Weight:	72 lbs.		
Installation Location:	Indoor + Outdoor		
No. of Stations Served:	2		

\*\*When used in non-temperature controlled environments, unit(s) must be adequately winterized and/or protected from extreme heat to prevent damage where climates dictate.

 Mechanically-Activated unit continues to supply water in event of service disruptions.



Included with Product:

Fountain with Back Plate, and Surface Mounting

#### Ships in one box.

A Century of Tradition and Quality. For more than 100 years, Elkay has been making innovative products and providing exceptional customer care. We take pride in offering plumbing products that make life easier, inspire change and leave the world a better place.



#### PRODUCT COMPLIANCE

ADA & ICC A117.1 ASME A112.19.3/CSA B45.4 NSF/ANSI 61 (Q≤1) & 372 (lead free) NSF REG4







Complies with ADA & ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards. Installation may require additional components and/or construction features to be fully compliant. Consult the local Authority Having Jurisdiction if necessary.

Installation Instructions (PDF) - 97922C

Water Systems are warranted for 12 months from date of installation. Warranty pertains to drinking water applications only. Non-drinking water applications are not covered under warranty. Warranty (PDF)

PART:	QTY:
PROJECT:	
CONTACT:	
DATE:	
NOTES:	
APPROVAL:	

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



## Elkay SwirlFlo Bi-Level Fountain Mechanical Bubbler with In-Wall Carrier Non-Filtered Non-Refrigerated Stainless

Λ	Λo	del	ED	FP	RM	111	70
ш	Nυ	uei		ГГ			<i>' L</i>

Optional Accessories					
<u>EWF172</u>	Elkay Universal Filtration Kit (1500-Gallon)  Spec Sheet (PDF)	(Eq.)			
AP99	Elkay Access Panel 9" x 9" x 6"  Spec Sheet (PDF)	35000m			
ACCESS12X38-5	Stainless Steel Access Panel for Bi-Level Architectural Fountains  Spec Sheet (PDF)				

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.



# Elkay SwirlFlo Bi-Level Fountain Mechanical Bubbler with In-Wall Carrier Non-Filtered Non-Refrigerated Stainless Model EDFPBM117C

#### OPERATION OF QUICK CONNECT FITTINGS **INSTALLER NOTE** 1/4" O.D. TUBE WATER INLET TO COOLER 3/8" O.D. TUBE CONNECT COLD WATER SUPPLY This drinking fountain is furnished with a bubbler **BUILDING WATER** SIMPLY PUSH IN TUBE TO ATTACH TUBE IS SECURED IN POSITION PUSH IN COLLET TO RELEASE TUBE and valve including all connecting fittings which are manufactured of completely lead free material. -0407 Shut off valve (not furnished) to accept 3/8" O.D. unplated copper tube. • UV77/-PUSHING TUBE IN BEFORE PULLING IT OUT HELPS TO RELEASE TUBE These products are designed to operate on 20 psi to 105 psi supply line pressure. Simultaneous operation of both bubblers on a bi-level NOTE: WATERFLOR DIRECTION unit may not be possible depending on water supply pressure. If simultaneous operation is desired, please ensure a minimum of 50 (NOT FURNISHED) 18-3/4" (476mm) WASTE ELBOW EXTENSION AND TRAP BY OTHERS (SHOWN WITHIN WALLS) 9-7/8" (251mm) 1-5/8 (41mm) 1-5/8". (41mm) 21-15/16" (557mm) 1-1/4" I.P.S. WASTE (LEFT OR RIGHT) 41-11/16" (1059mm) 33-15/16" (863mm) (229mm) 27" (686mm) ADA REQUIREMENT (229mm) 1/2" AP99 (22 ACCESS PANELS (OPTIONAL) 3/8" I.P.S. SUPPL' (LEFT OR RIGHT) 14" (356mm) 16-1/2" (419mm) ACCESS REQUIRED FOR INSTALLATION FINISHED FLOOR 111 /// NOTE: REINFORCE THE WALL IN THE SHADED AREAS TO SUPPORT UP TO 300 LBS. STATIC LOAD SURFACE MOUNTING PLATE INSTRUCTIONS 1/4" (6mm) Ø HOLES FOR MOUNTING PLATE TO WALL 18-3/4" (476mm) LOAD BEARING WALL CONSTRUCTION \_ 1-1/4" (32mm) SURFACE MOUNTING PLATE 5/8" (16mm) -5/16"-18 THREADED HOLES FOR MOUNTING FOUNTAINS TO WALL 1 4 4 0 3/8" (10mm) Ø HOLES FOR **+** (BY OTHERS) ATTACH SURFACE MOUNTING PLATE TO FINISHED WALL MOUNTING PLATE TO WALL (20) .0. 20-1/8" (511mm) WASTE 1-1/4" I.P.S. LEFT OR RIGHT SIDE WASTE IS SHOWN IN WALL BUT MAY 0 INSTALL (12) 5/16" (8mm) LAG SCREWS OR EQUIVALENT WITH FLAT WASHERS BE BEHIND WALL WASTE \_ TRAP (BY OTHERS) 11-15 29-1/4" (743mm) OTHERS) 8" (203mm) (940mm) — SUPPLY — (SHUT OFF BY OTHERS) 36-1/2" (927mm) 21-1/2" (564mm) 3/8" I.P.S. SUPPLY (LEFT OR RIGHT) OPENINGS FOR (2) OPTIONAL AP99 14-1/4" (362mm) 16-1/2" (419mm) (476mm)

In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.

FINISHED FLOOR FRONT VIEW

SIDE VIEW