

# **800 Large Diameter Series**

APOLLOXPRESS® Press End Copper Coupling
CxC with Stop (2 ½" through 4")



Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	







#### DESCRIPTION

The APOLLOXPRESS® 800 Large Diameter Press Coupling features a Lead-Free dezincification resistant copper body, a patented stainless-steel solid cross-section Grab Ring, a Nylon Separation Ring and an EPDM O-Ring. Our Large Diameter APOLLOXPRESS® products are manufactured utilizing proven ASTM materials and standards. Proudly Made In The USA.

#### **FEATURES**

- Lead-Free Construction
- Leak-Before-Press Technology
- Visual element, Break Away Band (Pat. Pending)
- Compatible with XL-C™ Pressing Tools
- Approved for underground installation (per local installation code)
- Use with hard/soft ASTM B88 K, L & M Copper Tube
- Made in USA
- cUPC® Compliant
- ARRA Compliant

#### PERFORMANCE RATING

- Maximum Pressure: 200 psi
- Temperature Range: o°F to 250°F depending on application. Hot Water up to 250°F, Chilled Water down to 33°F

# **APPROVALS**

- NSF/ANSI NSF 61 ~ Water Quality
- NSF/ANSI NSF-372 ~ Lead Free (LF)
- IAPMO File Listings: 4861, 6174 & N-4951

# **APOLLOXPRESS**

- Large Diameter Sizes 2 1/2", 3" & 4"
- Model 800, Coupling with Stop C x C.


### STANDARD MATERIALS

Part Name	Material				
Body	UNS C12200 Copper				
Grab Ring	304 / 306 Stainless Steel				
Spacer Ring	Nylon 66				
O-Ring	EPDM				
Lubrication	Silicone, ANSI/NSF-61 Listed				

# **DIMENSIONS**

		Dimension (in.)								
Item No.	Description	Α	В	C*	D**	E*	Height	Width	Depth	Weight
10061947	800 2½ CxC	4.33	3.16	1.90	0.53	1.90	3.16	4.33	3.16	1.01
10061952	800 3 CxC	4.65	3.68	2.10	0.46	2.10	3.68	4.65	3.68	1.48
10061957	800 4 CxC	5.53	4.70	2.50	0.53	2.50	4.70	5.53	4.70	2.67

<sup>\*</sup> Tolerance +/- .02"



#### **Elkhart Products Corporation**

1255 Oak Street, Elkhart, IN 46514 www.elkhartproducts.com | (574) 264-3181

This specification is provided for reference only. Elkhart Products Corporation reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Elkhart products previously or subsequently sold.



<sup>\*\*</sup> Tolerance +.15 / -.03