

FIG. 7062

Bullhead Tee (GR x GR x FPT)




FIGURE 7062 BULLHEAD TEE
(GR x GR x FPT)

Nominal Size	Center to End of Run	Center to End of Branch	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	Lbs./Kg
5 x 5 x 8 125 x 125 x 200	7¾ 197	5½ 140	31.0 14.1
6 x 6 x 8 150 x 150 x 200	7¾ 197	6½ 165	37.6 17.1

See Fitting Size chart on next page for O.D.

These fittings are designed to provide minimal pressure drop and uniform strength. Pressure ratings of Gruvlok Fittings conforms to those of Fig. 7001 Gruvlok Standard Coupling.



FIG. 7065

Standpipe Tee (GR x GR x FPT)




FIGURE 7065 STANDPIPE TEE
(GR x GR x FPT)


Nominal Size	O.D.	Center to End of Run	Center to End of Branch	Approx. Wt. Ea.
In./DN(mm)	In./mm	In./mm	In./mm	Lbs./Kg
4 x 4 x 2½ 100 x 100 x 65	4.500 114.3	3¼ 83	4 102	7.6 3.4
6 x 6 x 2½ 150 x 150 x 65	6.625 168.3	3¼ 83	5⅞ 130	11.2 5.1

See Fitting Size chart on next page for O.D.

These fittings are designed to provide minimal pressure drop and uniform strength. Pressure ratings of Gruvlok Fittings conforms to those of Fig. 7001 Gruvlok Standard Coupling.

FIG. 7050DR

90° Drain elbow



Available fabricated Schedule 10/40.
Drain elbow has a standard 1" female NPT outlet.

FIGURE 7050DR 90° DRAIN ELBOW

Nominal Size	O.D.	Max Working Pressure	Dimensions		Approx. Wt. Ea.
			C to E	H	
In./DN(mm)	In./mm	PSI/bar	In./mm	In./mm	Lbs./Kg
1¼ 32	1.660 42.2	300 20.7	2¾ 69	1¾ 44	0.7 0.3
1½ 40	1.900 48.3	300 20.7	2¾ 69	1¾ 44	1.7 0.8
2 50	2.375 60.3	300 20.7	3¼ 83	1¾ 44	2.0 0.9
2½ 65	2.875 73.0	300 20.7	3¾ 95	1⅞ 48	2.5 1.1
3 80	3.500 88.9	300 20.7	4¼ 108	2 51	3.2 1.5
4 100	4.500 114.3	300 20.7	5 127	2¼ 57	4.6 2.1
5 125	5.583 141.3	300 20.7	5½ 140	2⅝ 60	11.5 5.2
6 150	6.625 168.3	300 20.7	6½ 165	2⅝ 60	9.6 4.4
8 200	8.625 219.1	300 20.7	7¾ 197	2½ 64	15.8 7.2
10 250	10.750 273.1	300 20.7	9 229	2¾ 69	48.5 22.0
12 300	12.750 323.9	300 20.7	10 254	2¾ 69	66.0 29.0

PROJECT INFORMATION

APPROVAL STAMP


Project:	☐ Approved
Address:	☐ Approved as noted
Contractor:	☐ Not approved
Engineer:	Remarks:
Submittal Date:	
Notes 1:	
Notes 2:	

Gruvlok fittings are available through 24" nominal pipe size in a variety of styles. Use the Fitting Size Table to convert nominal pipe size to corresponding pipe O.D.

These fittings are designed to provide minimum pressure drop and uniform strength.

Depending on styles and size, Gruvlok fittings are provided in various materials including ductile iron, forged steel or fabricated steel.

Pressure ratings of Gruvlok standard fittings conform to those of Fig. 7001 Gruvlok coupling.



FLOW DATA – FRICTIONAL RESISTANCE (EXPRESSED AS EQUIVALENT STRAIGHT PIPE)

Nom. Size	O.D.	Pipe Wall Thickness	Elbow		Tee	
			90°	45°	Branch	Run
In./DN(mm)	In./mm	In./mm	ft./m	ft./m	ft./m	ft./m
1	1.315	0.133	1.7	0.9	4.4	1.7
25	33.4	3.4	0.5	0.3	1.3	0.5
1 1/4	1.660	0.140	2.3	1.2	5.8	2.3
32	42.2	3.6	0.7	0.4	1.8	0.7
1 1/2	1.900	0.145	2.7	1.3	6.7	2.7
40	48.3	3.7	0.8	0.4	2.0	0.8
2	2.375	0.154	3.4	1.7	8.6	3.4
50	60.3	3.9	1.0	0.5	2.6	1.0
2 1/2	2.875	0.203	4.1	2.1	10.3	4.1
65	73.0	5.2	1.2	0.6	3.1	1.2
3 O.D.	2.996	0.197	4.3	2.2	10.8	4.3
76.1	76.1	5.0	1.3	0.7	3.3	1.3
3	3.500	0.216	5.1	2.6	12.8	5.1
80	88.9	5.5	1.6	0.8	3.9	1.6
4 1/4 O.D.	4.250	0.220	6.4	3.2	16.1	6.4
108.0	108.0	5.6	2.0	1.0	4.9	2.0
4	4.500	0.237	6.7	3.4	16.8	6.7
100	114.3	6.0	2.0	1.0	5.1	2.0
5 1/4 O.D.	5.236	0.248	8.0	4.0	20.1	8.0
133.0	133.0	6.3	2.4	1.2	6.1	2.4
5 1/2 O.D.	5.500	0.248	8.3	4.2	20.9	8.3
139.7	139.7	6.3	2.5	1.3	6.4	2.5
5	5.563	0.258	8.4	4.2	21.0	8.4
125	141.3	6.6	2.6	1.3	6.4	2.6
6 1/4 O.D.	6.259	0.280	9.7	4.9	24.3	9.7
159.0	159.0	7.1	3.0	1.5	7.4	3.0
6 1/2 O.D.	6.500	0.280	10.0	5.0	24.9	10.0
165.1	165.1	7.1	3.0	1.5	7.6	3.0
6	6.625	0.280	10.1	5.1	25.3	10.1
150	168.3	7.1	3.1	1.6	7.7	3.1
8	8.625	0.322	13.3	6.7	33.3	13.3
200	219.1	8.2	4.1	2.0	10.1	4.1
10	10.750	0.365	16.7	8.4	41.8	16.7
250	273.1	9.3	5.1	2.6	12.7	5.1
12	12.750	0.375	20.0	10.0	50.0	20.0
300	323.9	9.5	6.1	3.0	15.2	6.1
14	14.000	0.375	22.2	11.7	64.2	22.9
350	355.6	9.5	6.8	3.4	19.6	7.0
16	16.000	0.375	25.5	12.4	73.9	26.4
400	406.4	9.5	7.8	4.0	22.5	8.0
18	18.000	0.375	28.9	14.5	87.2	31.1
450	457.2	9.5	8.8	4.4	26.6	9.5
20	20.000	0.375	32.2	16.1	97.3	34.8
500	508.0	9.5	9.8	4.9	29.7	10.6
24	24.000	0.375	38.9	19.5	113.0	40.4
600	609.6	9.5	11.9	6.0	34.4	12.3

For the reducing tee and branches, use the value that is corresponding to the branch size. For example: for 6" x 6" x 3" tee, the branch value of 3" is 12.8 ft (3.9).

MATERIAL SPECIFICATIONS

CAST FITTINGS:

Ductile iron conforming to ASTM A 536, Grade 65-45-12

Malleable iron conforming to ASTM A 47

FABRICATED FITTINGS:

1-12" Carbon steel, Schedule 40, conforming to ASTM A 53, Grade B

14-24" Carbon steel, 0.375 wall, conforming to ASTM A 53, Grade B

COATINGS:

Rust inhibiting paint – Color: ORANGE (standard)

Hot Dipped Zinc Galvanized conforming to ASTM A 153 (optional)

Other Colors Available (IE: RAL3000 and RAL9000)

FITTING SIZE

Nominal Size	O.D.	Nominal Size	O.D.
In./DN(mm)	In./mm	In./DN(mm)	In./mm
1	1.315	5	5.563
25	33.4	140	141.3
1 1/4	1.660	6 1/4 O.D.	6.259
32	42.4	159.0	159.0
1 1/2	1.900	6 1/2 O.D.	6.500
40	48.3	165.1	165.1
2	2.375	6	6.625
50	60.3	150	168.3
2 1/2	2.875	8	8.625
65	73.0	200	219.1
3 O.D.	2.996	10	10.750
76.1	76.1	250	273.0
3	3.500	12	12.750
80	88.9	300	323.9
3 1/2	4.000	14	14.000
90	101.6	350	355.6
4 1/4 O.D.	4.250	16	16.000
108.0	108.0	400	406.4
4	4.500	18	18.000
100	114.3	450	457.2
5 1/4 O.D.	5.236	20	20.000
133.0	133.0	500	508.0
5 1/2 O.D.	5.500	24	24.000
139.7	139.7	600	609.6

The Fitting Size Chart is used to determine the O.D. of the pipe that the fittings is to be used with. Gruvlok Fittings are identified by either the Nominal size in inches or the Pipe O.D. in/mm.