AQUAFLO®



SPECIFICATION

Reinforced PVC liner with a stainless steel braided cover. Manufactured to withstand dramatic changes in water pressure to prevent bursting.

DESIGN FEATURES

- · Chloramine resistant soft cone
- Exclusive double POWR-TIGHT 12-point crimp-many times the industry standard for strength
- Chloramine resistant tubing
- Easy installation, no special tools required

OPERATING SPECS

- Working Temperature 40°F-160°F with intermittent temps up to 180°F
- Working Pressure 20-125 PSI with intermittent impulse up to 180 PSI



3689 Arrowhead Drive, Carson City, NV 89706
Phone (800) 854-3215 Fax (800) 243-1777
E-mail sales@Ispproducts.com Website
www.lspproducts.com
Content matter is subject to change at any time. It is the
user's responsibility to ensure the most updated revisions
are obtained.

AF/S-2010 (05-17) Rev 4

MIGHTYFLEX™ STAINLESS STEEL CONNECTORS Specification Sheet



MATERIAL SPECIFICATIONS

- Tubing Reinforced PVC
- End fittings Brass
- Connection Nuts

 Nickel plated brass or engineered polymer for ballcock nuts
- Washers NSF/ANSI 61 Compliant

COMPLIANCES/LISTINGS

- ASME A112.18.6/CSA B125.6 Through IAPMO, File #2111
- NSF/ANSI 61 Through IAPMO, File # N-6614
- Lead Free per Section 1417 (d) of Safe Drinking Water Act through IAPMO, File# 6545



Certified to NSF/ANSI 61



$\overline{}$		
	Product Submitta	l
Job Name:		
Date:		
Part Number		Quantity
Architect:	·	
Contractor:		

FAUCET CONNECTORS				
Part Number	Description	Length		
SFC-109-PP	1/2" FIP Soft Cone x 3/8" Soft Compression	9"		
SFC-112-PP		12"		
SFC-116-PP		16"		
SFC-120-PP		20"		
SFC-124-PP		24"		
SFC-130-PP		30"		
SFC-136-PP		36"		
SFC-148-PP		48"		
SFC-312-PP	1/2" FIP Soft Cone x 1/2" Compression	12"		
SFC-316-PP		16"		
SFC-320-PP	Soft Cone	20"		
SFC-409-PP	1/2" FIP Soft Cone x 1/2" FIP Soft Cone	9"		
SFC-412-PP		12"		
SFC-416-PP		16"		
SFC-420-PP		20"		
SFC-424-PP		24"		
SFC-430-PP		30"		
SFC-436-PP		36"		
SFC-448-PP		48"		
SFC-509-PP	3/8" Soft Compression x 3/8" Soft Compression	9"		
SFC-512-PP		12"		
SFC-516-PP		16"		
SFC-520-PP		20"		
SFC-524-PP		24"		
SFC-530-PP		30"		
SFC-548-PP		48"		
SFC-572-PP		72"		
SFF-112-PP	1/2" FIP Soft Cone x 3/8" Flare	12"		
SFF-116-PP		16"		
SFF-120-PP		20"		
SFF-130-PP		30"		

MIGHTYFLEX™ STAINLESS STEEL CONNECTORS Specification Sheet

TOILET CONNECTORS				
Part Number	Description	Length		
SFT-109-PP*	7/8" Soft Cone Ballcock x 3/8" Flare	9"		
SFT-112-PP		12"		
SFT-116-PP		16"		
SFT-120-PP		20"		
SFT-309-PP*	7/8" Soft Cone Ballcock	9"		
SFT-312-PP		12"		
SFT-316-PP	x 1/2" Flare	16"		
SFT-320-PP		20"		
SWC-109-PP	7/8" Soft Cone Ballcock	9"		
SWC-112-PP		12"		
SWC-116-PP	x 3/8" Soft Compres- sion	16"		
SWC-120-PP		20"		
SWC-309-PP	7/8" Soft Cone Ballcock	9"		
SWC-312-PP		12"		
SWC-316-PP	x 1/2" Compression Soft Cone	16"		
SWC-320-PP		20"		
SWC-409-PP	7/8" Soft Cone Ballcock	9"		
SWC-412-PP		12"		
SWC-416-PP	x 1/2" FIP Soft Cone	16"		
SWC-420-PP		20"		
SWC-512-PP	7/8" Soft Cone Metal Ballcock x 3/8" Soft Compres-	12"		
SWC-516-PP		16"		
SWC-520-PP	sion	20"		

^{*}Does Not Comply with Lead Free



3689 Arrowhead Drive, Carson City, NV 89706
Phone (800) 854-3215 Fax (800) 243-1777
E-mail sales@lspproducts.com Website
www.lspproducts.com
Content matter is subject to change at any time. It is the
user's responsibility to ensure the most updated revisions
are obtained.

AF/S-2010 (05-17) Rev 4

Product Submittal		
Job Name:		
Date:		
Part Number	Quantity	
Architect:		
Contractor:		