

H-Series Unit • Body: POLYMER CONCRETE • Cover: POLYMER CONCRETE








Tier 15 & 22*





- · Standard Hex/Penta cover anchor hardware.
- · Custom padlock available on sizes 13"x24" and above.
- R. Solid Polymer Concrete Cover
- · With Hex, Penta, Coil, or Vandal Resistant Bolt Anchor hardware.
- Cover rated to multiple industry specifications including SCTE, WUC, and AASHTO.
- S. Polymer Concrete Body
- · Polymer Concrete units are 30% lighter weight than similar concrete sizes.
- Polymer Concrete material reduces shipping costs and provides longer product life.





Products are rated by the lowest component rating. A tier 15 cover with a tier 22 body is rated tier 15. A tier 22 cover with a tier 22 body is rated tier 22.



Material	Model	Size (LxW)	Shape	Wall Type	Depths	Design Load	Tier
Polymer	910	9" Dia	0	Flared 🗀	10"	**	15 / 20
	1118	11" x 18"		Straight	12" 18" 24"		15 / 22
	1212	12" x 12"			12"24" 36"	8,000	8
	1324	13" x 24"			12" 15" 18" 24" 30"	**	15 / 22
	1324	13" x 24"		Flared _	18"	15,000 lbf	15
	1730	17" x 30"		Straight	12" 18" 24" 30" 36"	**	15 / 22
	1730	17" x 30"		Flared _	18"	15,000 lbf	15
	2424	24" x 24"		Straight	24" 36" 48" 60"	**	15 / 22
	2436	24" x 36"			18" 24" 36" 42"		
	3048	30" x 48"			18" 24" 36" 42" 48"		
	3060	30" x 60"			24" 30" 36" 48"		
	3636	36" x 36"			36" 48" 72" 84" 96"		
	4848	48" x 48"			36" 48" 72" 84" 96"		

^{**}Tier 15 Design Load: 15,000 lbf Tier 22 Design Load: 22,500 lbf
Blue - Stacked Body Units (Stacked body units are currently not rated)











Testing and Features









Chemical Resistant



Mouseholes available



Water Resistant







Freeze/Thaw Resilient



Non-Flammable



Non-Conductive



Custom Options





For more information on Enclosures or a distributor near you call (800) 735-5566



