

Access Risers - Kor Flo®

Applications

Orenco's Access Risers provide access to septic tank openings and can be cast into the tops of concrete tanks, bonded in place, or installed using a riser tank adaptor. They can also be used as valve enclosures.



General

Kor Flo® Access Risers are constructed of 30-in. (750-mm) nominal diameter ribbed PVC pipe. Risers are available in heights corresponding to the pipe ribs' spacing. Kor-Flo risers have bolt catches that allow an Orenco fiberglass lid to be secured to them.

Standard Model

RR30XX

Product Code Diagram

RR 30 + +

Discharge grommet option, in. (mm):

Blank = no discharge grommet

10 = 1 (25)

12 = 1¼ (32)

15 = 1½ (38)

20 = 2 (50)

Splice box grommet or splice box options (choose one):

Blank = no grommet or splice box

or

S = grommet installed, 1-in. (25-mm), fits SB1-SB4

L = grommet installed, 1¼-in. (32-mm), fits SB5-SB6

SX = hole drilled for Orenco® external splice box*

or

S1 = grommet and SB1 internal splice box installed

S2 = grommet and SB2 internal splice box installed

S3 = grommet and SB3 internal splice box installed

S4 = grommet and SB4 internal splice box installed

L5 = grommet and SB5 internal splice box installed

L6 = grommet and SB6 internal splice box installed

or

XS = grommet and simplex explosion-proof splice box installed**

XD = grommet and duplex explosion-proof splice box installed**

XT = grommet and triplex explosion-proof splice box installed**

Riser height in inches (2-in. increments standard)

30-inch (750-mm) riser diameter:

Ribbed Riser, Kor-Flo®

* Requires minimum 18-in. (457-mm) riser height

** For Class I Division I environments

Material of Construction

Pipe: PVC

Specifications

Dimensions	Model RR30
I.D.	29.50 in. (750 mm)
O.D. including ribs	32.13 in. (816 mm)
Rib spacing	2 in. (51 mm)
Weight	18 lb/ft (27 kg/m)

Kor Flo® is a trademark of Royal Municipal Solutions