

UNDERGROUND PIPE CLAMPS



FUNCTION: Designed to secure tie rods when used in conjunction with Fig. 580 two bolt underground pipe clamp.

MATERIAL: Low carbon steel. Cast Iron ($\frac{3}{4}$ " Tie Rod Only)

FINISH: Plain or Electro-galvanized



ORDERING: Specify tie rod size and figure number.

**Fig. 585
WASHER
For Fig. 580**

Available in stainless steel except for $\frac{3}{4}$ " tie rod.

To order, specify 304 or 316 and add suffix SS to figure number.

Price on request.



Tie Rod Size	Dia. B		C		D		E		For Pipe Sizes		Wt. Each	
											lbs.	kg
$\frac{3}{4}$	$\frac{7}{8}$	(22.23)	$\frac{5}{8}$	(15.88)	$1\frac{3}{4}$	(44.45)	$2\frac{5}{16}$	(58.74)	3 - 12	(80 - 300)	.80	(.36)
1	$1\frac{1}{8}$	(28.58)	$\frac{1}{2}$	(12.70)	3	(76.20)	$3\frac{1}{2}$	(88.90)	14	(350)	1.45	(.66)
$1\frac{1}{8}$	$1\frac{1}{4}$	(31.75)	$\frac{5}{8}$	(15.88)	3	(76.20)	4	(101.60)	16	(400)	2.31	(1.05)
$1\frac{1}{4}$	$1\frac{3}{8}$	(34.93)	$\frac{5}{8}$	(15.88)	3	(76.20)	4	(101.60)	18	(450)	2.26	(1.03)
$1\frac{3}{8}$	$1\frac{1}{2}$	(38.10)	$\frac{3}{4}$	(19.05)	3	(76.20)	4	(101.60)	20	(500)	2.87	(1.30)
$1\frac{1}{2}$	$1\frac{5}{8}$	(41.28)	$\frac{3}{4}$	(19.05)	3	(76.20)	4	(101.60)	24	(600)	2.71	(1.23)
$1\frac{3}{4}$	$1\frac{7}{8}$	(47.63)	1	(25.40)	3	(76.20)	4	(101.60)	30 - 36	(750 - 900)	4.17	(1.89)

Note: Tie rod size $\frac{3}{4}$ " made of cast iron material.

Unless otherwise specified, all dimensions on drawings and in charts are in inches and dimensions shown in parentheses are in millimeters.