


STRUT CLAMPS



Clamp With Cushion

2501 - 2587

Figure Number	O.D. Size A	Nom. Tube Size	B	C	D	Standard Package	Wt. Each Lbs. kg
2501	1/4 (6.35)	1/8 (3)	1 1/16 (26.99)	.060 (1.52)	1/2 (12.70)	30	0.12 (0.05)
2502	3/8 (9.53)	1/4 (6)	1 1/4 (31.75)	.060 (1.52)	5/8 (15.88)	30	0.13 (0.06)
2503	1/2 (12.70)	3/8 (10)	1 3/8 (34.93)	.060 (1.52)	3/4 (19.05)	30	0.13 (0.06)
2504	5/8 (15.88)	1/2 (15)	1 1/2 (38.10)	.060 (1.52)	7/8 (22.23)	20	0.15 (0.07)
2505	3/4 (19.05)	5/8 (20)	1 3/4 (44.45)	.075 (1.91)	1 1/8 (28.58)	20	0.21 (0.09)
2506	7/8 (22.23)	3/4 (25)	1 7/8 (47.63)	.075 (1.91)	1 1/4 (31.75)	20	0.22 (0.10)
2507	1 1/8 (28.58)	1 (32)	2 1/16 (52.39)	.075 (1.92)	1 1/2 (38.10)	10	0.29 (0.13)
2508	1 3/8 (34.93)	1 1/4 (40)	2 7/16 (61.91)	.075 (1.91)	1 3/4 (44.45)	10	0.33 (0.15)
2509	1 5/8 (41.28)	1 1/2 (50)	3 (76.20)	.105 (2.67)	2 1/4 (57.15)	10	0.42 (0.19)
2510	2 1/8 (53.98)	2 (65)	3 3/8 (85.73)	.105 (2.67)	2 3/4 (69.85)	10	0.50 (0.23)
2511	2 5/8 (66.68)	2 1/2 (80)	3 7/8 (98.43)	.105 (2.67)	3 1/4 (82.55)	10	0.62 (0.28)
2512	3 1/8 (79.38)	3 (90)	4 5/16 (109.54)	.105 (2.67)	3 3/4 (95.25)	10	0.66 (0.30)
2514	4 1/8 (104.78)	4 (100)	5 1/2 (139.70)	.125 (3.18)	4 3/4 (120.65)	10	0.88 (0.40)



CLAMP MATERIAL:

Low carbon steel

CUSHION MATERIAL:

Multi-Flex TES A9110 EV1 Black, in accordance with ASTM D4474 TES 0130 A90000

TEMPERATURE RANGE:

-65°F to 275°F
(-54°C to 135°C)





Figure Number	O.D. Size	Max. Rec. Load					
		X		Y		Z	
		Lbs.	kN	Lbs.	kN	Lbs.	kN
2501	1/4 (6.35)	50	(0.22)	50	(0.22)	400	(1.78)
2502	3/8 (9.53)	50	(0.22)	50	(0.22)	400	(1.78)
2503	1/2 (12.70)	50	(0.22)	50	(0.22)	400	(1.78)
2504	5/8 (15.88)	50	(0.22)	50	(0.22)	400	(1.78)
2505	3/4 (19.05)	75	(0.33)	75	(0.33)	600	(2.67)
2506	7/8 (22.23)	75	(0.33)	75	(0.33)	600	(2.67)
2507	1 1/8 (28.58)	75	(0.33)	75	(0.33)	600	(2.67)
2508	1 3/8 (34.93)	75	(0.33)	75	(0.33)	600	(2.67)
2509	1 5/8 (41.28)	75	(0.33)	75	(0.33)	600	(2.67)
2510	2 1/8 (53.98)	125	(0.56)	125	(0.56)	800	(3.56)
2511	2 5/8 (66.68)	125	(0.56)	125	(0.56)	800	(3.56)
2512	3 1/8 (79.38)	125	(0.56)	125	(0.56)	800	(3.56)
2514	4 1/8 (104.78)	150	(0.67)	200	(0.89)	1000	(4.45)

Figure Number	Nominal Pipe Size	O.D. Size A	B	C	D	Standard Package	Wt. Each Lbs. kg
2574	1/4 (5)	.540 (13.72)	1.41 (35.81)	.075 (1.91)	.91 (23.11)	30	.16 (0.07)
2575	3/8 (10)	.675 (17.15)	1.59 (40.39)	.075 (1.91)	1.07 (27.18)	30	.17 (0.08)
2576	1/2 (15)	.840 (21.34)	1.91 (48.51)	.075 (1.91)	1.45 (36.83)	30	.21 (0.10)
2577	3/4 (20)	1.050 (26.67)	2.16 (54.86)	.105 (2.67)	1.79 (45.47)	10	.31 (0.14)
2578	1 (25)	1.315 (33.40)	2.75 (69.85)	.119 (3.02)	2.22 (56.39)	20	.43 (0.20)
2579	1 1/4 (32)	1.660 (42.16)	3.03 (76.96)	.119 (3.02)	2.47 (62.74)	10	.48 (0.22)
2580	1 1/2 (40)	1.900 (48.26)	3.28 (83.31)	.119 (3.02)	2.47 (62.74)	10	.52 (0.24)
2581	2 (50)	2.375 (60.33)	3.78 (96.01)	.119 (3.02)	3.22 (81.79)	10	.61 (0.28)
2582	2 1/2 (65)	2.875 (73.03)	4.27 (108.46)	.119 (3.02)	3.72 (94.49)	10	.63 (0.29)
2583	3 (80)	3.500 (88.90)	4.91 (124.71)	.119 (3.02)	4.36 (110.74)	10	.72 (0.33)
2584	3 1/2 (90)	4.000 (101.60)	5.53 (140.46)	.119 (3.02)	4.97 (126.24)	10	.88 (0.40)
2585	4 (100)	4.500 (114.30)	6.03 (153.16)	.119 (3.02)	5.47 (138.94)	10	.94 (0.43)
2586	5 (125)	5.563 (141.30)	7.03 (178.56)	.119 (3.02)	6.47 (164.34)	10	1.22 (0.55)
2587	6 (150)	6.625 (168.28)	8.03 (203.96)	.119 (3.02)	7.47 (189.74)	10	1.44 (0.65)
2588	8 (200)	8.625 (219.08)	10.3 (261.62)	.130 (3.30)	9.38 (238.25)	10	2.00 (0.90)

Figure Number	O.D. Size	Max. Rec. Load					
		X		Y		Z	
		Lbs.	kN	Lbs.	kN	Lbs.	kN
2574	.540 (13.72)	50	(0.22)	50	(0.22)	400	(1.78)
2575	.675 (17.15)	75	(0.33)	75	(0.33)	600	(2.67)
2576	.840 (21.34)	75	(0.33)	75	(0.33)	600	(2.67)
2577	1.050 (26.67)	75	(0.33)	75	(0.33)	600	(2.67)
2578	1.315 (33.40)	75	(0.33)	75	(0.33)	600	(2.67)
2579	1.660 (42.16)	125	(0.56)	125	(0.56)	800	(3.56)
2580	1.900 (48.26)	125	(0.56)	125	(0.56)	800	(3.56)
2581	2.375 (60.33)	125	(0.56)	125	(0.56)	800	(3.56)
2582	2.875 (73.03)	125	(0.56)	125	(0.56)	800	(3.56)
2583	3.500 (88.90)	150	(0.67)	200	(0.89)	1000	(4.45)
2584	4.000 (101.60)	150	(0.67)	200	(0.89)	1000	(4.45)
2585	4.500 (114.30)	150	(0.67)	200	(0.89)	1000	(4.45)
2586	5.563 (141.30)	150	(0.67)	200	(0.89)	1000	(4.45)
2587	6.625 (168.28)	150	(0.67)	200	(0.89)	1000	(4.45)
2588	8.625 (219.08)	150	(0.67)	200	(0.89)	1000	(4.45)



Unless otherwise specified, all dimensions on drawings and in charts are in inches and dimensions shown in parentheses are in millimeters.