

Royal® Flushometer 195-1 8 3/4 LDIM

▶ Code Number

3913285

Description

Concealed Urinal Flushometer, for 3/4" back spud urinals.

► Flush Cycle

1.0 gpf/3.8 Lpf

▶ Specifications

Quiet, Concealed, Diaphragm Type, Rough Brass Urinal Flushometer for either left or right hand supply with the following features:

- Vacuum Breaker
- Spud Coupling for ¾" Concealed Back Spud Urinals
- Chrome Plated Exposed Flushometer Parts
- Elbow Flush Connection
- Non-Hold-Open Handle, Fixed Metering Bypass and No External Volume Adjustment to Ensure Water Conservation
- Diaphragm, Handle Packing and Vacuum Breaker to be molded from PERMEX® Rubber Compound for Chloramine Resistance
- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- Flush accuracy controlled by CID® technology
- 3/4" I.P.S. Wheel Handle Bak-Chek® Angle Stop

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.

▶ Variations

8 3/4 LDIM

▶ L Dimension

Specify the "L" Dimension for the proper length of the Handle Assembly and Flush Connection. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 23/4" (70 mm).


Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories

▶ Fixtures

Consult factory for matching Sloan brand fixture options.





▶ Compliance & Certifications







This space for Architect/Engineer Approval