

Ecoflex® Compression Wall Seal

Submittal Information

Revision D: Feb. 18, 2015

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material:

Rubber Gasket: Ethylene propylene diene monomer (EDPM) rubber

Hardware: Stainless steel

Product Information and Application Use

The Compression Wall Seal can be used with the Wall Sleeve, or can be used alone where a field core drill is preferred. It creates a watertight seal between the core drill surface and the outer jacket of Ecoflex® piping.



✓	Description	Part Number	Core Drill	O.D.	I.D.	Length	Weight
	Compression Wall Seal for 2.7" Jacket	1007358	4.75"	4.75"	2.75"	4.125"	2.6 lbs.
	Compression Wall Seal for 5.5" Jacket	1007360	8"	7.9"	5.51"	5.375"	5.1 lbs.
	Compression Wall Seal for 6.9" Jacket	1007361	10"	9.75"	6.95"	5.375"	7.8 lbs.
	Compression Wall Seal for 7.9" Jacket	1007362	10"	9.9"	7.95"	5.25"	6.1 lbs.

Installation

For new concrete walls, install over the pipe and into the Wall Sleeve for a watertight seal. For an existing wall with a field core drill, install between core drill surface and outer jacket of the Ecoflex pipe. Refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual for more information.

Standards

N/A

Codes

N/A

Listings

N/A

Related Applications

Pre-insulated Pipe Systems
Radiant Heating and Cooling Systems
Snow and Ice Melting Systems
Permafrost Protection Systems
Turf Conditioning Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: 800.321.4739
Fax: 952.891.2008
www.uponorpro.com

Uponor Ltd.
2000 Argentia Rd., Plaza 1, Ste. 200
Mississauga, ON L5N 1W1 CANADA
Phone: 888.994.7726
Fax: 800.638.9517
www.uponorpro.com