

Engineered Plastic (EP) Heating Manifold Single Section with Balancing Valve and Flow Meter

Submittal Information

Revision A: Oct. 15, 2008

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Manifold:	PA66-GF30
Valve Insert, Handwheels:	POM
Metal Inserts:	Brass C38500
Axel:	Stainless Steel
Spring:	Stainless Steel
O-ring:	EPDM



Product Information and Application Use

The Engineered Plastic (EP) Heating Manifold Single Section with Balancing Valve and Flow Meter (A2670003) adds additional loops to an EP Heating Manifold assembly for use in hydronic radiant heating and cooling systems. Use only propylene glycol in radiant systems with EP Heating Manifolds; never use ethylene glycol.

✓	Description	Part Number	Height	Width	Weight
	EP Heating Manifold Single Section with Balancing Valve and Flow Meter	A2670003	7.5"	2.0"	0.36 lbs.
□	EP Heating Manifold Flow Meter Valve Body, replacement part	A2670005			
	EP Heating Manifold Valve Replacement Tool	A2670007			
	EP Heating Manifold Replacement O-ring	A2670008			

Installation

Select the proper bracket spacing for the manifold and mount the bracket to the wall. Snap the manifold to the bracket. See the installation manual for complete instructions. **Note:** Use only propylene glycol in radiant heating and cooling systems with EP Heating Manifolds; never use ethylene glycol. Refer to the EP Heating Manifold Installation Guide for a complete chemicals list.

Standards

N/A

Codes

N/A

Listings

N/A

Related Applications

Radiant Heating and Cooling Systems
Snow and Ice Melting Systems
Permafrost Protection Systems
Turf Conditioning Systems

Contact Information

Uponor, Inc.
5925 148th Street West
Apple Valley, MN 55124 USA
Phone: (800) 321-4739
Fax: (952) 891-2008
www.uponor-usa.com

Uponor Ltd.
2000 Argentia Road, Plaza 1, Suite 200
Mississauga, ON L5N 1W1 CANADA
Phone: (888) 994-7726
Fax: (800) 638-9517
www.uponor.ca