sue date: 17.03.2022	v 2	Last Revision Date: 17.03.202
1 Identification		
· Product identifier		
· Trade name: MOTORV	AC MV-6 Fuel System Clear	ner
• <b>Part number:</b> 400-006	0-1	
<ul> <li>Details of the supplier of the CPS Product Inc USA</li> <li>1010 East 31st Street</li> <li>Hialeah, FL 33013 USA</li> <li>Phone: (305) 687 - 4121</li> <li>Email: cs@cpsproducts.com</li> <li>Manufacturer/Supplier: CPS Product Inc - USA</li> <li>1010 East 31st Street</li> <li>Hialeah, FL 33013 USA</li> <li>Contact Phone: (305) 687</li> <li>email of person respons</li> </ul>	-4121 <b>ible:</b> cs@cpsproducts.com	
• Emergency telephone nu	umber:	

Flammable Aerosols 1	H222 Extremely flammable aerosol. Pressurized container. May burst if heated.
Skin Irrititation 2	H315 Causes skin irritation.
Eye Irritation 2A	H319 Causes serious eye irritation.
Germ Cell Mutagenicity 1B	H340 May cause genetic defects.
Carcinogenicity 1B	H350 May cause cancer.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.

## · Label elements

## · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).  $\cdot$  Hazard pictograms



· Signal word Danger

- **Hazard-determining components of labeling:** Naphtha (petroleum), light alkylate Distillates (petroleum), hydrotreated light Solvent naphtha (petroleum), heavy arom.
- Hazard statements Extremely flammable aerosol. Pressurized container. May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause genetic defects. May cause cancer.

(Contd. on page 2)

NA

Last Revision Date: 17.03.2022

## Trade name: MOTORVAC MV-6 Fuel System Cleaner (Contd. of page 1) May be fatal if swallowed and enters airways. Precautionary statements Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents in accordance with local regulations. · Additional information: Restricted to professional users. · Other hazards • **PBT:** Not applicable. · vPvB: Not applicable.

## **3 Composition/information on ingredients**

#### · Chemical characterization: Mixtures

· Chemical components:			
64741-66-8	Naphtha (petroleum), light alkylate	≥25-≤50%	
1330-20-7	xylene	≥25-≤50%	
	2-butoxyethanol	≥2.5-≤25%	
	4-methylpentan-2-ol	≥2.5-≤10%	
64742-47-8	Distillates (petroleum), hydrotreated light	2.5-10%	
64742-94-5	Solvent naphtha (petroleum), heavy arom.	≤2.5%	
· Other Ingredients			

#### Proprietary Additive

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **4 First-aid measures**

#### Description of first aid measures

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

- After swallowing: If symptoms persist consult doctor.
- · Information for doctor: Treat Symptomatically

(Contd. on page 3)

2.5-10%

N/

#### v 2

Last Revision Date: 17.03.2022

## Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 2)

- Most important symptoms and effects, both acute and delayed Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. See section 11.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

## **5 Fire-fighting measures**

## · Extinguishing media

• Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture See section 10 for additional information. • Advice for firefighters
  - · Protective equipment:

Recommend wearing self-contained breathing apparatus. Water may cause splattering.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.
- **Methods and material for containment and cleaning up:** Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

## 7 Handling and storage

#### · Handling:

- Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- · Information about protection against explosions and fires:
- Do not spray on a naked flame or any incandescent material.
- Keep ignition sources away Do not smoke.
- Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

NA

v 2

# Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 3)

Conditions for safe storage, including any incompatibilities
 Storage:

• **Requirements to be met by storerooms and receptacles:** See section 10 for incompatible materials.

Observe official regulations on storing packagings with pressurized containers.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

· Specific end use(s) No further relevant information available.

· Control para	controls/personal protection	
• Components with limit values that require monitoring at the workplace:		
•	lene (25-50%)	
PEL (USA)	TWA: 435 mg/m <sup>3</sup> , 100 ppm	
REL (USA)	STEL: 655 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm	
TLV (USA)	STEL: (150) ppm TWA: (100) NIC-20 ppm BEI, A4	
EL (Canada)	STEL: 150 ppm TWA: 100 ppm	
EV (Canada)	STEL: 650 mg/m³, 150 ppm TWA: 435 mg/m³, 100 ppm	
111-76-2 2-bi	utoxyethanol (10-25%)	
PEL (USA)	TWA: 240 mg/m³, 50 ppm Skin	
REL (USA)	TWA: 24 mg/m³, 5 ppm Skin	
TLV (USA)	TWA: 20 ppm BEI, A3	
EL (Canada)	TWA: 20 ppm	
EV (Canada)	TWA: 20 ppm Skin	
108-11-2 4-m	ethylpentan-2-ol (2.5-10%)	
PEL (USA)	TWA: 100 mg/m³, 25 ppm Skin	
REL (USA)	STEL: 165 mg/m³, 40 ppm TWA: 100 mg/m³, 25 ppm Skin	
TLV (USA)	STEL: 40 ppm TWA: 20 ppm	
	(Contd. on page	

v 2

Issue date: 17.03.2022

Last Revision Date: 17.03.2022

# Trade name: MOTORVAC MV-6 Fuel System Cleaner (Contd. of page 4) EL (Canada) STEL: 40 ppm TWA: 25 ppm EV (Canada) STEL: 167 mg/m<sup>3</sup>, 40 ppm TWA: 104 mg/m<sup>3</sup>, 25 ppm Skin 64742-47-8 Distillates (petroleum), hydrotreated light (2.5-10%) EL (Canada) TWA: 200 mg/m<sup>3</sup> Skin · Ingredients with biological limit values: 1330-20-7 xylene (25-50%) BEI (USA) 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 111-76-2 2-butoxyethanol (10-25%) BEI (USA) 200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis) • Additional information: The lists that were valid during the creation were used as basis. Exposure controls · Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Store protective clothing separately. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Chemical resistant protective gloves · Eye protection: Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

(Contd. on page 6)

v 2

Last Revision Date: 17.03.2022

# Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 5)

9 Physical and chemical propertie	es		
· Information on basic physical and chemical properties			
· General Information			
· Appearance:			
· Form:	Aerosol		
· Color:	According to product specification		
· Odor:	Characteristic		
Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
<ul> <li>Melting point/Melting range:</li> </ul>	Undetermined.		
· Boiling point/Boiling range:	140 °C		
· Flash point:	21 °C		
· Flammability (solid, gaseous):	Not applicable.		
· Decomposition temperature:	Not determined.		
· Auto igniting:	Product is not selfigniting.		
Danger of explosion:	Product is not explosive. However, formation of explosive		
	air/vapor mixtures are possible.		
· Explosion limits:			
· Lower:	Not determined.		
· Upper:	Not determined.		
· Vapor pressure:	Not determined.		
· Density:	Not determined.		
Relative density	Not determined.		
· Vapor density	Not determined.		
• Evaporation rate	Not applicable.		
· Solubility in / Miscibility with			
· Water:	Partially miscible.		
· Partition coefficient (n-octanol/wat	er): Not determined.		
· Viscosity:			
· Dynamic:	Not determined.		
· Kinematic:	Not determined.		
· Solvent separation test			
· VOC content:	68.35-81.35 %		
· Other information	No further relevant information available.		

# 10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 7)

NA

#### v 2

Last Revision Date: 17.03.2022

Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 6)

· Chemical stability

• Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

• Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid Heat, open flames, sparks.

• Incompatible materials: No further relevant information available.

· Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

	on on toxicologic toxicity:	al effects	
	-	are relevant for classification:	
	te Toxicity Estim		
Oral	LD50	10,909-15,000 mg/kg	
Dermal	LD50	4,878-6,061 mg/kg	
		105-144 mg/L (gpg)	
1330-20-7	xylene		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
Inhalative	LC50/4 h (vapor)	6,700 mg/L (rat)	
	2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE)	
		1,414 mg/kg (gpg)	
Dermal	LD50	2,000 mg/kg (gpg)	
Inhalative	LC50/4 h (vapor)		
108-11-2 4	4-methylpentan-2	-ol	
Oral	LD50	2,590 mg/kg (rat)	
Dermal	LD50	3,560 mg/kg (rabbit)	
Sen Additio The pro prepara Irritant	on the eye: Irritatin sitization: No ser onal toxicologica oduct shows the f ations:	nt to skin and mucous membranes. ng effect. nsitizing effects known.	ethods f
•	ARC (Internation	al Agency for Research on Cancer)	
1330-20-7	xylene		3
111_76_2	2-butoxyethanol		3
111702			

v 2

## Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 7)

R

## · NTP (National Toxicology Program)

91-20-3 naphthalene

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

· Toxicity

• Aquatic toxicity: No further relevant information available.

- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:

Bioaccumulative potential

#### 108-11-2 4-methylpentan-2-ol

Bioaccumulation 1.43 (-) (potential low)

• Mobility in soil No further relevant information available.

## · Additional ecological information:

## · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

#### • Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

• Other adverse effects No further relevant information available.

## **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

## · Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
· DOT, ADR, IMDG, IATA	UN1950	
UN proper shipping name		
DOT	Aerosols, flammable	
·IMDG	AEROSÓLS	

Issue date: 17.03.2022 v 2 Last Revision Date: 17.03.2022 Trade name: MOTORVAC MV-6 Fuel System Cleaner (Contd. of page 8) ·IATA AEROSOLS, flammable · Transport hazard class(es) · DOT · Class 2.1 Gases · Label 2.1 · IMDG, IATA · Class 2.1 Gases · Label 2.1 Packing group · DOT, IMDG, IATA Not Regulated · Environmental hazards: Not applicable. Warning: Gases · Special precautions for user · Hazard identification number (Kemler code): -· EMS Number: F-D.S-U SW1 Protected from sources of heat. Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · IMDG · Limited quantities (LQ) 1L (Contd. on page 10) NA

v 2

Last Revision Date: 17.03.2022

# Trade name: MOTORVAC MV-6 Fuel System Cleaner

(Contd. of page 9)

• Excepted quantities (EQ)

Code: E0 Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

# **15 Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions

Contains no REACH candidate substance

# · Sara

· Sara				
· Section 355 (extremely hazardous substances):				
None of the ingredients is listed.				
· Section 313 (Specific toxic chemical listings):				
1330-20-7	xylene			
111-76-2	2-butoxyethanol			
95-63-6	1,2,4-trimethylbenzene			
91-20-3	naphthalene			
· TSC	A (Toxic Substances Control Act):			
64741-66-8	Naphtha (petroleum), light alkylate	ACTIVE		
1330-20-7	xylene	ACTIVE		
111-76-2	2-butoxyethanol	ACTIVE		
108-11-2	4-methylpentan-2-ol	ACTIVE		
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE		
64742-94-5	Solvent naphtha (petroleum), heavy arom.	ACTIVE		
95-63-6	1,2,4-trimethylbenzene	ACTIVE		
91-20-3	naphthalene	ACTIVE		
108-67-8	mesitylene	ACTIVE		
526-73-8	1,2,3-trimethylbenzene	ACTIVE		

## · Proposition 65

<sup>•</sup> Chemicals known to cause cancer:	
91-20-3 naphthalene	
<ul> <li>Chemicals known to cause reproductive toxicity for females:</li> </ul>	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
	(Contd. on page 11)

v 2

Issue date: 17.03.2022

Last Revision Date: 17.03.2022

	.2022	٧Z	Last Revision Date. 17.0	00.2022
Trade name: N	IOTORVAC MV-6 Fuel Sys	tem Cleaner		
			(Contd. of	nade 10)
Care	inogenic categories		(conta. or	puge io)
	PA (Environmental Protection A	(acrev)		
1330-20-7		(gency)	1	
	2-butoxyethanol			1
	1,2,4-trimethylbenzene		II	<u> </u>
	naphthalene			, CBD
	mesitylene			, 000
	1,2,3-trimethylbenzene			
	LV (Threshold Limit Value)			
1330-20-7				A4
	2-butoxyethanol			A4 A3
	naphthalene			A4
	•			
	IOSH-Ca (National Institute for	Occupational Sa	arety and Health)	
	ingredients is listed.			
	idian substance listings:			
	anadian Domestic Substances	<b>、</b> ,		
	Naphtha (petroleum), light alkyla	ate		
1330-20-7				
	2-butoxyethanol			
	4-methylpentan-2-ol Distillates (petroleum), hydrotrea	atad light		
	Solvent naphtha (petroleum), he	-		
	1,2,4-trimethylbenzene	avy aroni.		
	naphthalene			
	mesitylene			
	1,2,3-trimethylbenzene			
	-		N	
	anadian Non-Domestic Substar	ices List (NDSL	)	
	ingredients is listed.			
	anadian Ingredient Disclosure	list (limit 0.1%)		
	2,4-trimethylbenzene			
	anadian Ingredient Disclosure	list (limit 1%)		
	-butoxyethanol			
108-11-2 4	-methylpentan-2-ol			

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:** Engineering Department

· Issue Date 17.03.2022

(Contd. on page 12)

NA

v 2

Last Revision Date: 17.03.2022

#### Trade name: MOTORVAC MV-6 Fuel System Cleaner (Contd. of page 11) · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health Flammable Aerosols 1: Aerosols – Category 1 Skin Irrititation 2: Skin corrosion/irritation – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B Carcinogenicity 1B: Carcinogenicity - Category 1B Aspiration Hazard 1: Aspiration hazard - Category 1