

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**1 Identification**· **Product identifier**· **Trade name: CarboClean MV3 Fuel System Cleaner**· **Part number:** 400-0020, 400-0022, 400-0126· **Application of the substance / the mixture** fuel system cleaner· **Details of the supplier of the safety data sheet**

CPS Product Inc. - USA

1010 East 31st Street

Hialeah, FL 33013 USA

Phone: (305) 687 - 4121

Email: cs@cpsproducts.com

· **Manufacturer/Supplier:**

CPS Product Inc - USA

1010 East 31st Street

Hialeah, FL 33013 USA

Contact Phone: (305) 687-4121

· **email of person responsible:** cs@cpsproducts.com· **Emergency telephone number:**

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

**2 Hazard(s) identification**· **Classification of the substance or mixture**

Flammable Liquids 3            H226 Flammable liquid and vapor.

Acute Toxicity - Inhalation 4   H332 Harmful if inhaled.

Skin Irritation 2                H315 Causes skin irritation.

Eye Irritation 2A                H319 Causes serious eye irritation.

Germ Cell Mutagenicity 1B    H340 May cause genetic defects.

Carcinogenicity 1A              H350 May cause cancer.

Aspiration Hazard 1            H304 May be fatal if swallowed and enters airways.

Aquatic Acute 3                 H402 Harmful to aquatic life.

Aquatic Chronic 3               H412 Harmful to aquatic life with long lasting effects.

· **Label elements**· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**· **Signal word** Danger· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

2-butoxyethanol

Solvent naphtha (petroleum), heavy arom.

cumene

(Contd. on page 2)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 1)

**· Hazard statements**

Flammable liquid and vapor.  
 Harmful if inhaled.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May be fatal if swallowed and enters airways.  
 Harmful to aquatic life.  
 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF exposed or concerned: Call a poison center/doctor.  
 In case of fire: Use CO<sub>2</sub>, sand, extinguishing powder to extinguish.  
 Store in a well-ventilated place. Keep cool.  
 Dispose of contents in accordance with local regulations.

**· Additional information:**

For Professional Use Only  
 Restricted to professional users.

**· Other hazards**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

**3 Composition/information on ingredients****· Chemical characterization: Mixtures****· Chemical components:**

|            |  |        |
|------------|--|--------|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | 9-37%  |
| 64742-94-5 | Solvent naphtha (petroleum), heavy arom. | 10-30% |
| 108-11-2   | 4-methylpentan-2-ol                      | 5-10%  |
| 111-76-2   | 2-butoxyethanol                          | 5-10%  |
| 98-82-8    | cumene                                   | <2.0%  |
| 71-43-2    | benzene                                  | <1.0%  |
| 91-20-3    | naphthalene                              | <1.0%  |

**· Other Ingredients**

|                      |       |
|----------------------|-------|
| Proprietary Additive | 5-10% |
|----------------------|-------|

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

**4 First-aid measures****· Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

(Contd. on page 3)

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 2)

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eye irritation develops or persists.

· **After swallowing:**

A person vomiting while lying on their back should be turned onto their side.

Rinse mouth with water.

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If conscious, give small quantities of water to drink.

Stop if victim feels sick.

Do not induce vomiting.

If symptoms persist consult doctor.

· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed**

May cause eye irritation. Symptoms may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.

Headache

Dizziness

Disorientation

Coughing

Nausea

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

See section 11.

· **Indication of any immediate medical attention and special treatment needed**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Treat Symptomatically

**5 Fire-fighting measures**· **Extinguishing media**· **Suitable extinguishing agents:**

Sand. Do not use water.

CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

(Contd. on page 4)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** See section 10 for additional information.
- **Advice for firefighters**
  - **Protective equipment:**  
Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Particular danger of slipping on leaked/spilled product.  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.  
Do not touch or walk through spilled material.
- **Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.  
Prevent from spreading (e.g. by damming-in or oil barriers).  
Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- **Handling:**
  - **Precautions for safe handling**  
Open and handle receptacle with care.  
Use only in well ventilated areas.  
Avoid contact with the eyes and skin.  
Avoid contact with clothing.  
Avoid splashes or spray in enclosed areas.  
Keep in the original containers.  
See section 8 for personal protective equipment.  
Do not reuse container.
  - **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.

(Contd. on page 5)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 4)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
  - **Requirements to be met by storerooms and receptacles:**
    - See section 10 for incompatible materials.
    - See section 10 for incompatible materials.
  - **Information about storage in one common storage facility:** Not required.
  - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**· **Control parameters**· **Components with limit values that require monitoring at the workplace:****108-11-2 4-methylpentan-2-ol (2.5-10%)**

|             |   |
|-------------|---|
| PEL (USA)   | TWA: 100 mg/m <sup>3</sup> , 25 ppm<br>Skin   |
| REL (USA)   | STEL: 165 mg/m <sup>3</sup> , 40 ppm<br>TWA: 100 mg/m <sup>3</sup> , 25 ppm<br>Skin |
| TLV (USA)   | STEL: 40 ppm<br>TWA: 20 ppm   |
| EL (Canada) | STEL: 40 ppm<br>TWA: 25 ppm   |
| EV (Canada) | STEL: 167 mg/m <sup>3</sup> , 40 ppm<br>TWA: 104 mg/m <sup>3</sup> , 25 ppm<br>Skin |

**111-76-2 2-butoxyethanol (2.5-10%)**

|             |   |
|-------------|---|
| PEL (USA)   | TWA: 240 mg/m <sup>3</sup> , 50 ppm<br>Skin |
| REL (USA)   | TWA: 24 mg/m <sup>3</sup> , 5 ppm<br>Skin   |
| TLV (USA)   | TWA: 20 ppm<br>BEI, A3                      |
| EL (Canada) | TWA: 20 ppm                                 |
| EV (Canada) | TWA: 20 ppm<br>Skin                         |

**98-82-8 cumene (≤2.5%)**

|             |   |
|-------------|---|
| PEL (USA)   | TWA: 245 mg/m <sup>3</sup> , 50 ppm<br>Skin |
| REL (USA)   | TWA: 245 mg/m <sup>3</sup> , 50 ppm<br>Skin |
| TLV (USA)   | TWA: 5 ppm<br>A3                            |
| EL (Canada) | STEL: 75 ppm<br>TWA: 25 ppm<br>IARC 2B      |

(Contd. on page 6)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 5)

|  |  |
|--|--|
| EV (Canada)                                      | TWA: 245 mg/m <sup>3</sup> , 50 ppm<br>Skin  |
| <b>71-43-2 benzene (≤2.5%)</b>                   |  |
| PEL (USA)  | STEL: 15* mg/m <sup>3</sup> , 5* ppm<br>TWA: 3* mg/m <sup>3</sup> , 1* ppm<br>*table Z-2 for exclusions in 29CFR1910.1028(d)   |
| REL (USA)  | STEL: 1 ppm<br>TWA: 0.1 ppm<br>See Pocket Guide App. A   |
| TLV (USA)  | STEL: 2.5 ppm<br>TWA: 0.5 ppm<br>Skin; BEI, A1   |
| EL (Canada)                                      | STEL: 2.5 ppm<br>TWA: 0.5 ppm<br>Skin; ACGIH A1; IARC 1  |
| EV (Canada)                                      | STEL: 2.5 ppm<br>TWA: 0.5 ppm<br>Skin  |
| <b>91-20-3 naphthalene (≤2.5%)</b>               |  |
| PEL (USA)  | TWA: 50 mg/m <sup>3</sup> , 10 ppm   |
| REL (USA)  | STEL: 75 mg/m <sup>3</sup> , 15 ppm<br>TWA: 50 mg/m <sup>3</sup> , 10 ppm  |
| TLV (USA)  | TWA: 10 ppm<br>Skin; BEI, A3   |
| EL (Canada)                                      | TWA: 10 ppm<br>Skin; IARC 2B   |
| EV (Canada)                                      | STEL: 78 mg/m <sup>3</sup> , 15 ppm<br>TWA: 52 mg/m <sup>3</sup> , 10 ppm  |
| <b>Ingredients with biological limit values:</b> |  |
| <b>111-76-2 2-butoxyethanol (2.5-10%)</b>        |  |
| BEI (USA)  | 200 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Butoxyacetic acid (BAA) (with hydrolysis)   |
| <b>71-43-2 benzene (≤2.5%)</b>                   |  |
| BEI (USA)  | 25 µg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: S-Phenylmercapturic acid (background<br><br>500 µg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: t,t-Muconic acid (background) |

(Contd. on page 7)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 6)

**91-20-3 naphthalene (≤2.5%)**

BEI (USA) -

Medium: -

Time: end of shift

Parameter: 1-Naphthol with hydrolysis + 2-Naphthol with hydrolysis (Nq,Ns)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.

- Immediately remove all soiled and contaminated clothing.

- Store protective clothing separately.

- Avoid contact with the eyes and skin.

- Do not eat, drink, smoke or sniff while working.

- **Breathing equipment:**

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Chemical resistant protective gloves

- **Eye protection:**



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

- **Body protection:** Protective work clothing

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:**

Liquid

- **Color:**

Amber colored

- **Odor:**

Petrol-like

- **Odor threshold:**

Not determined.

- **pH-value at 20 °C:**

9.5

- **Change in condition**

- **Melting point/Melting range:**

Undetermined.

- **Boiling point/Boiling range:**

131 °C

- **Flash point:**

45 °C

- **Flammability (solid, gaseous):**

Not applicable.

(Contd. on page 8)

NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 7)

|  |  |
|--|--|
| · Ignition temperature:                    | 240 °C   |
| · Decomposition temperature:               | Not determined.  |
| · Auto igniting:                           | Product is not selfigniting.   |
| · Danger of explosion:                     | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits:                        |  |
| · Lower:                                   | 0.7 Vol %  |
| · Upper:                                   | 7.5 Vol %  |
| · Vapor pressure at 20 °C:                 | 5 hPa  |
| · Density at 20 °C:                        | 0.88 g/cm <sup>3</sup>   |
| · Relative density                         | Not determined.  |
| · Vapor density                            | Not determined.  |
| · Evaporation rate                         | Not determined.  |
| · Solubility in / Miscibility with         |  |
| · Water:                                   | Not miscible or difficult to mix.  |
| · Partition coefficient (n-octanol/water): | Not determined.  |
| · Viscosity:                               |  |
| · Dynamic:                                 | Not determined.  |
| · Kinematic:                               | Not determined.  |
| · Solvent separation test                  |  |
| · VOC content:                             | 16.7-<50.41 %  |
| · Other information                        | No further relevant information available.   |

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
  - **Thermal decomposition / conditions to be avoided:**  
Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, open flames, sparks.
- **Incompatible materials:** Strong Oxidizers, strong acids.
- **Hazardous decomposition products:** May include, and are not limited to: oxides of carbon.

NA

(Contd. on page 9)



## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 8)

**11 Toxicological information**· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values that are relevant for classification:****ATE (Acute Toxicity Estimate)**

|            |                  |                      |
|------------|------------------|----------------------|
| Oral       | LD50             | >10,244-17,872 mg/kg |
| Dermal     | LD50             | >3,871-4,286 mg/kg   |
| Inhalative | LC50/4 h (vapor) | >22-77.7 mg/L        |

**64742-95-6 Solvent naphtha (petroleum), light arom.**

|            |                  |                    |
|------------|------------------|--------------------|
| Oral       | LD50             | >6,800 mg/kg (rat) |
| Dermal     | LD50             | >3,400 mg/kg (rab) |
| Inhalative | LC50/4 h (vapor) | >10.2 mg/L (rat)   |

**108-11-2 4-methylpentan-2-ol**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 2,590 mg/kg (rat)    |
| Dermal | LD50 | 3,560 mg/kg (rabbit) |

**111-76-2 2-butoxyethanol**

|            |                  |  |
|------------|------------------|--|
| Oral       | LD50             | 1,200 mg/kg (ATE)<br>1,414 mg/kg (gpg) |
| Dermal     | LD50             | 2,000 mg/kg (gpg)                      |
| Inhalative | LC50/4 h (vapor) | 11.5 mg/L (gpg)                        |

**98-82-8 cumene**

|            |                  |                       |
|------------|------------------|-----------------------|
| Oral       | LD50             | 1,400 mg/kg (rat)     |
| Dermal     | LD50             | 12,300 mg/kg (rabbit) |
| Inhalative | LC50/4 h (vapor) | 24.7 mg/L (mouse)     |

**71-43-2 benzene**

|            |                  |                    |
|------------|------------------|--------------------|
| Oral       | LD50             | 4,894 mg/kg (rat)  |
| Dermal     | LD50             | 48 mg/kg (mouse)   |
| Inhalative | LC50/4 h (vapor) | 9,980 mg/L (mouse) |

**91-20-3 naphthalene**

|        |      |                   |
|--------|------|-------------------|
| Oral   | LD50 | 490 mg/kg (rat)   |
| Dermal | LD50 | 5,000 mg/kg (rat) |

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:**  
Irritating effect.  
May cause eye irritation. Symptoms may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.
- **Inhalation:**  
Do not inhale, can cause respiratory system irritation.  
coughing
- **Ingestion:** May be fatal if swallowed and enter airways.
- **Sensitization:** May produce an allergic reaction.

(Contd. on page 10)

-NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 9)

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

The product can cause inheritable damage.

· **IARC (International Agency for Research on Cancer)**

|          |                 |    |
|----------|-----------------|----|
| 111-76-2 | 2-butoxyethanol | 3  |
| 98-82-8  | cumene          | 2B |
| 71-43-2  | benzene         | 1  |
| 91-20-3  | naphthalene     | 2B |

· **NTP (National Toxicology Program)**

|         |             |   |
|---------|-------------|---|
| 98-82-8 | cumene      | R |
| 71-43-2 | benzene     | K |
| 91-20-3 | naphthalene | R |

· **OSHA-Ca (Occupational Safety & Health Administration)**

|         |         |  |
|---------|---------|--|
| 71-43-2 | benzene |  |
|---------|---------|--|

**12 Ecological information**· **Toxicity**

- **Aquatic toxicity:** Harmful to aquatic life with long lasting effects.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

· **Bioaccumulative potential**

|                                     |                          |
|-------------------------------------|--------------------------|
| <b>108-11-2 4-methylpentan-2-ol</b> |                          |
| Bioaccumulation                     | 1.43 (-) (potential low) |

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

· **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** Avoid release to the environment.

NA

(Contd. on page 11)

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022



Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 10)

### 13 Disposal considerations

- **Waste treatment methods**
  - **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
  - **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

|  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> <li>· <b>TDG</b></li> </ul>  | <p>UN1993<br/>UN1993</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>TDG</b></li> <li>· <b>IMDG, IATA</b></li> </ul>  | <p>Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light arom., Benzene, Methyl isobutyl carbinol, Isopropylbenzene)</p> <p>Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light arom., Methyl isobutyl carbinol, 2-butoxyethanol)</p> <p>FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum), light arom., BENZENE, METHYL ISOBUTYL CARBINOL, ISOPROPYL BENZENE)</p> |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> <li>  </li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> <li>· <b>TDG</b></li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul> | <p>3 Flammable liquids<br/>3</p> <p>3 Flammables<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· <b>IMDG, IATA</b></li> <li>  </li> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | <p>3 Flammable liquids<br/>3</p>   |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, IMDG, IATA</b></li> </ul>   | <p>III</p>   |

(Contd. on page 12)

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

**Trade name: Carboclean MV3 Fuel System Cleaner**

(Contd. of page 11)

|   |  |
|---|--|
| · TDG   | III  |
| · Environmental hazards:  |  |
| · Marine pollutant:   | No   |
| · Special precautions for user  | Warning: Flammable liquids   |
| · Hazard identification number (Kemler code):                             | 30   |
| · EMS Number:   | F-E, S-E   |
| · Stowage Category  | A  |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable.  |
| · Transport/Additional information:                                       |  |
| · IMDG  |  |
| · Limited quantities (LQ)   | 5L   |
| · Excepted quantities (EQ)  | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml                         |
| · UN "Model Regulation":  | UN 1993 FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM., BENZENE, METHYL ISOBUTYL CARBINOL, ISOPROPYLBENZENE), 3, III |

**15 Regulatory information**

## · Safety, health and environmental regulations/legislation specific for the substance or mixture

No REACH Annex XVII restrictions

Contains no REACH candidate substance

## · Sara

## · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

## · Section 313 (Specific toxic chemical listings):

|          |                 |
|----------|-----------------|
| 111-76-2 | 2-butoxyethanol |
| 98-82-8  | cumene          |
| 71-43-2  | benzene         |
| 91-20-3  | naphthalene     |

## · TSCA (Toxic Substances Control Act):

|            |  |        |
|------------|--|--------|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | ACTIVE |
| 64742-94-5 | Solvent naphtha (petroleum), heavy arom. | ACTIVE |
| 108-11-2   | 4-methylpentan-2-ol                      | ACTIVE |
| 111-76-2   | 2-butoxyethanol                          | ACTIVE |
| 98-82-8    | cumene                                   | ACTIVE |
| 71-43-2    | benzene                                  | ACTIVE |

(Contd. on page 13)

-NA

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 12)

|         |             |        |
|---------|-------------|--------|
| 91-20-3 | naphthalene | ACTIVE |
|---------|-------------|--------|

· **Proposition 65**· **Chemicals known to cause cancer:**

|         |             |
|---------|-------------|
| 98-82-8 | cumene      |
| 71-43-2 | benzene     |
| 91-20-3 | naphthalene |

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

|         |         |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Chemicals known to cause developmental toxicity:**

|         |         |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

|          |                 |        |
|----------|-----------------|--------|
| 111-76-2 | 2-butoxyethanol | NL     |
| 98-82-8  | cumene          | D, CBD |
| 71-43-2  | benzene         | A, K/L |
| 91-20-3  | naphthalene     | C, CBD |

· **TLV (Threshold Limit Value)**

|          |                 |    |
|----------|-----------------|----|
| 111-76-2 | 2-butoxyethanol | A3 |
| 71-43-2  | benzene         | A1 |
| 91-20-3  | naphthalene     | A4 |

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

|         |         |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Canadian substance listings:**· **Canadian Domestic Substances List (DSL)**

|            |  |
|------------|--|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. |
| 64742-94-5 | Solvent naphtha (petroleum), heavy arom. |
| 108-11-2   | 4-methylpentan-2-ol                      |
| 111-76-2   | 2-butoxyethanol                          |
| 98-82-8    | cumene                                   |
| 71-43-2    | benzene                                  |
| 91-20-3    | naphthalene                              |

· **Canadian Non-Domestic Substances List (NDSL)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

|         |         |
|---------|---------|
| 71-43-2 | benzene |
|---------|---------|

· **Canadian Ingredient Disclosure list (limit 1%)**

|          |                     |
|----------|---------------------|
| 108-11-2 | 4-methylpentan-2-ol |
| 111-76-2 | 2-butoxyethanol     |

(Contd. on page 14)

## Safety Data Sheet

Issue date: 17.03.2022

v 4

Last Revision Date: 17.03.2022

Trade name: **Carboclean MV3 Fuel System Cleaner**

(Contd. of page 13)

98-82-8 cumene

**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

Engineering Department  
Engineering Department

· **Issue Date**

17.03.2022  
2015/12/18

· **Revision Changes:**

v 1.0 - original SDS release (2015/08/27)  
v 2.0 - modification to section 9, added VOC content (2015/12/18)  
v 3.0 - revised (2015/08/23)

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
Flammable Liquids 3: Flammable liquids – Category 3  
Acute Toxicity - Inhalation 4: Acute toxicity – Category 4  
Skin Irritation 2: Skin corrosion/irritation – Category 2  
Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A  
Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B  
Carcinogenicity 1A: Carcinogenicity – Category 1A  
Aspiration Hazard 1: Aspiration hazard – Category 1  
Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· \* **Data compared to the previous version altered.**

NA