Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

1 Identification

- · Product identifier
 - Trade name: CarbonClean Gas/Petrol Injection Cleaner

· Part number: 400-2001, 400-2001EU

Details of the supplier of the safety data sheet

CPS Product Inc. - USA
1010 East 31st Street
Hialeah, FL 33013 USA
Phone: (305) 687 - 4121
Email: cs@cpsproducts.com
· Manufacturer/Supplier:
CPS Product Inc - USA

1010 East 31st Street
Hialeah, FL 33013 USA

Contact Phone: (305) 687-4121

- · email of person responsible: cs@cpsproducts.com
- · Emergency telephone number:

CHEMTREC International +1 (703) 527-3887 (outside the US), 1-800-424-9300 (in the US) 24 hr

2 Hazard(s) identification

· Classification of the substance or mixture

Flammable Liquids 3 H226 Flammable liquid and vapor.

Skin Irritiation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Germ Cell Mutagenicity 1B H340 May cause genetic defects.

Carcinogenicity 1B H350 May cause cancer.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause genetic defects.

(Contd. on page 2)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 1)

May cause cancer.

May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

· Precautionary statements

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep cool.

Dispose of contents in accordance with local regulations.

· Additional information:

For Professional Use Only

Restricted to professional users.

· Other hazards

PBT: Not applicable.vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Chemical components:		
	Solvent naphtha (petroleum), light arom.	50-100%
111-76-2	2-butoxyethanol	10-25%
64741-86-2	Distillates (petroleum), sweetened middle	2.5-10%
	n,n'-Disalicylidene-1,2-propanediamine	≤2.5%
61791-44-4	Ethanol, 2,2'-iminobis-, N-tallow alkylderivs.	≤2.5%
91-20-3	naphthalene	≤2.5%
100-41-4	ethylbenzene	≤2.5%
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	≤2.5%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

(Contd. on page 3)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 2)

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Rinse cautiously with water. Remove contact lenses, if present and easy to do. Get medical attention if eve irritation develops or persists.

After swallowing:

A person vomiting while lying on their back should be turned onto their side.

Rinse mouth with water.

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

If conscious, give small quantities of water to drink.

Stop if victim feels sick.

Do not induce vomitting.

If symptoms persist consult doctor.

· Information for doctor:

Most important symptoms and effects, both acute and delayed

May cause eye irritation. Symptons may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.

Headache

Dizziness

Disorientation

Coughing

Nausea

Harmful if swallowed. May be fatal if swallowed and enters airways. Swallowing a small quantity of this material will result in serious health hazard.

May cause respiratory tract irritation.

May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

See section 11.

· Indication of any immediate medical attention and special treatment needed

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Treat Symptomatically

5 Fire-fighting measures

· Extinguishing media

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture See section 10 for additional information.
- Advice for firefighters

· Protective equipment:

Wear full protective firegear including self-containing breathing apparatus operated in the positive pressure mode with full facepiece, coat, pants, gloves and boots. Do not use a water jet.

NA

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Particular danger of slipping on leaked/spilled product.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Do not touch or walk through spilled material.

· Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No smoking.

Prevent from spreading (e.g. by damming-in or oil barriers).

Take precautions to avoid release to the environment. Prevent from entering into soil, ditches, sewers, waterways and/or groundwater.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Open and handle receptacle with care.

Use only in well ventilated areas.

Avoid contact with the eyes and skin.

Avoid contact with clothing.

Avoid splashes or spray in enclosed areas.

Keep in the original containers.

See section 8 for personal protective equipment.

Do not reuse container.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

See section 10 for incompatible materials.

See section 10 for incompatible materials.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

· Specific end use(s) No further relevant information available.

(Contd. of page 4)

Control para	nts with limit values that require monitoring at the workplace:
-	utoxyethanol (10-25%)
PEL (USA)	TWA: 240 mg/m³, 50 ppm Skin
REL (USA)	TWA: 24 mg/m³, 5 ppm Skin
TLV (USA)	TWA: 20 ppm BEI, A3
EL (Canada)	TWA: 20 ppm
,	TWA: 20 ppm Skin
91-20-3 naph	thalene (≤2.5%)
PEL (USA)	TWA: 50 mg/m³, 10 ppm
REL (USA)	STEL: 75 mg/m³, 15 ppm TWA: 50 mg/m³, 10 ppm
TLV (USA)	TWA: 10 ppm Skin; BEI, A3
EL (Canada)	TWA: 10 ppm Skin; IARC 2B
EV (Canada)	STEL: 78 mg/m³, 15 ppm TWA: 52 mg/m³, 10 ppm
100-41-4 ethy	ylbenzene (≤2.5%)
PEL (USA)	TWA: 435 mg/m³, 100 ppm
REL (USA)	STEL: 545 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm
TLV (USA)	TWA: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3
EL (Canada)	TWA: 20 ppm IARC 2B
EV (Canada)	STEL: 540 mg/m³, 125 ppm TWA: 435 mg/m³, 100 ppm
· Ingr	redients with biological limit values:
_	utoxyethanol (10-25%)
	00 mg/g creatinine
	edium: urine me: end of shift

NA

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 5)

91-20-3 naphthalene (≤2.5%)

BEI (USA) -

Medium: -

Time: end of shift

Parameter: 1-Naphthol with hydrolysis + 2-Naphthol with hydrolysis (Nq,Ns)

100-41-4 ethylbenzene (≤2.5%)

BEI (USA) 0.15 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:





Chemical resistant protective gloves

· Eye protection:



Safety glasses. If potential for splash or mist exists, wear chemical goggles or faceshield.

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
 - · General Information
 - · Appearance:

· Form: Liquid

· Color: yellow to light orange

· Odor: Characteristic · Odor threshold: Not determined.

· **pH-value:** Not determined.

(Contd. on page 7)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

	(Contd. of page
· Change in condition · Melting point/Melting range: · Boiling point/Boiling range:	Undetermined. 162°C
· Flash point:	45 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosi air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	0.7 Vol %
· Upper:	10.6 Vol %
· Vapor pressure at 20 °C:	5 hPa
· Density:	Not determined.
Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity:	
· Dynamic:	Not determined.
· Kinematic:	Not determined.
Solvent separation test VOC content:	92.00 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided:

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid Heat, open flames, sparks.
- Incompatible materials: Strong Oxidizers, strong acids.
- · Hazardous decomposition products: May include, and are not limited to: oxides of carbon.

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 7)

11 Toxicological information

- · Information on toxicological effects

· Acute	toxicity:		
· LD/	· LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)			
Oral	LD50	4,303 mg/kg	
Dermal	LD50	13,333 mg/kg	
Inhalative	LC50/4 h (vapor)	>10.2 mg/L	
64742-95-	6 Solvent naphth	a (petroleum), light arom.	
Oral	LD50	>6,800 mg/kg (rat)	
Dermal	LD50	>3,400 mg/kg (rab)	
Inhalative	LC50/4 h (vapor)	>10.2 mg/L (rat)	
111-76-2	2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE)	
		1,414 mg/kg (gpg)	
Dermal	LD50	2,000 mg/kg (gpg)	
Inhalative	LC50/4 h (vapor)	11.5 mg/L (gpg)	
64741-86-	2 Distillates (petr	oleum), sweetened middle	
Inhalative	LC50/4 h (vapor)	4.6 mg/L (rat)	
94-91-7 n,	n'-Disalicylidene	-1,2-propanediamine	
Oral	LD50	1,350 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rat)	
61791-44-	4 Ethanol, 2,2'-in	ninobis-, N-tallow alkylderivs.	
Oral	LD50	100 mg/kg (ATE)	
	91-20-3 naphthalene		
Oral	LD50	490 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
100-41-4 ethylbenzene			
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	17,800 mg/kg (rabbit)	
Inhalative	LC50/4 h (vapor)	17.8 mg/L (rat)	
	and invitant offer		

- · Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye:

Irritating effect.

May cause eye irritation. Symptons may include discomfort or pain, excessive blinking and tear production, with possible redness and swelling.

Inhalation:

Do not inhale, can cause respiratory system irritation. coughing

· Ingestion: May be fatal if swallowed and enter airways.

(Contd. on page 9)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 8)

· Sensitization:

May produce an allergic reaction.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

The product can cause inheritable damage.

	adot our oudoo milonable damage.		
· 1/	ARC (International Agency for Research on Cancer)		
111-76-2	2-butoxyethanol	3	
91-20-3	naphthalene	2B	
100-41-4	ethylbenzene	2B	
1330-20-7	xylene	3	
· N	ITP (National Toxicology Program)		
91-20-3 na	91-20-3 naphthalene		
· C	SHA-Ca (Occupational Safety & Health Administration)		
None of the	e ingredients is listed.		

12 Ecological information

- · Toxicity
 - · Aquatic toxicity: Harmful to aquatic life with long lasting effects.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
 - · Remark: Harmful to fish
- · Additional ecological information:
 - · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
 - · **PBT:** Not applicable.
 - · vPvB: Not applicable.
- Other adverse effects Avoid release to the environment.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 10)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 9)

· Uncleaned packagings:
· Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, ADR, IMDG, IATA	UN1993
· UN proper shipping name · DOT	Flammable liquids, n.o.s. (Solvent naphth (petroleum), light arom.)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Solvent naphth (petroleum), light arom.)
· Transport hazard class(es)	
· DOT	
FLAMMARE LOUID	
· Class · Label	3 Flammable liquids3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
 Hazard identification number (K EMS Number: 	F-E,S-E
Stowage Category	A A
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 3

(Contd. on page 11)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

(Contd. of page 10)

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.), 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No REACH Annex XVII restrictions Contains no REACH candidate substance

· Sara

· S	· Section 355 (extremely hazardous substances):		
None of the	None of the ingredients is listed.		
· S	· Section 313 (Specific toxic chemical listings):		
111-76-2	2-butoxyethanol		
91-20-3	naphthalene		
95-63-6	1,2,4-trimethylbenzene		
100-41-4	ethylbenzene		
1330-20-7	xylene		
· TSC	· TSCA (Toxic Substances Control Act):		

TOOM (TOXIO CUBStances Control A

All components have the value ACTIVE.

· Proposition 65

	Chemicals known to cause cancer:		
91-20-3	naphthalene		
100-41-4	ethylbenzene		
	. Chamicala known to course reproductive toxicity for famalace		

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· E	PA (Environmental Protection Agency)		
111-76-2	2-butoxyethanol	NL	
	naphthalene	C, C	BD
95-63-6	1,2,4-trimethylbenzene	П	
100-41-4	ethylbenzene	D	
1330-20-7	xylene	I	
• Т	LV (Threshold Limit Value)		
111-76-2	2-butoxyethanol		A3
			- 4

(Contd. on page 12)

Issue date: 23.03.2022 v 2 Last Revision Date: 23.03.2022

Trade name: CarbonClean Gas/Petrol Injection Cleaner

		(Contd. of page 11)
91-20-3	naphthalene	A4
100-41-4	t ethylbenzene	A3
1330-20-7	zylene	A4
	NIOSH-Ca (National Institute for Occupational Safety and Health)	·
None of the	ne ingredients is listed.	
· Ca	nadian substance listings:	
	Canadian Domestic Substances List (DSL)	
All ingred	ents are listed.	
	Canadian Non-Domestic Substances List (NDSL)	
None of the	ne ingredients is listed.	
	Canadian Ingredient Disclosure list (limit 0.1%)	
95-63-6	1,2,4-trimethylbenzene	
100-41-4	ethylbenzene	
	Canadian Ingredient Disclosure list (limit 1%)	
111-76-2	2-butoxyethanol	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact: Engineering Department
 - · Issue Date

23.03.2022

08/SEP/2016

· Revision Changes:

v 1.0 - initial SDS release (25/JUN/2015)

v 2.0 - revised (08/SEP/2016)

Abbreviations and acronyms:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irrititation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Sensitization - Skin 1: Skin sensitisation - Category 1

Germ Cell Mutagenicity 1B: Germ cell mutagenicity - Category 1B

Carcinogenicity 1B: Carcinogenicity - Category 1B

Aspiration Hazard 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.